US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
YINNZ (IAF)	POOBA (FB)	036.84 / 8.90	4000
POOBA (IF)	PENCL (FB)	094.76 / 6.28	4000
PENCL	ZMANN (FB)	094.84 / 2.99	4000
ZMANN	DAELE (FB)	094.87 / 4.10	2700
DAELE (FAF)	WOMTO/2.50 NM TO RW10 (FB)	094.91 / 2.66	
WOMTO/2.50 NM TO RW10	RW10 (MAP) (FO)	094.94 / 2.50	
(SEE FORM 8260-10)			

MISSED APPROACH

LPV: DA
LNAV/VNAV: DA
LNAV: RW10

CLIMB TO 1600 THEN CLIMBING RIGHT TURN TO 3000 DIRECT SCARR AND HOLD.

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. PROFILE STARTS AT POOBA
3. FAC: 094.91 FAF: DAELE DIST FAF TO MAP: 5.16 THLD: 5.16
4. MIN. ALT: POOBA 4000, PENCL 4000, ZMANN 4000, DAELE 2700, WOMTO/2.50 NM TO RW10 1840*
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: 2700 GS ALT AT: DAELE 2700 OM: ____ MM: ____ IM: ____
7. GS ANGLE: 3.00 TCH: 57.8 34:1 IS CLEAR
8. MSA FROM: RW10 3100

ADDITIONAL FLIGHT DATA:
HOLD S, RT, 005.00 INBOUND.
CHART FAS OBST: 1219 TOWER 333747N/0842909W
DISTANCE TO THLD FROM 200 HATH: 0.45 NM.
CHART VDP AT 1.32 MILES TO RW10*
*LNAV ONLY.
WAAS CHANNEL # 40399
REFERENCE PATH ID: W10A
LTP HAE: 275.5 M
CHART LOC RWY 8 L/R AND RWY 9L/R.

MAG VAR: 5W EPOCH YEAR: 2015

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A STANDARD

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1200	2400	200	1200	2400	200	1200	2400	200	1200	2400	200			
LNAV/VNAV DA	1540	1 3/8	540	1540	1 3/8	540	1540	1 3/8	540	1540	1 3/8	540			
LNAV MDA	1480	2400	480	1480	2400	480	1480	5000	480	1480	5000	480			

NOTES:
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART PLANVIEW NOTE: RADAR REQUIRED.
CHART NOTE: FOR INOPERATIVE ALSF-2, INCREASE LNAV/VNAV ALL CATS AND LNAV CAT C AND D VISIBILITY
(SEE FORM 8260-10)

CITY AND STATE	ELEVATION: 1026 THRE: 1000 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
ATLANTA, GA	HARTSFIELD - JACKSON ATLANTA INTL	RNAV	RNAV (GPS) Y RWY 10, AMDT 2B, 11/15/2012	AMDT: 2A DATED 03/08/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
[ ] YES [X] NO		11/15/2012

COORDINATED WITH:

ATA	AAT	ALPA	APA	AOPA	NBAA	OTHER (specify)
X		X	X	X	X	X ZTL, ATL APP CON, MCN FSS, AIRPORT MANAGER

FLIGHT CHECKED BY		
NAME: DEREK ROSS MILLER	FIFO FIOG	DATE: 03/14/2011
DEVELOPED BY		
NAME: KELLY DEAN	FIFO AJV-352	DATE: 05/18/2012
APPROVED BY		
NAME: DARRYEL ADAMS MANAGER	FIFO AJV-352	DATE:

CHANGES:

1. LINE 3 FAC CHANGED FROM 091.91 TO 094.91.
2. MISSED APPROACH HODING COURSE CHANGED FROM 002/182 TO 005/185.
3. POOBA CHANGED FROM IAF TO IF, IF MOVED FROM PENCIL TO POOBA.
4. TERMINAL ROUTE FROM YINNZ (IAF) TO POOBA COURSE AND DISTANCE CHANGED FROM 033.84 / 8.90 TO 036.84 / 8.90.
5. TERMINAL ROUTE FROM POOBA (IF) TO PENCIL COURSE AND DISTANCE CHANGED FROM 091.76 / 6.28 TO 094.76 / 6.28.
6. TERMINAL ROUTE FROM PENCIL TO ZMANN COURSE AND DISTANCE CHANGED FROM 091.84 / 2.99 TO 094.84 / 2.99.
7. TERMINAL ROUTE FROM ZMANN TO DAELE COURSE AND DISTANCE CHANGED FROM 091.87 / 4.10 TO 094.87 / 2.99.
8. TERMINAL ROUTE FROM DAELE (FAF) TO WOMTO/2.50 NM TO RWY 10 COURSE AND DISTANCE CHANGED FROM 091.91 / 2.66 TO 094.91 / 2.66.
9. CHANGED HIGH TEMP LIMITATION FROM 37C (98F) TO 54C (130F).

REASONS:

1., 4., 5., 6., 7., 8. KATL MAG/VAR CHANGED FROM 2W TO 5W.
2. ATL VORTC MAG/VAR CHANGED FROM 0W TO 5W.
3. CODING AND MATCH OTHER PROCEDURES TO RWY 10.
9. NEW EMAIL GUIDANCE.

8/24/12: THIS IS A CORRECT COPY OF THE FORM APPROVED ON 8/20/12.

1. 8260-10 PAGES 4-6 CHANGED AIRPORT NAME FROM HARTSFIELD-JACKSON ATLANTA I TO HARTSFIELD-JACKSON ATLANTA INTL.

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW10 (MAP)	1600 MSL	094.94	1600
1600 MSL	SCARR (FO)		3000

NOTES, (CONT.):
3/8 MILE.
CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH ILS OR LOC RWY 8L, ILS RWY 8L (CAT II), ILS RWY 8L (CAT III), ILS OR LOC RWY 8R, ILS RWY 8R (CAT II), ILS RWY 8R (CAT III), RWY 9L, RWY 9R.
CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.
CHART NOTE: LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS.

QUALITY CHECKED

CITY AND STATE	ELEVATION: 1026 THRE: 1000	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
ATLANTA, GA	AIRPORT NAME: HARTSFIELD - JACKSON ATLANTA INTL	RNAV	RNAV (GPS) Y RWY 10, AMDT 2B, 11/15/2012	AMDT: 2A
				DATED: 03/08/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	FIFO	DATE:
APPROVED BY		
NAME:	FIFO	DATE:

CHANGES:

REASONS:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD	DATA
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KATL
RUNWAY	RW10
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W10A
LTP/FTP LATITUDE	333712.9830N
LTP/FTP LONGITUDE	0842652.3560W
LTP/FTP ELLIPSOIDAL HEIGHT	+02755
FPAP LATITUDE	333713.0100N
FPAP LONGITUDE	0842505.6600W
THRESHOLD CROSSING HEIGHT (TCH)	00057.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0008
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
CRC REMAINDER	7BD6C24F

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+03049
FPAP ORTHOMETRIC HEIGHT	+03049

QUALITY CHECKED

CITY AND STATE	ELEVATION: 1026 THRE: 1000	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
ATLANTA, GA	AIRPORT NAME: HARTSFIELD - JACKSON ATLANTA INTL	RNAV	RNAV (GPS) Y RWY 10, AMDT 2B, 11/15/2012	AMDT: 2A
				DATED: 03/08/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	FIFO	DATE:
APPROVED BY		
NAME:	FIFO	DATE:

CHANGES:

REASONS:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - **FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
WP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAEAENRT   DAELE K70    C     N33371266W084330279                    W0046     NAR           DAELE
        SUSAEAENRT   PENCL K70    C     N33371173W084413216                    W0045     NAR           PENCL
        SUSAEAENRT   POOBA K70    C     N33371041W084490342                    W0044     NAR           POOBA
        SUSAEAENRT   SCARR K70    C   L N33224310W084260625                    W0046     NAR           SCARR
        SUSAEAENRT   WOMTO K70    W     N33371287W084295198                    W0046     NAR           WOMTO
        SUSAEAENRT   YINNZ K70    C     N33293627W084544065                    W0043     NAR           YINNZ
        SUSAEAENRT   ZMANN K70    C     N33371219W084375769                    W0045     NAR           ZMANN

                 1         2         3         4         5         6         7         8         9         0         1         2         3
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KATLK7AATL     0     118YHN33381212W084254031W005001026         1800018000C    MNAR    HARTSFIELD - JACKSON ATLANTA I

                 1         2         3         4         5         6         7         8         9         0         1         2         3
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KATLK7FR10-Y AYINNZ 010YINNZK7EA0E  A    IF                                          18000                A JS
        SUSAP KATLK7FR10-Y AYINNZ 020POOBAK7EA0EE B 010TF                    03680089    + 04000                         A JS
        SUSAP KATLK7FR10-Y R      010POOBAK7EA0E  I    IF                               + 04000     18000                A JS
        SUSAP KATLK7FR10-Y R      011PENCLK7EA0E S  051TF                    09480063    + 04000                         A JS
        SUSAP KATLK7FR10-Y R      012ZMANNK7EA0E S  051TF                    09480030    + 04000                         A JS
        SUSAP KATLK7FR10-Y R      020DAELEK7EA1E  F 051TF                    09490041    + 02700                 RW10  K7PGA JS
        SUSAP KATLK7FR10-Y R      020DAELEK7EA2WALPV       ALNAV/VNAV ALNAV                                                JS
        SUSAP KATLK7FR10-Y R      021WOMTOK7EA0E S  031TF                    09490027    V 0184001854        -300         A JS
        SUSAP KATLK7FR10-Y R      030RW10 K7PG0GY M 031TF                    09490025      01058             -300         A JS
        SUSAP KATLK7FR10-Y R      040         0  M     CA                    0949        + 01600                         A JS
        SUSAP KATLK7FR10-Y R      050SCARRK7EA0EY  R   DF                                + 03000                         A JS
        SUSAP KATLK7FR10-Y R      060SCARRK7EA0EE  R   HM                    00500040    + 03000                         A JS

                 1         2         3         4         5         6         7         8         9         0         1         2         3
RUNWAY  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KATLK7GRW10    0090000950 N33371298W084265236+0000    +0275501000000058150I

                 1         2         3         4         5         6         7         8         9         0         1         2         3
PP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KATLK7PR10-Y RW10 001Y0000W10A0N3337129830W08426523560+027550300N3337130100W084250566001067500080005 78F4003507BD6C24F
        SUSAP KATLK7PR10-Y RW10 002E      +03049+03049LPV       40399

                 1         2         3         4         5         6         7         8         9         0         1         2         3
```

CITY AND STATE	ELEVATION: 1026 THRE: 1000	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
ATLANTA, GA	AIRPORT NAME: **HARTSFIELD - JACKSON ATLANTA INTL**	**RNAV**	**RNAV (GPS) Y RWY 10, AMDT 2B, 11/15/2012**	AMDT: **2A**
				DATED: **03/08/2012**

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	NFPG	DATE:
APPROVED BY		
NAME:	NFPG	DATE:

CHANGES:

REASONS:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

```
MSA     123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------
        SUSAP KATLK7SRW10 K7PG                0   18018003125                                                                      M
```

CITY AND STATE	ELEVATION: 1026 THRE: 1000	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
ATLANTA, GA	AIRPORT NAME: HARTSFIELD - JACKSON ATLANTA INTL	RNAV	RNAV (GPS) Y RWY 10, AMDT 2B, 11/15/2012	AMDT: 2A
				DATED: 03/08/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	NFPG	DATE:
APPROVED BY		
NAME:	NFPG	DATE:

CHANGES:

REASONS:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	YINNZ	YINNZ	010	IAF	IF		FB					
	YINNZ	POOBA	020		TF		FB	1.0	036.8(031.8T)	008.9	AA 04000	
		POOBA	010	FACF	IF		FB				AA 04000	
		PENCL	011	SDF	TF		FB	0.5	094.8(089.8T)	006.3	AA 04000	
		ZMANN	012	SDF	TF		FB	0.5	094.8(089.8T)	003.0	AA 04000	
		DAELE	020	FAF	TF		FB	0.5	094.9(089.9T)	004.1	AA 02700	
		WOMTO	021	SDF	TF		FB	0.3	094.9(089.9T)	002.7	AA 01840 GS 01854	
		RW10	030	MAP	TF		FO	0.3	094.9(089.9T)	002.5	AT 01058	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		094.9(089.9T)		AA 01600	
	SCARR	050		DF	R	FO				AA 03000	
	SCARR	060		HM	R	FO		005.0(360.0T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DAELE	N333712.66	W0843302.79	N3337.211	W08433.047
	PENCL	N333711.73	W0844132.16	N3337.196	W08441.536
	POOBA	N333710.41	W0844903.42	N3337.174	W08449.057
	SCARR	N332243.10	W0842606.25	N3322.718	W08426.104
	WOMTO	N333712.87	W0842951.98	N3337.215	W08429.866
	YINNZ	N332936.27	W0845440.65	N3329.605	W08454.678
	ZMANN	N333712.19	W0843757.69	N3337.203	W08437.962
	RW10	N333712.98	W0842652.36	N3337.216	W08426.873

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW10	01000	58

CITY AND STATE	ELEVATION: 1026	THRE: 1000	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
ATLANTA, GA	AIRPORT NAME: HARTSFIELD - JACKSON ATLANTA INTL		RNAV	RNAV (GPS) Y RWY 10, AMDT 2B, 11/15/2012	AMDT: 2A
					DATED: 03/08/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	NFPG	DATE:
APPROVED BY		
NAME:	NFPG	DATE:

CHANGES:

REASONS:

STANDARD INSTRUMENT APPROACH PROCEDURE DATA RECORD

PART - A OBSTRUCTION DATA

1. APP SEGMENT	FROM	TO	OBSTRUCTION	COORDINATES	ELEV. MSL	ROC	ALT. ADJUSTMENTS	MIN. ALT.
INITIAL	YINNZ	POOBA	1. AAO	333515.00N/0845221.00W	1399 (2C)	1000	AT1601	4000
			2. TERRAIN	333515.00N/0845221.00W	1199 (1200)		AS1500	2700
INTERMEDIATE	POOBA	PENCL	3. TOWER (13-002285)	333744.00N/0845013.00W	1229 (5E)	500	AT2271	4000
			4. TERRAIN	333842.00N/0844936.00W	1047 (1000)		AS1500	2500
INTERMEDIATE:	PENCL	ZMANN	5. AAO	333721.00N/0844006.00W	1199 (2C)	500	AT2301	4000
STEPDOWN			6. TERRAIN	333721.00N/0844006.00W	999 (1000)		AS1500	2500
INTERMEDIATE:	ZMANN	DAELE	7. TOWER (13-002289)	333609.00N/0843317.00W	1331 (5E)	500	AC125 AT744	2700
STEPDOWN			8. TERRAIN	333609.00N/0843317.00W	1031 (1000)		AS1500	2500
FINAL: LPV	DAELE	RW10				ASC		1200/200
FINAL: LNAV/VNAV	DAELE	RW10	9. TANK (13-000253)	333739.00N/0842803.00W	1186 (4D)	23.4:1	AC50	1540/540
FINAL: LNAV	DAELE	WOMTO/2.50 NM TO RW10	7. TOWER (13-002289)	333609.00N/0843317.00W	1331 (5E)	250	AC125 DG134	1840
FINAL: LNAV STEPDOWN	WOMTO/2.50 NM TO RW10	RW10	10. TOWER (13-000058)	333747.00N/0842909.00W	1219 (2A)	250		1480
2. PROCEDURE TURN	NA							
3. MISSED APPROACH MAP:	DA / DA / RW10	SCARR				ASC		3000
			11. TOWER (13-001628)	332719.00N/0842435.00W	1387 (2C)	1000		2400
ELEV:	1031/1379/1380		12. TERRAIN	333609.00N/0842118.00W	1023 (1000)		AS1500	2500

4. CIRCLING AREA	DISTANCE	HT. ABV. ARPT. REQUIRED	HT. ABV. ARPT. ACTUAL
CATEGORY A	1.3 NM	350	
CATEGORY B	1.5 NM	450	
CATEGORY C	1.7 NM	450	
CATEGORY D	2.3 NM	550	
CATEGORY E	4.5 NM	550	

5. MINIMUM SAFE ALTITUDES — PRIMARY NAVAID: RW10

SECTOR	OBSTRUCTION	BRG/DIST	ELEVATION (MSL)	M S A	SECTOR	OBSTRUCTION	BRG/DIST	ELEVATION (MSL)	M S A
360-360	TWR (13-000006)	033/ 12.1	2049 (5D)	3100					

CITY AND STATE	ELEVATION: 1026 / AIRPORT NAME:	FACILITY	PROCEDURE AND AMENDMENT NO:	REGION
ATLANTA, GA	HARTSFIELD - JACKSON ATLANTA INTL	RNAV	RNAV (GPS) Y RWY 10, AMDT 2B, 11/15/2012	ASO

PART B - SUPPLEMENTAL DATA

1. COMMUNICATIONS WITH:	2. WEATHER SERVICE			3. ALTIMETER SETTING
ATL APP CON ATL TOWER		N W S	OTHER: ASOS	SOURCE: KATL
		F A A		DISTANCE:
SATISFACTORY ON:		A / C		HOURS REMOTE OPERATION:
X V H F X U H F H F	LOCATION:			ADJUSTMENT: 0

4. MONITOR STATUS	PRIMARY NAVAID:	
	MONITOR POINT:	
	HRS OPTN: CAT 1	
	HRS OPTN: CAT 3	
5. APPROACH & RUNWAY LIGHTING	X	ALSF-2 10, 28, 08L, 27L, 09R
		(S) SALS
	X	MALS 27R MALSR 09L, 26L, 26R
	X	HIRL 09L, 10, 28, 08L, 08R, 27L, 26L, 26R, 09R, 27R
		MIRL
		REIL
	X	TDZ 10, 28, 08L, 27L, 26R, 09R
	X	C/L 09L, 10, 28, 08L, 08R, 27L, 26L, 26R, 09R, 27R
	X	OTHER (SPECIFY) PAPI-4R 09L, 27L, 27R PAPI-4L 08L, 08R, 26L, 26R, 09R
6. RUNWAY MARKINGS	BASIC	
	ALL WEATHER	PIR-G 09L, 10, 28, 08L, 08R, 27L, 26L, 26R, 09R, 27R
	INSTRUMENT	
7. RUNWAY VISUAL RANGE	APPROACH	09L, 10, 28, 08L, 08R, 27L, 26L, 26R, 09R, 27R
	MIDFIELD	09L, 10, 28, 08L, 08R, 27L, 26L, 26R, 09R, 27R
	ROLL OUT	09L, 10, 28, 08L, 08R, 27L, 26L, 26R, 09R, 27R
8. GLIDE PATH	GP ANGLE: 3.00	ELEV RWY THRESHOLD: 1000.3
	DISTANCE FROM RWY:	ELEV GP ANTENNA:
		THRESHOLD CROSSING HEIGHT: 57.8
9. FINAL APPROACH COURSE AIMING	X	RUNWAY THRESHOLD FT. FROM THRESHOLD
	X	ON CENTERLINE FT. FROM CENTERLINE

10. WAIVERS: NONE

PART D - PREPARED BY: KELLY DEAN	DATE: 05/18/2012
TITLE: AERONAUTICAL INFORMATION SPECIALIST	OFFICE: AJV-352

PART C - REMARKS:

FLIGHT CHECK RDH 57.78 FT, (ORDER 8260.3B CHG 19).

PRECIPITOUS TERRAIN EVALUATION COMPLETED.

BACK-UP ALTIMETER NOT REQUIRED DUE TO REDUNDANT LOCAL SOURCES.

NO ADDITIONAL AIRSPACE REQUIRED.

TAA NOT DEVELOPED PER ATL FPO.
CIRCLING NOT AUTHORIZED PER ATC.

LPV
OUTER SURFACE= 34:1
LNAV/VNAV
INNER SURFACE=23.4:1
OUTER SURFACE=34:1

ISA DEVIATION -30

QUALITY & CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: DAELE **STATE:** GA **COUNTRY:** US

LATITUDE/LONGITUDE: 333712.66N/0843302.79W **TYPE:** WP, RADAR, DME

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

FIX MAKE-UP FACILITIES:

FAC	NAME	IDENT	TYPE	CLASS	MAG BRG	TRUE BRG	DME	DIST FROM FAC NM	DIST FROM FAC FEET	MRA	MAA
1	ATLANTA	I-OMO	LOC/DME		274.97	269.97	6.80	6.80	41336	2700	5400

HOLDING: **HOLDING TYPE OF ACTION:** NO CHANGE

REMARKS:
ATLANTA (FAC 1) USED TO ESTABLISH FIX COORDINATES

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	ILS OR LOC RWY 10	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT II)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT III)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT II)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT III)	1		KATL	ATLANTA	GA (US)
IAP	RNAV (GPS) Y RWY 10			KATL	ATLANTA	GA (US)
IAP	RNAV (RNP) Z RWY 10			KATL	ATLANTA	GA (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 2 **DATE OF REVISION:** 11/15/2012

REASON FOR REVISION:
CHANGED FAC 1 MAG BRG FROM 273.97 TO 274.97.
UPDATED FIX USE AND REMARKS.

DEVELOPED BY: **DATE:** 05/16/2012 **OFFICE:** AJV-352 **NAME:** KELLY DEAN

APPROVED BY: **DATE:** **OFFICE:** AJV-352 **NAME:** DARRYEL ADAMS

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: EST
ARTCC: ZTL
ATC FACILITY: ATL/ATL
OTHER:

QUALITY CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: PENCL **STATE:** GA **COUNTRY:** US

LATITUDE/LONGITUDE: 333711.73N/0844132.16W **TYPE:** WP, RADAR, DME

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

FIX MAKE-UP FACILITIES:

FAC	NAME	IDENT	TYPE	CLASS	MAG BRG	TRUE BRG	DME	DIST FROM FAC NM	DIST FROM FAC FEET	MRA	MAA
1	ATLANTA	I-OMO	LOC/DME		274.97	269.97	13.89	13.89		2700	5400

HOLDING: **HOLDING TYPE OF ACTION:** NO CHANGE

REMARKS:
ATLANTA (FAC 1) USED TO ESTABLISH FIX COORDINATES

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	ILS OR LOC RWY 10	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT II)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT III)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT II)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT III)	1		KATL	ATLANTA	GA (US)
IAP	RNAV (GPS) Y RWY 10			KATL	ATLANTA	GA (US)
IAP	RNAV (RNP) Z RWY 10			KATL	ATLANTA	GA (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 3 **DATE OF REVISION:** 11/15/2012

REASON FOR REVISION:
CHANGED FAC 1 MAG BRG FROM 273.97 TO 274.97.
UPDATED FIX USE AND REMARKS.

DEVELOPED BY: **DATE:** 05/16/2012 **OFFICE:** AJV-352 **NAME:** KELLY DEAN

APPROVED BY: **DATE:** **OFFICE:** AJV-352 **NAME:** DARRYEL ADAMS

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: EST
ARTCC: ZTL
ATC FACILITY: ATL/ATL
OTHER:

ORIGINAL & CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: POOBA **STATE:** GA **COUNTRY:** US

LATITUDE/LONGITUDE: 333710.41N/0844903.42W **TYPE:** WP, RADAR, DME

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

FIX MAKE-UP FACILITIES:

FAC	NAME	IDENT	TYPE	CLASS	MAG BRG	TRUE BRG	DME	DIST FROM FAC NM	DIST FROM FAC FEET	MRA	MAA
1	ATLANTA	I-OMO	LOC/DME		274.97	269.97	20.17	20.17		2700	5400

EXPANDED SERVICE VOLUME (ESV):

FAC IDENT	FAC TYPE	RADIAL/BEARING	DISTANCE	MIN ALTITUDE	MAX ALTITUDE
I-OMO	LOC/DME	R-275	21	2700	6000

HOLDING: **HOLDING TYPE OF ACTION:** NO CHANGE

REMARKS:
ATLANTA (FAC 1) USED TO ESTABLISH FIX COORDINATES

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	ILS OR LOC RWY 10	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT II)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT III)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT II)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT III)	1		KATL	ATLANTA	GA (US)
IAP	RNAV (GPS) Y RWY 10			KATL	ATLANTA	GA (US)
IAP	RNAV (RNP) Z RWY 10			KATL	ATLANTA	GA (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 3 **DATE OF REVISION:** 11/15/2012

REASON FOR REVISION:
CHANGED FAC 1 MAG BRG FROM 273.97 TO 274.97.
CHANGED ESV RADIAL FROM 274 TO 275.
UPDATED FIX USE AND REMARKS.

DEVELOPED BY: **DATE:** 05/16/2012 **OFFICE:** AJV-352 **NAME:** KELLY DEAN

APPROVED BY: **DATE:** **OFFICE:** AJV-352 **NAME:** DARRYEL ADAMS

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: EST
ARTCC: ZTL
ATC FACILITY: ATL/ATL
OTHER:

RADIO FIX AND HOLDING DATA RECORD

NAME: SCARR **STATE:** GA **COUNTRY:** US

LATITUDE/LONGITUDE: 332243.10N/0842606.25W **TYPE:** WP, INT, DME

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

FIX MAKE-UP FACILITIES:

FAC	NAME	IDENT	TYPE	CLASS	MAG BRG	TRUE BRG	DME	DIST FROM FAC NM	DIST FROM FAC FEET	MRA	MAA
1	ATLANTA	ATL	VORTAC	H	185.00	180.00	15.00	15.00		3000	17500
2	LAGRANGE	LGC	VORTAC	H	061.84	062.84		43.55		3000	17500
3	PEACHTREE	PDK	VOR/DME	L	194.96	192.96	30.54	30.54		3000	17500

EXPANDED SERVICE VOLUME (ESV):

FAC IDENT	FAC TYPE	RADIAL/BEARING	DISTANCE	MIN ALTITUDE	MAX ALTITUDE
LGC	VORTAC	R-062	44	3000	17500

HOLDING: **HOLDING TYPE OF ACTION:** MODIFY

PATTERNS:

PAT	DIR	IDENT	TYPE	RAD/CRS/BRG	CRS INBOUND	TURN (L OR R)	LEG LENGTH TIME	LEG LENGTH DME	HOLDING ALTITUDES MIN	HOLDING ALTITUDES MAX	TEMPLATES MIN	TEMPLATES MAX
1	S	ATL	VORTAC	185.00	005.00	R	1		3000	14000	5	11
2	S		WP	185.00	005.00	R		4	3000	14000	5	11
3	S	PDK	VOR/DME	194.96	014.96	R	1		3000	6000	6	7

CONTROLLING OBSTRUCTIONS:

PAT	AIRSPEED	OBSTRUCTION	COORDINATES	ELEVATION	ACCURACY CODE
1	200	TOWER (13-001628)	332719.00N/0842435.00W	1387	2C
2	200	TOWER (13-001628)	332719.00N/0842435.00W	1387	2C
3	200	TOWER (13-001628)	332719.00N/0842435.00W	1387	2C

HOLDING RESTRICTIONS:
HOLDING LIMITED TO ESTABLISHED PATTERNS.

REMARKS:
ATLANTA (FAC 1) AND LAGRANGE (FAC 2) USED TO ESTABLISH FIX COORDINATES
PRECIPITOUS TERRAIN EVALUATION COMPLETED.

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	ILS OR LOC RWY 10	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS OR LOC RWY 10 (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS OR LOC RWY 28	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS OR LOC RWY 28 (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT II)(SCP)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT II)(SCP) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT III)(SCP)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT III)(SCP) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (SCP)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (SCP) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 28 (CAT II)(SCP)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 28 (CAT II)(SCP) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 28 (SCP)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 28 (SCP) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT II)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT II) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT III)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT III) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (SA CAT 1)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (SA CAT I) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS RWY 28 (CAT II)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS RWY 28 (CAT II) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	ILS RWY 28 (SA CAT 1)	1, 2	1	KATL	ATLANTA	GA (US)
IAP	ILS RWY 28 (SA CAT I) (ALT MISS)	2, 3	3	KATL	ATLANTA	GA (US)
IAP	RNAV (GPS) Y RWY 10		2	KATL	ATLANTA	GA (US)
IAP	RNAV (GPS) Y RWY 28		2	KATL	ATLANTA	GA (US)
IAP	RNAV (RNP) Z RWY 10		2	KATL	ATLANTA	GA (US)
IAP	RNAV (RNP) Z RWY 28		2	KATL	ATLANTA	GA (US)

REQUIRED CHARTING: IAP, AREA, CONTROLLER, EN ROUTE LOW

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 7 **DATE OF REVISION:** 11/15/2012

REASON FOR REVISION:
CHANGED FAC 1 MAG BRG FROM 180 TO 185.
CHANGED HOLDING PATTERN 1 CRS FROM 180/360 TO 185/005.
CHANGED HOLDING PATTERN 2 CRS FROM 182/002 TO 185/005.
UPDATED FIX USE AND REMARKS.

DEVELOPED BY:	**DATE:** 05/16/2012	**OFFICE:** AJV-352	**NAME:** KELLY DEAN
APPROVED BY:	**DATE:**	**OFFICE:** AJV-352	**NAME:** DARRYEL ADAMS
	SIGNATURE:		

DISTRIBUTION:
NFDC
FPO: EST
ARTCC: ZTL
ATC FACILITY: ATL/ATL
OTHER:

INFO ONLY

RADIO FIX AND HOLDING DATA RECORD

NAME: WOMTO **STATE:** GA **COUNTRY:** US

LATITUDE/LONGITUDE: 333712.87N/0842951.98W **TYPE:** WP

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** ESTABLISH

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	RNAV (GPS) Y RWY 10			KATL	ATLANTA	GA (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: ORIG **DATE OF REVISION:** 05/05/2011

DEVELOPED BY: **DATE:** 11/18/2010 **OFFICE:** AVN-110 **NAME:** GEORGETTE BARNETT

APPROVED BY: **DATE:** **OFFICE:** AVN-110 **NAME:** DARRYEL ADAMS

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: EST
ARTCC: ZTL
ATC FACILITY: ATL/ATL
OTHER:

QUALITY CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: YINNZ **STATE:** GA **COUNTRY:** US

LATITUDE/LONGITUDE: 332936.27N/0845440.65W **TYPE:** WP, RADAR, INT, DME

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

FIX MAKE-UP FACILITIES:

FAC	NAME	IDENT	TYPE	CLASS	MAG BRG	TRUE BRG	DME	DIST FROM FAC NM	DIST FROM FAC FEET	MRA	MAA
1	ATLANTA	ATL	VORTAC	H	256.34	251.34	25.22	25.22		4000	17500
2	LAGRANGE	LGC	VORTAC	H	028.06	029.06	30.46	30.46		4000	17500

HOLDING: **HOLDING TYPE OF ACTION:** NO CHANGE

REMARKS:
ATLANTA (FAC 1) AND LAGRANGE (FAC 2) USED TO ESTABLISH FIX COORDINATES

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	ILS OR LOC RWY 10	1, 2		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT II)(SCP)	1, 2		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT III)(SCP)	1, 2		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (SCP)	1, 2		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT II)	1, 2		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT III)	1, 2		KATL	ATLANTA	GA (US)
IAP	RNAV (GPS) Y RWY 10			KATL	ATLANTA	GA (US)
IAP	RNAV (RNP) Z RWY 10			KATL	ATLANTA	GA (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 1 **DATE OF REVISION:** 11/15/2012

REASON FOR REVISION:
CHANGED FAC 1 MAG BRG FROM 251.34 TO 256.34.
UPDATED FIX USE AND REMARKS.

DEVELOPED BY: **DATE:** 05/16/2012 **OFFICE:** AJV-352 **NAME:** KELLY DEAN

APPROVED BY: **DATE:** **OFFICE:** AJV-352 **NAME:** DARRYEL ADAMS

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: EST
ARTCC: ZTL
ATC FACILITY: ATL/ATL
OTHER:

QUALITY CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: ZMANN **STATE:** GA **COUNTRY:** US

LATITUDE/LONGITUDE: 333712.19N/0843757.69W **TYPE:** WP, RADAR, DME

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

FIX MAKE-UP FACILITIES:

FAC	NAME	IDENT	TYPE	CLASS	MAG BRG	TRUE BRG	DME	DIST FROM FAC NM	DIST FROM FAC FEET	MRA	MAA
1	ATLANTA	I-OMO	LOC/DME		274.97	269.97	10.91	10.91		2700	5400

HOLDING: **HOLDING TYPE OF ACTION:** NO CHANGE

REMARKS:
ATLANTA (FAC 1) USED TO ESTABLISH FIX COORDINATES

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	ILS OR LOC RWY 10	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT II)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (CAT III)(SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS PRM RWY 10 (SCP)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT II)	1		KATL	ATLANTA	GA (US)
IAP	ILS RWY 10 (CAT III)	1		KATL	ATLANTA	GA (US)
IAP	RNAV (GPS) Y RWY 10			KATL	ATLANTA	GA (US)
IAP	RNAV (RNP) Z RWY 10			KATL	ATLANTA	GA (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 3 **DATE OF REVISION:** 11/15/2012

REASON FOR REVISION:
CHANGED FAC 1 MAG BRG FROM 273.97 TO 274.97.
UPDATED FIX USE AND REMARKS.

DEVELOPED BY: **DATE:** 05/16/2012 **OFFICE:** AJV-352 **NAME:** KELLY DEAN

APPROVED BY: **DATE:** **OFFICE:** AJV-352 **NAME:** DARRYEL ADAMS

SIGNATURE:

DISTRIBUTION: **NFDC**
FPO: EST
ARTCC: ZTL
ATC FACILITY: ATL/ATL
OTHER:

QUALITY CHECKED