

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
CLEARFIELD, PA	CLEARFIELD-LAWRENCE		3

TAKEOFF MINIMUMS:

RWY 12, STANDARD.

RWY 30, STANDARD WITH MINIMUM CLIMB OF 342 FT PER NM TO 3500 OR 1900-3 FOR CLIMB IN VISUAL CONDITIONS.

TEXTUAL DEPARTURE PROCEDURES:

RWY 12: CLIMB HEADING 110 TO 2500 BEFORE PROCEEDING ON COURSE.

RWY 30: CLIMB HEADING 298.91 TO 2700 BEFORE PROCEEDING ON COURSE, OR FOR CLIMB IN VISUAL CONDITIONS CROSS CLEARFIELD-LAWRENCE AIRPORT AT OR ABOVE 3300 BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 12: TREES BEGINNING 166 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/ 1635 FT MSL. TOWER, 2.73 NM FROM DER, 4881 FT RIGHT OF CENTERLINE, 422 FT AGL/ 2032 FT MSL.

NOTE RWY 30: AIRPLANE ON TAXIWAY 7 FT FROM DER, 131 FT LEFT OF CENTERLINE, UP TO 15 FT AGL/ 1534 FT MSL. TREES BEGINNING 53 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/ 2135 FT MSL. VEHICLES ON ROADWAY BEGINNING 241 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 15 FT AGL/ 1534 FT MSL. TOWERS BEGINNING 2.32 NM FROM DER, 760 FT LEFT AND RIGHT OF CENTERLINE, UP TO 611 FT AGL/ 2996 FT MSL.

CONTROLLING OBSTACLES:

RWY 30: 2665 FT MSL TOWER 410405.00N/0783107.00W, 2996 FT MSL TOWER 410432.00N/0783258.00W.

VCOA: 3160 FT MSL TOWER 410720.24N/0782628.93W, 2279 FT AAO 410446.14N/0782913.04W.

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 30- 3160 FT MSL TOWER 410720.24N/0782628.93W.
RWY 12- 3160 FT MSL TOWER 410720.24N/0782628.93W, 2032 FT MSL TOWER 410111.00N/0782123.00W.



