US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
FAPAD (IF/IAF)	FEMOS (FB)	012.95 / 6.87	2700
FEMOS (FAF)	RW01R (MAP) (FO)	012.99 / 4.16	
RW01R (MAP)	1521 MSL	012.99	
1521 MSL	JAXSU (FO)		3600

MISSED APPROACH

LPV: DA
LNAV/VNAV: DA
LNAV: RW01R

CLIMB TO 3600 DIRECT JAXSU AND HOLD.

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD S FAPAD, RT, 012.95 INBOUND, 3600 FT. IN LIEU OF PT (IAF)
3. FAC: 012.99 FAF: FEMOS DIST FAF TO MAP: 4.16 THLD: 4.16
4. MIN. ALT: FAPAD 3600, FEMOS 2700
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: 2700 GS ALT AT: FEMOS 2700 OM: ____ MM: ____ IM: ____
7. GS ANGLE: 3.00 TCH: 54.0 34:1 IS CLEAR
8. MSA FROM:

ADDITIONAL FLIGHT DATA:
HOLD N, RT, 193.07 INBOUND.
CHART FAS OBST: 1400 T-L TWR 373512N/0972618W
1549 AAO 373449N/0972851W
CHART LOC RWY 1L
DISTANCE TO THLD FROM 200 HATH: 0.46 NM.
CHART VDP AT 1.15 MILES TO RW01R*
*LNAV ONLY.
WAAS CHANNEL # 65929
REFERENCE PATH ID: W01B
CHART: A-683
LTP HAE: 373.9 M

MAG VAR: 7E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A STANDARD @

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1521	2400	200	1521	2400	200	1521	2400	200	1521	2400	200	1521	2400	200
LNAV/VNAV DA	1660	3200	339	1660	3200	339	1660	3200	339	1660	3200	339	1660	3200	339
LNAV MDA	1740	2400	419	1740	2400	419	1740	4000	419	1740	4000	419	1740	4000	419
CIRCLING	1800	1	467	1800	1	467	1800	1 1/2	467	1900	2	567	2000	2 1/4	667

NOTES:
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 35C (95F). @ CAT E 800-2 1/4
CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LPV CAT E VISIBILITY TO 3/4, LNAV/VNAV CAT E VISIBILITY TO 1 1/8 AND LNAV CAT C,D AND E VISIBILITY TO 1 1/8.
CHART NOTE: DME/DME RNP-0.3 NA.
(SEE FORM 8260-10)

QUALITY CHECKED

CITY AND STATE	ELEVATION: 1333 THRE: 1321	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
WICHITA, KS	AIRPORT NAME: WICHITA MID-CONTINENT	RNAV	RNAV (GPS) RWY 1R, AMDT 1	AMDT: ORIG-B
				DATED 04/05/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
[ ] YES [X] NO		ROUTINE

COORDINATED WITH:

ATA	AAT	ALPA	APA	AOPA	NBAA	OTHER (specify)
X		X	X	X	X	X ICT APP CON, ZKC, AMGR, KS AERO

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:

DEVELOPED BY		
NAME: THOMAS L KIRKPATRICK	FIFO AJV-353	DATE: 02/15/2012

APPROVED BY		
NAME: LARRY H STROUT MANAGER	FIFO AJV-353	DATE:

CHANGES:

1. ADD LPV LINE OF MINIMA AND ALL ASSOCIATED NOTES.
2. REMOVED ATOYI AND CURUM INITIALS FROM TAA AND TERMINAL ROUTES.
3. CHANGED DIST FAF TO MAP/THLD FROM -/5.03 TO 4.16/4.16.
4. CHANGED MIN ALTITUDE AT FEMOS FROM 3000 TO 2700.
5. CHANGED LNAV/VNAV VISIBILITIES FROM RVR 4000 TO RVR 3200 ALL CATS, AND LNAV CAT D VISIBILITY FROM RVR 5000 TO RVR 4000.
6. ADD CAT E MINIMUMS.
7. CHANGED BARO-VNAV HIGH AND LOW TEMPS.
8. ADD SIMULTANEOUS NOTES.
9. ADD INOPERATIVE MALSR NOTE.

REASONS:

1. FPT REQUEST.
2. FPT REQUEST AS RESULT OF NEW CRITERIA.
3. FAF MOVED TO L-V PFAF LOCATION.
4. FPT REQUEST.
5. NEW VISIBILITY TABLES
6. AIRPORT REQUEST.
7. NEW CALCULATION BASED ON 5 YEAR AVERAGE (2006-2010)
8. AS DIRECTED BY ATO.
9. REQUIREMENT.

PDF EDITS:
TERMINAL ROUTES: ADD (FAF) AFTER FEMOS, CHANGED 1521 TO 3600.
ADDITIONAL FLIGHT DATA: REMOVED OBST FROM 1549 AAO.
ADD AMDT DATE 04/05/2012.

QUALITY 2 CHECKED

NOTES, (CONT.):
CHART NOTE: LNAV PROCEDURE NA DURING SIMULTANEOUS OPERATIONS.
CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH ILS OR LOC RWY 1L AND ILS RWY 1L (CAT II).
CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.

TAA

	FROM	TO	ALT
1.	283/30 CW 103/30 (NOPT)	FAPAD (IF/IAF) (FB)	3600
2.	283/30 CW 103/30	FAPAD (IF/IAF) (FO)	3600

QUALITY 2 CHECKED

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	FIFO	DATE:
APPROVED BY		
NAME:	FIFO	DATE:

CHANGES:

REASONS:

QUALITY 2 CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD	DATA
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KICT
RUNWAY	RW01R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W01B
LTP/FTP LATITUDE	373833.9450N
LTP/FTP LONGITUDE	0972534.6270W
LTP/FTP ELLIPSOIDAL HEIGHT	+03739
FPAP LATITUDE	373957.7700N
FPAP LONGITUDE	0972456.2300W
THRESHOLD CROSSING HEIGHT (TCH)	00054.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
CRC REMAINDER	C23E1D7E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+04026
FPAP ORTHOMETRIC HEIGHT	+04026

QUALITY 2 CHECKED

CITY AND STATE	ELEVATION: 1333 THRE: 1321	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
WICHITA, KS	AIRPORT NAME: WICHITA MID-CONTINENT	RNAV	RNAV (GPS) RWY 1R, AMDT 1	AMDT: ORIG-B
				DATED: 04/05/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	FIFO	DATE:
APPROVED BY		
NAME:	FIFO	DATE:

CHANGES:

REASONS:

QUALITY 2 CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
WP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAEAENRT   FAPAD K30    W     N37281125W097301894                      E0043     NAR           FAPAD
        SUSAEAENRT   FEMOS K30    W     N37343908W097272209                      E0042     NAR           FEMOS
        SUSAEAENRT   JAXSU K30    W     N37502733W097200691                      E0042     NAR           JAXSU

                 1         2         3         4         5         6         7         8         9         0         1         2         3
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KICTK3AICT     0     103YHN37385980W097255900E007001333         1800018000C    MNAR    WICHITA MID-CONTINENT

                 1         2         3         4         5         6         7         8         9         0         1         2         3
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KICTK3FR01R  AFAPAD 010FAPADK3EA0EE AR   HF                    01300040    + 03600     18000                A JS
        SUSAP KICTK3FR01R  R      010FAPADK3EA0E  I    IF                                + 03600     18000                A JS
        SUSAP KICTK3FR01R  R      020FEMOSK3EA1E  F 051TF                    01300069    + 02700                          A JS
        SUSAP KICTK3FR01R  R      020FEMOSK3EA2WALPV       ALNAV/VNAV ALNAV                                                 JS
        SUSAP KICTK3FR01R  R      030RW01RK3PG0GY M 031TF                    01300042      01375            -300          A JS
        SUSAP KICTK3FR01R  R      040         0  M     CA                    0130        + 01521                          A JS
        SUSAP KICTK3FR01R  R      050JAXSUK3EA0EY      DF                                + 03600                          A JS
        SUSAP KICTK3FR01R  R      060JAXSUK3EA0EE  R   HM                    19310040    + 03600                          A JS

                 1         2         3         4         5         6         7         8         9         0         1         2         3
RUNWAY  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KICTK3GRW01R   0073010130 N37383395W097253463+0000    +0373901321000054150I

                 1         2         3         4         5         6         7         8         9         0         1         2         3
PP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KICTK3PR01R  RW01R001 0000W01B0N3738339450W09725346270+037390300N3739577700W09724562300106750528000540F400350C23E1D7E
        SUSAP KICTK3PR01R  RW01R002E      +04026+04026LPV       65929
```

QUALITY CHECKED 1

CITY AND STATE	ELEVATION: 1333 THRE: 1321	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
WICHITA, KS	AIRPORT NAME: WICHITA MID-CONTINENT	RNAV	RNAV (GPS) RWY 1R, AMDT 1	AMDT: ORIG-B
				DATED: 04/05/2012

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	NFPG	DATE:
APPROVED BY		
NAME:	NFPG	DATE:

CHANGES:

REASONS:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - **FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	FAPAD	FAPAD	010	IAF	HF	R	FO		013.0(020.0T)	004.0	AA 03600	
		FAPAD	010	FACF	IF		FB				AA 03600	
		FEMOS	020	FAF	TF		FB	0.5	013.0(020.0T)	006.9	AA 02700	
		RW01R	030	MAP	TF		FO	0.3	013.0(020.0T)	004.2	AT 01375	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		013.0(020.0T)		AA 01521	
	JAXSU	050		DF		FO				AA 03600	
	JAXSU	060		HM	R	FO		193.1(200.1T)	004.0	AA 03600	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	FAPAD	N372811.25	W0973018.94	N3728.188	W09730.316
	FEMOS	N373439.08	W0972722.09	N3734.651	W09727.368
	JAXSU	N375027.33	W0972006.91	N3750.456	W09720.115
	RW01R	N373833.95	W0972534.63	N3738.566	W09725.577

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW01R	01321	54

QUALITY CHECKED

CITY AND STATE	ELEVATION: 1333 THRE: 1321	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
WICHITA, KS	AIRPORT NAME: **WICHITA MID-CONTINENT**	**RNAV**	**RNAV (GPS) RWY 1R, AMDT 1**	AMDT: **ORIG-B**
				DATED: **04/05/2012**

ALL AFFECTED PROCEDURES REVIEWED?	COORDINATES OF FACILITIES	REQUIRED EFFECTIVE DATE
☐ YES ☐ NO		

COORDINATED WITH:

ATA ☐ AAT ☐ ALPA ☐ APA ☐ AOPA ☐ NBAA ☐ OTHER (specify) ☐ _____

FLIGHT CHECKED BY		
NAME:	FIFO	DATE:
DEVELOPED BY		
NAME:	NFPG	DATE:
APPROVED BY		
NAME:	NFPG	DATE:

CHANGES:

REASONS:

STANDARD INSTRUMENT APPROACH PROCEDURE DATA RECORD

PART - A OBSTRUCTION DATA

1. APP SEGMENT	FROM	TO	OBSTRUCTION	COORDINATES	ELEV. MSL	ROC	ALT. ADJUSTMENTS	MIN. ALT.
STRAIGHT-IN AREA	283/30 CW 103/30	FAPAD	1. TOWER (20-001156)	372124.00N/0965756.00W	2563 (1D)	1000		3600
			2. TERRAIN	373515.00N/0980930.00W	1680 (1700)		AS1500	3200
STRAIGHT-IN AREA	283/30 CW 103/30	FAPAD	1. TOWER (20-001156)	372124.00N/0965756.00W	2563 (1D)	1000		3600
			2. TERRAIN	373515.00N/0980930.00W	1680 (1700)		AS1500	3200
INTERMEDIATE	FAPAD (IF/IAF)	FEMOS	3. TOWER (20-020349)	372956.98N/0973051.30W	1588 (1A)	500	AT612	2700
			4. TERRAIN	373318.00N/0973039.00W	1378 (1400)		AS1000	2400
FINAL: LPV	FEMOS	RW01R				ASC		1521/200
FINAL: LNAV/VNAV	FEMOS	RW01R	5. RW01R	373833.95N/0972534.63W	1321 (1A)	PDA	XP89	1660/339
FINAL: LNAV	FEMOS	RW01R	6. T-L TWR (20-020859)	373512.16N/0972618.44W	1400 (2C)	250	XP90	1740
2. HOLD-IN-LIEU-OF-PT	FAPAD	P-5	7. TOWER (20-001427)	372411.00N/0973523.00W	1834 (5D)	1000	AT766	3600
			8. TERRAIN	372542.00N/0973212.00W	1378 (1400)		AS1500	2900
3. MISSED APPROACH — MAP:	DA / DA / RW01R	JAXSU				ASC		3600
			9. TOWER (20-000141)	374407.00N/0972104.00W	1844 (1D)	1000		2900
ELEV:	1353/1499/1640		10. TERRAIN	375057.00N/0971806.00W	1434 (1400)		AS1500	2900

4. CIRCLING AREA	DISTANCE	HT. ABV. ARPT. REQUIRED	HT. ABV. ARPT. ACTUAL							
CATEGORY A	1.3 NM	350	467	11. TOWER (20-001825)	373947.10N/0972742.42W	1494 (2C)	300			1800
CATEGORY B	1.5 NM	450	467	11. TOWER (20-001825)	373947.10N/0972742.42W	1494 (2C)	300			1800
CATEGORY C	1.7 NM	450	467	11. TOWER (20-001825)	373947.10N/0972742.42W	1494 (2C)	300			1800
CATEGORY D	2.3 NM	550	567	11. TOWER (20-001825)	373947.10N/0972742.42W	1494 (2C)	300		HAA	1900
CATEGORY E	4.5 NM	550	667	12. TWR (20-000987)	374113.00N/0972025.00W	1639 (5D)	300		AC50	2000

5. MINIMUM SAFE ALTITUDES — PRIMARY NAVAID:

SECTOR	OBSTRUCTION	BRG/DIST	ELEVATION (MSL)	M S A	SECTOR	OBSTRUCTION	BRG/DIST	ELEVATION (MSL)	M S A

QUALITY CHECKED 2

CITY AND STATE	ELEVATION: 1333 / AIRPORT NAME:	FACILITY	PROCEDURE AND AMENDMENT NO:	REGION
WICHITA, KS	WICHITA MID-CONTINENT	RNAV	RNAV (GPS) RWY 1R, AMDT 1	ACE

PART B - SUPPLEMENTAL DATA

1. COMMUNICATIONS WITH:	2. WEATHER SERVICE		3. ALTIMETER SETTING
ZKC ARTCC ICT APP CON ICT FSS	N W S F A A A / C	OTHER: ASOS	SOURCE: KICT DISTANCE: HOURS REMOTE OPERATION:
SATISFACTORY ON:			
X V H F X U H F H F	LOCATION: KICT		ADJUSTMENT: 0

4. MONITOR STATUS	PRIMARY NAVAID:	
	MONITOR POINT:	
	HRS OPTN: CAT 1	
	HRS OPTN: CAT 3	
5. APPROACH & RUNWAY LIGHTING	X	ALSF-2 01L
		(S) SALS
	X	MALSR 01R, 19L, 19R
	X	HIRL 01R, 19L, 01L, 14, 19R, 32
		MIRL
	X	REIL 14, 32
	X	TDZ 01L
	X	C/L 01L, 19R
	X	OTHER (SPECIFY) PAPI-4L 19L, 14, 32
6. RUNWAY MARKINGS	BASIC	BSC-G 32
	ALL WEATHER	PIR-G 01R, 19L, 01L, 19R
	INSTRUMENT	NPI-G 14
7. RUNWAY VISUAL RANGE	APPROACH	01R, 01L, 19R
	MIDFIELD	01L, 19R
	ROLL OUT	01L, 19R

8. GLIDE PATH	GP ANGLE: 3.00	ELEV RWY THRESHOLD: 1320.9
	DISTANCE FROM RWY:	ELEV GP ANTENNA:
		THRESHOLD CROSSING HEIGHT: 54.0

9. FINAL APPROACH COURSE AIMING	X	RUNWAY THRESHOLD	FT. FROM THRESHOLD
	X	ON CENTERLINE	FT. FROM CENTERLINE

10. WAIVERS: NONE

PART D - PREPARED BY: THOMAS L KIRKPATRICK	DATE: 02/15/2012
TITLE: AERONAUTICAL INFORMATION SPECIALIST	OFFICE: AJV-353

PART C - REMARKS:

PRECIPITOUS TERRAIN EVALUATION COMPLETED.

TERPS PARAGRAPH 289 APPLIED TO 1549 AAO
373449N/0972851W

ALTERNATE ALSTG NOT REQUIRED, REDUNDANT WEATHER SOURCES AVAILABLE AT AIRPORT.

VGSI: NONE

NO ADDITIONAL AIRSPACE REQUIRED.

LPV:
SURFACE = 34:1
LNAV/VNAV:
SURFACE = 23.239:1

AVERAGE COLD TEMPERATURE (ACT) BASED ON 5 YEAR AVERAGE
2006 (3), 2007 (6), 2008 (4), 2009 (3), 2010 (0)
ACT= -16C.

OBS NUMBERS KICTT0058, KICTT0026, KICTT0056, KICTT0055, KICT0054, AND KICTT0064 ARE AIRPORT AND FAA USE ONLY, BECAUSE THEY ARE INSIDE THE PERIMETER FENCING AND UNDER CONTROL OF ATC, OBSTACLES HAVE BEEN DETERMINED TO HAVE NO ADVERSE EFFECT.

PROCEDURE BUILT TO MATCH PREVIOUS TCH OF 54', DID NOT MATCH ILS SINCE THE ILS GS ANGLE IS 2.8 DEGREES

XP89: TO MATCH PREVIOUSLY PUBLISHED DA

XP90: TO MATCH PREVIOUSLY PUBLISHED MDA

QUALITY 2 CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: FEMOS **STATE:** KS **COUNTRY:** US

LATITUDE/LONGITUDE: 373439.08N/0972722.09W **TYPE:** WP

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

HOLDING: **HOLDING TYPE OF ACTION:** NO CHANGE

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	RNAV (GPS) RWY 01R			KICT	WICHITA	KS (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 1 **DATE OF REVISION:** 07/26/2012

REASON FOR REVISION:
UPDATE FIX COORDINATES, FIX MOVED 5265 FEET NORTHWEST.
REMOVED FAC 1.

DEVELOPED BY: **DATE:** 02/15/2012 **OFFICE:** AJV-353 **NAME:** THOMAS KIRKPATRICK

APPROVED BY: **DATE:** **OFFICE:** AJV-353 **NAME:** LARRY STROUT

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: CEN
ARTCC: ZKC
ATC FACILITY: ICT APP CON
OTHER:

QUALITY 2 CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: FAPAD **STATE:** KS **COUNTRY:** US

LATITUDE/LONGITUDE: 372811.25N/0973018.94W **TYPE:** WP

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

"INFO ONLY"

HOLDING: **HOLDING TYPE OF ACTION:** MODIFY

PATTERNS:

PAT	DIR	IDENT	TYPE	RAD/CRS/BRG	CRS INBOUND	TURN (L OR R)	LEG LENGTH TIME	LEG LENGTH DME	HOLDING ALTITUDES MIN	HOLDING ALTITUDES MAX	TEMPLATES MIN	TEMPLATES MAX
1	S		WP	192.95	012.95	R		4	3600	10000	5	7

CONTROLLING OBSTRUCTIONS:

PAT	AIRSPEED	OBSTRUCTION	COORDINATES	ELEVATION	ACCURACY CODE
1	230	TOWER (20-001427)	372411.00N/0973523.00W	1834	5D

HOLDING RESTRICTIONS:
HOLDING LIMITED TO ESTABLISHED PATTERN.

REMARKS:
PRECIPITOUS TERRAIN EVALUATION COMPLETE.

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	RNAV (GPS) RWY 1R		1	KICT	WICHITA	KS (US)
IAP	RNAV (GPS) Y RWY 19L		1	KICT	WICHITA	KS (US)
IAP	RNAV (RNP) Z RWY 19L		1	KICT	WICHITA	KS (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 1 **DATE OF REVISION:** 09/23/2010

REASON FOR REVISION:
REMOVED FAC 1 NOT REQUIRED.
CHANGED TEMPLATES MAX FROM 7-10.
UPDATED CONTROLLING OBSTACLE, NEW OBSTACLE NO AFFECT ON HOLDING MINIMUM OR ON THE RNAV (GPS) RWY 1R
UPDATED DISTRIBUTION.

DEVELOPED BY: **DATE:** 05/21/2010 **OFFICE:** AVN-130 **NAME:** ANDREW FIELDS

APPROVED BY: **DATE:** 07/07/2010 **OFFICE:** AVN-130 **NAME:** SUE CRUMB

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: CEN
ARTCC: ZKC
ATC FACILITY: ICT APP CON
OTHER:

QUALITY 2 CHECKED

RADIO FIX AND HOLDING DATA RECORD

NAME: JAXSU **STATE:** KS **COUNTRY:** US

LATITUDE/LONGITUDE: 375027.33N/0972006.91W **TYPE:** WP

"INFO ONLY"

AIRSPACE DOCKET: **FIX TYPE OF ACTION:** MODIFY

HOLDING: **HOLDING TYPE OF ACTION:** MODIFY

PATTERNS:

PAT	DIR	IDENT	TYPE	RAD/CRS/BRG	CRS INBOUND	TURN (L OR R)	LEG LENGTH TIME	LEG LENGTH DME	HOLDING ALTITUDES MIN	HOLDING ALTITUDES MAX	TEMPLATES MIN	TEMPLATES MAX
1	N		WP	013.07	193.07	R		4	3600	7000	5	7

CONTROLLING OBSTRUCTIONS:

PAT	AIRSPEED	OBSTRUCTION	COORDINATES	ELEVATION	ACCURACY CODE
1	200	TOWER (20-000368)	374801.00N/0971751.00W	1871	4F

REMARKS:
HOLDING LIMITED TO ESTABLISHED PATTERN.

FIX USE:

USE TYPE	USE TITLE	FAC	PAT	AIRPORT IDENT	CITY	STATE
IAP	RNAV (GPS) RWY 01R		1	KICT	WICHITA	KS (US)
IAP	RNAV (GPS) Y RWY 19L		1	KICT	WICHITA	KS (US)
IAP	RNAV (RNP) Z RWY 19L			KICT	WICHITA	KS (US)

REQUIRED CHARTING: IAP

COMPULSORY REPORTING POINT: NO

RECORD REVISION NUMBER: 2 **DATE OF REVISION:** 09/23/2010

REASON FOR REVISION:
REMOVED DME FROM TYPE, COULD NOT FIND IT USED AS DME FIX.
REMOVED REMARK FIX LOCATED ON V12, IT IS NOT CHARTED AND ATC DOES NOT WANT THE IT CHARTED.
REMOVED FAC 1 AND 2 NO LONGER REQUIRED.
UPDATED CONTOLLING OBSTACLE DID NOT RAISE MIN HOLDING ALTITUDE.
UPDATED FIX USE TO REPORT FORMAT.
MOVED FIX 12.77' NORTHWEST OPTIMUM PLACEMENT.
UPDATED FPO INFO.

DEVELOPED BY: **DATE:** 04/29/2010 **OFFICE:** AVN-130 **NAME:** ANDREW FIELDS

APPROVED BY: **DATE:** 07/07/2010 **OFFICE:** AVN-130 **NAME:** SUE CRUMB

SIGNATURE:

DISTRIBUTION:
NFDC
FPO: CEN
ARTCC: ZKC
ATC FACILITY: ICT APP CON
OTHER:

QUALITY 2 CHECKED