

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
CHEYENNE, WY	CHEYENNE RGNL/JERRY OLSON FIELD		4

TAKEOFF MINIMUMS:

RWY 09, 13, 27, 31, STANDARD.

TEXTUAL DEPARTURE PROCEDURES:

RWY 31 – CLIMB HEADING 305.29 TO 6700 BEFORE TURNING LEFT.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 13, FENCE BEGINNING 30 FT FROM DER, 246 FT RIGHT OF CENTERLINE, UP TO 9 FT AGL/6126 FT MSL. TREES BEGINNING 48 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 68 FT AGL/6177 FT MSL. MULTIPLE POLES BEGINNING 165 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 27 FT AGL/6136 FT MSL.

NOTE: RWY 27, LOCALIZER ANTENNA 404 FT FROM DER, ON CENTERLINE, 10 FT AGL/6156 FT MSL. LIGHT ON LOCALIZER ANTENNA, 408 FT FROM DER, 49 FT LEFT OF CENTERLINE, 10 FT AGL/6156 FT MSL. VEHICLES ON ROAD BEGINNING 422 FT FROM DER, 247 FT LEFT OF CENTERLINE, UP TO 15 FT AGL/6162 FT MSL. TREES BEGINNING 514 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 65 FT AGL/6224 FT MSL. MULTIPLE POLES BEGINNING 741 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 60 FT AGL/6203 FT MSL.

NOTE: RWY 31, TREES BEGINNING 140 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 57 FT AGL/6226 FT MSL. VEHICLES ON ROAD BEGINNING 193 FT FROM DER, 248 FT LEFT OF CENTERLINE, UP TO 15 FT AGL/6179 FT MSL. FENCE BEGINNING 196 FT FROM DER, 1 FT LEFT OF CENTERLINE, 9 FT AGL/6175 FT MSL. SIGN 370 FT FROM DER, 59 FT LEFT OF CENTERLINE, 9 FT AGL/6171 FT MSL. MULTIPLE POLES BEGINNING 383 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 35 FT AGL/6229 FT MSL. SIGN 3248 FT FROM DER, 600 FT LEFT OF CENTERLINE, 56 FT AGL/6244 FT MSL.

CONTROLLING OBSTACLES:

RWY 31, OBSTACLE MANDATING ODP ROUTE DEVELOPMENT – 6584 FT MSL WINDMILL 411041.83N/1045305.09W.



U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
CHEYENNE, WY	CHEYENNE RGNL/JERRY OLSON FIELD		4

REMARKS:

6584 FT MSL WINDMILL 4D ACCURACY VERIFICATION REQUESTED FROM FLIGHT CHECK.

FLIGHT INSPECTED BY:

REQUIRED EFFECTIVE DATE:

ROUTINE

DEVELOPED BY:

ADOLFO URRUTIA (WES COMBS) AJV-354

APPROVED BY:

DEZ SILAGYI AJV-354

COORDINATED WITH:

ATA, APA, AOPA, NBAA, ALPA, ZDV, CYS ATCT, ARPT MGR, WST FPO

CHANGES:

1. ADDED "CLIMB HEADING 305.29 TO 6700 BEFORE TURNING LEFT." TO RWY 31 INSTRUCTIONS
2. UPDATED LOW, CLOSE-IN OBSTACLES.

REASONS:

1-2. NEW OBSTACLE SURVEY DATA, NOTAM 01/6857, AND IAW 8260.46D.

