

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
				MAP: 5.13 MILES AFTER TNV VORTAC OR AT MAJLO/TNV 5.13 DME FIX	
				CLIMB TO 2000 THEN LEFT TURN DIRECT TNV VORTAC AND HOLD.	
				ADDITIONAL FLIGHT DATA: HOLD NW, RT, 117.95 INBOUND. FAS OBST: 479 AAO 381825N/0960339W 529 AAO 301823N/0960252W CHART BRENHAM AWOS-3 FAC CROSSES MID POINT OF RWY 17-35.	

1. PT L SIDE OF COURSE 140.89 OUTBOUND 2000 FT WITHIN 10 MILES OF TNV VORTAC (IAF)
2. _____
3. FAC 320.89 FAF TNV VORTAC DIST FAF TO MAP 5.13 THLD _____
4. MIN. ALT TNV VORTAC 2000
8. MSA FROM: TNV VORTAC 040-310 2100, 310-040 3000

MAG VAR: 8E EPOCH YEAR: 1965

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		X			
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	820	1	591	820	1	591	820	1 1/2	591	980	2 1/2	751			

NOTES:

CHART NOTE: USE BRENHAM ALTIMETER SETTING, WHEN NOT RECEIVED, USE COLLEGE STATION ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET.

CITY AND STATE NAVASOTA, TX	ELEVATION: 229 TDZE:	FACILITY IDENTIFIER: TNV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR-A, AMDT 2 7 MARCH 2013	SUP VOR OR GPS-A
	AIRPORT NAME: NAVASOTA MUNI			AMDT 1A
				DATE 04/18/2002