US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
LDN VORTAC (IAF)	RECUF (FB)	261.12 / 6.13	4200
RECUF (IF)	FAVOV (FB)	229.78 / 6.05	3000

MISSED APPROACH

LNAV: AYOCE

CLIMB TO 6000 DIRECT FIBIR AND VIA 213.01 TRACK TO SAHDO AND HOLD, CONTINUE CLIMB-IN-HOLD TO 6000.

ADDITIONAL FLIGHT DATA:
HOLD NE, RT, 215.78 INBOUND.
FAS OBST: 1671 AAO 384539N/0782712W
FAVOV TO RW22: 3.23/40
CHART CHARLOTTESVILLE ASOS 118.425
FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD.

1. PT NA SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. PROFILE STARTS AT RECUF
3. FAC: 230.28 FAF: FAVOV DIST FAF TO MAP: 5.51 THLD: 6.00
4. MIN. ALT: RECUF 4200, FAVOV 3000
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: ____ GS ALT AT: ____ OM: ____ MM: ____ IM: ____
7. GS ANGLE: ____ TCH: 34:1 IS NOT CLEAR
8. MSA FROM: AYOCE 5300

MAG VAR: 9W EPOCH YEAR: 1995

MINIMUMS

TAKEOFF: [ ] STANDARD [X] SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A [X]

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2280	1 1/4	1377	2280	1 1/2	1377	2280	3	1377		NA				
CIRCLING	2320	1 1/4	1417	2320	1 1/2	1417	2320	3	1417		NA				

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT LDN VORTAC VIA V144 SOUTHEAST BOUND.
CHART NOTE: USE CHARLOTTESVILLE ALTIMETER SETTING; WHEN NOT RECEIVED, USE ORANGE ALTIMETER SETTING AND INCREASE ALL MDAS 20 FEET.

CITY AND STATE	ELEVATION: 903 TDZE: 903	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
LURAY, VA	AIRPORT NAME: LURAY CAVERNS	RNAV	RNAV (GPS) RWY 22, ORIG FEB 14 2008	AMDT: NONE DATED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-15

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
NAVAID  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAD        LDN   K6011430VTL  N38511581W078122000    N38511581W078122000W006002440      NAWLINDEN

                 1         2         3         4         5         6         7         8         9         0         1         2         3
WP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAEAENRT   AYOCE K60    W  RL N38403854W078292939                    W0097     NAW           AYOCE
        SUSAEAENRT   FAVOV K60    W  RL N38444730W078245092                    W0097     NAW           FAVOV
        SUSAEAENRT   FIBIR K60    W  RL N38390410W078311495                    W0097     NAW           FIBIR
        SUSAEAENRT   RECUF K60    W  RL N38492254W078194785                    W0097     NAW           RECUF
        SUSAEAENRT   SAHDO K60    W  RL N38302415W078360970                    W0097     NAW           SAHDO

                 1         2         3         4         5         6         7         8         9         0         1         2         3
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP W45 K6AW45     0     031YHN38400140W078300210W009000903         1800018000C    MNAW    LURAY CAVERNS

                 1         2         3         4         5         6         7         8         9         0         1         2         3
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP W45 K6FP22   ALDN   010LDN  K6D 0V  A    IF                                          18000                G  S
        SUSAP W45 K6FP22   ALDN   020RECUFK6EA0EE   010TF                    26110061    + 04200                        G  S
        SUSAP W45 K6FP22   P      010RECUFK6EA0E  I    IF                                + 04200     18000              G  S
        SUSAP W45 K6FP22   P      020FAVOVK6EA0E  F 051TF                    22980061    + 03000                AYOCE K6EAG  S
        SUSAP W45 K6FP22   P      030AYOCEK6EA0EY M 031TF                    23030055      01113            -323        G  S
        SUSAP W45 K6FP22   P      040         0  M  010CA                    2303        + 01303                        G  S
        SUSAP W45 K6FP22   P      050FIBIRK6EA0E    010DF                                                              G  S
        SUSAP W45 K6FP22   P      060SAHDOK6EA0EY   010TF                    2130        + 06000                        G  S
        SUSAP W45 K6FP22   P      070SAHDOK6EA0EE HR020HM                    21580050    + 06000                        G  S

                 1         2         3         4         5         6         7         8         9         0         1         2         3
RUNWAY  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP W45 K6GRW22    0031252236 N38401413W078295086              00903000040075

                 1         2         3         4         5         6         7         8         9         0         1         2         3
MSA     123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
```

CITY AND STATE	ELEVATION: 903 TDZE: 903	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
LURAY, VA	AIRPORT NAME: LURAY CAVERNS	RNAV	RNAV (GPS) RWY 22, ORIG FEB 14 2008	AMDT: NONE DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

```
SUSAP W45 K6SAYOCEK6EA          0 25180053                    M
```

CITY AND STATE	ELEVATION: 903 TDZE: 903	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
LURAY, VA	AIRPORT NAME: LURAY CAVERNS	RNAV	RNAV (GPS) RWY 22, ORIG FEB 14 2008	AMDT: NONE DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	LDN	LDN	010	IAF	IF		FB				
	LDN	RECUF	020		TF		FB	1.0	261.1(252T)	006.1	04200
		RECUF	010	FACF	IF		FB				04200
		FAVOV	020	FAF	TF		FB	0.5	229.8(221T)	006.1	03000
		AYOCE	030	MAP	TF		FO	0.3	230.3(221T)	005.5	01113

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	230.3(221T)		01303
	FIBIR	050		DF		FB	1.0			
	SAHDO	060		TF		FO	1.0	213.0(204T)		06000
	SAHDO	070		HM	R	FO	2.0	215.8(207T)	005.0	06000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	LDN	N385115.81	W0781220.00	N3851.264	W07812.333
	AYOCE	N384038.54	W0782929.39	N3840.642	W07829.490
	FAVOV	N384447.30	W0782450.92	N3844.788	W07824.849
	FIBIR	N383904.10	W0783114.95	N3839.068	W07831.249
	RECUF	N384922.54	W0781947.85	N3849.376	W07819.798
	SAHDO	N383024.15	W0783609.70	N3830.403	W07836.162
	RW22	N384014.13	W0782950.86	N3840.236	W07829.848

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW22	00903	40

CITY AND STATE				
LURAY, VA	ELEVATION: 903 TDZE: 903 AIRPORT NAME: LURAY CAVERNS	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG FEB 14 2008	SUP: AMDT: NONE DATED: