U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
EED VORTAC (IF/IAF)	LONDN/7.00 DME	138.89 / 7.00	3500

MISSED APPROACH

MAP: CEKVU/ 12.35 DME

CLIMBING RIGHT TURN TO 6000 DIRECT EED VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 6000.

ADDITIONAL FLIGHT DATA

CHART FAS OBST: 1494 TREE 343714N/1142305W
2559 AAO 344041N/1142329W
FAC CROSSES MID POINT OF RWY 14-32

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD NW EED VORTAC, RT, 138.89 INBOUND, 4000 FT. IN LIEU OF PT (IAF)
3. FAC 138.89 FAF LONDN/7.00 DME DIST FAF TO MAP ____ THLD ____
4. MIN. ALT LONDN 3500, ARHEY/10.00 DME 2540
8. MSA FROM: EED VORTAC 070-160 6800, 160-250 5400, 250-340 5000, 340-070 8900

MAG VAR: 15E EPOCH YEAR: 1965

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: N A X

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1800	1 1/4	1017	1800	1 1/2	1017	1800	3	1017	1800	3	1017			

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE NEEDLES ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET.
CHART NOTE: CIRCLING NA NE OF RWY 14-32

QUALITY CHECKED 4

CITY AND STATE	ELEVATION: 783 TDZE: AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP VOR/DME OR GPS-A
LAKE HAVASU CITY, AZ	LAKE HAVASU CITY	EED	VOR/DME-A, AMDT 1 31 MAY 2012	AMDT ORIG-C DATE 06/08/2006