

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
CANON CITY, CO	FREMONT COUNTY	7 FEBRUARY 2013	1

TAKEOFF MINIMUMS:

RWY 17, 35 NA – ATC.
RWY 11, 29 STANDARD.

TEXTUAL DEPARTURE PROCEDURES:

RWY 11: CLIMB ON HEADING 109.86 AND PUB R-270 TO PUB VORTAC BEFORE PROCEEDING ON COURSE.

RWY 29: CLIMBING LEFT TURN TO INTERCEPT PUB R-270 TO PUB VORTAC BEFORE PROCEEDING ON COURSE. DO NOT EXCEED 210 KNOTS UNTIL ESTABLISHED ON PUB R-270 EASTBOUND.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 11, TREES BEGINNING 5 FT FROM DER, 321 FT LEFT OF CENTERLINE, UP TO 10 FT AGL/5384 FT MSL. LIGHT SUPPORT STRUCTURE 10 FT FROM DER, 20 FT LEFT OF CENTERLINE, 2 FT AGL/5383 FT MSL. LIGHT SUPPORT STRUCTURE 10 FT FROM DER, 19 FT RIGHT OF CENTERLINE, 2 FT AGL/5383 FT MSL.

NOTE: RWY 29, VEHICLES ON ROAD BEGINNING 57 FT FROM DER, 338 FT LEFT OF CENTERLINE, UP TO 15 FT AGL/5450 FT MSL. FENCE 8 FT FROM DER, 432 FT RIGHT OF CENTERLINE, 6 FT AGL/5450 FT MSL. NAVAID 10 FT FROM DER, 113 FT RIGHT OF CENTERLINE, 6 FT AGL/5448 FT MSL. VEHICLES ON ROAD 349 FT FROM DER, 542 FT RIGHT OF CENTERLINE, 15 FT AGL/5454 FT MSL. VERTICAL STRUCTURE 119 FT FROM DER, 433 FT RIGHT OF CENTERLINE, 10 FT AGL/5447 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 11, 29 – 14310 FT MSL AAO 385020.60N/1050238.00W. 12567 FT MSL AAO 384723.10N/1045931.20W.

