

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
 NDB STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
SNY VORTAC	BAJ NDB	185.47 / 35.68	6300
AKO VOR/DME	BAJ NDB	341.17 / 22.69	6300
RAYME INT	BAJ NDB	085.87 / 25.36	6700

MAP: 4.78 MILES AFTER BAJ NDB

CLIMBING LEFT TURN TO 6200 DIRECT TO BAJ NDB AND HOLD.

ADDITIONAL FLIGHT DATA:
 HOLD SE, LT, 334.54 INBOUND.
 FAS OBST: 4249 AAO 403319N/1031235W
 OBST: 4349 AAO 403230N/1031222W
 BAJ NDB TO RW33: 3.02/44.

- PT R SIDE OF COURSE 154.54 OUTBOUND 6200 FT WITHIN 10 MILES OF BAJ NDB (IAF)
-
- FAC 334.54 FAF BAJ NDB DIST FAF TO MAP 4.78 THLD 4.78
- MIN. ALT BAJ NDB 5600
- MSA FROM: BAJ NDB 6200

MAG VAR: 8E EPOCH YEAR: 2015

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X							
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-33	4560	1	534	4560	1	534	4560	1 1/2	534	4560	1 1/2	534				
CIRCLING	4560	1	522	4560	1	522	4580	1 1/2	542	4600	2	562				

NOTES:
 CHART NOTE: CIRCLING TO RWY 22 NA AT NIGHT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AKRON ALTIMETER SETTING AND INCREASE ALL MDA 160 FEET AND S-33 CAT C AND D VISIBILITY 1/2 MILE, CIRCLING CAT C VISIBILITY 1/2 MILE AND CAT D 1/4 MILE.

CITY AND STATE STERLING, CO	ELEVATION: 4038	THRE: 4026	FACILITY IDENTIFIER: BAJ NDB	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 33, AMDT 3 20 SEPTEMBER 2012	SUP	
	AIRPORT NAME: STERLING MUNI				AMDT	2
					DATE	11/02/1978

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE STERLING, CO	ELEVATION: 4038 THRE: 4026 AIRPORT NAME: STERLING MUNI	FACILITY IDENTIFIER: BAJ NDB	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: NDB RWY 33, AMDT 3 20 SEPTEMBER 2012	SUP:
				AMDT: 2
				DATED: 11/02/1978