US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
TTH VORTAC	POKHY (FO)	230.05 / 15.13	2600
GOZUM (IAF)	POKHY (NOPT) (FB)	315.96 / 10.87	2600
IFIGO (IAF)	POKHY (NOPT) (FB)	134.28 / 8.40	2600
POKHY (IF/IAF)	SOXME (FB)	049.10 / 6.02	2100
SOXME (FAF)	VARUY/1.70 NM TO RW05 (FB)	049.17 / 2.91	
VARUY/1.70 NM TO RW05	RW05 (MAP) (FO)	049.20 / 1.70	
(SEE FORM 8260-10)			

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD SW POKHY, RT, 049.10 INBOUND, 2600 FT. IN LIEU OF PT (IAF)
3. FAC: 049.16 FAF: SOXME DIST FAF TO MAP: 4.61 THLD: 4.61
4. MIN. ALT: POKHY 2600, SOXME 2100, VARUY/1.70 NM TO RW05 1140*
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: 2100 GS ALT AT: SOXME 2100 OM: ____ MM: ____ IM: ____
7. GS ANGLE: 3.00 TCH: 39.8 34:1 IS CLEAR
8. MSA FROM: RW05 2600

MISSED APPROACH

LPV: DA
LNAV/VNAV: DA
LNAV: RW05

CLIMB TO 2400 DIRECT IPEDY AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD NE, RT, 229.34 INBOUND.
CHART FAS OBST: 655 TREE 392558N/0872012W
CHART FAS OBST: 679 TREE 392503N/0872008W
DISTANCE TO THLD FROM 302 HATH: 0.83 NM.
CHART VDP AT 1.03 MILES TO RW05*
*LNAV ONLY.
WAAS CHANNEL # 82109
REFERENCE PATH ID: W05A
CHART: ASR
LTP HAE: 141.6 M

MAG VAR: 2W EPOCH YEAR: 2000

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A STANDARD @

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	875	2400	302	875	2400	302	875	2400	302	875	2400	302			
LNAV/VNAV DA	924	4000	351	924	4000	351	924	4000	351	924	4000	351			
LNAV MDA	940	2400	368	940	2400	368	940	2400	368	940	5000	368			
CIRCLING	1020	1	431	1040	1	451	1040	1 1/2	451	1140	2	551			

NOTES:
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON TTH VORTAC AIRWAY RADIALS 140 CW 320.
*LNAV ONLY
(SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY CHECKED

CITY AND STATE	ELEVATION: 589 THRE: 572	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
TERRE HAUTE, IN	AIRPORT NAME: TERRE HAUTE INTL-HULMAN FIELD		RNAV (GPS) RWY 5, ORIG-B 15 DEC 2011	AMDT: ORIG-A DATED 03/10/2011

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW05 (MAP)	875 MSL	049.20	
875 MSL	IPEDY (FO)		2400

NOTES, (CONT.):
CHART NOTE: VDP AND BARO-VNAV NA WHEN USING PARIS ALTIMETER SETTING.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PARIS ALTIMETER SETTING AND INCREASE ALL DA 61 FEET, AND ALL MDA 80 FEET. INCREASE LPV AND LNAV/VNAV VISIBILITY ALL CATS AND LNAV CAT C VISIBILITY 1/4 MILE, FOR INOPERATIVE MALSR INCREASE LPV VISIBILITY ALL CATS 1/2 MILE, AND LNAV CAT D VISIBILITY 1/4 MILE. FOR INOPERATIVE MALSR, WHEN USING PARIS ALTIMETER SETTING INCREASE LPV VISIBILITY ALL CATS TO RVR 6000, LNAV/VNAV ALL CATS AND LNAV CAT D TO 1 1/2 AND CAT C TO 1 1/4.
CHART NOTE: CIRCLING RWY 36 NA AT NIGHT.
CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 18 NA AT NIGHT.

QUALITY CHECKED 1

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD	DATA
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KHUF
RUNWAY	RW05
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W05A
LTP/FTP LATITUDE	392625.8810N
LTP/FTP LONGITUDE	0871923.3725W
LTP/FTP ELLIPSOIDAL HEIGHT	+01416
FPAP LATITUDE	392726.4600N
FPAP LONGITUDE	0871758.9600W
THRESHOLD CROSSING HEIGHT (TCH)	00039.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
CRC REMAINDER	B352AB79

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+01743
FPAP ORTHOMETRIC HEIGHT	+01743

QUALITY CHECKED

CITY AND STATE	ELEVATION: 589 THRE: 572	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
TERRE HAUTE, IN	AIRPORT NAME: TERRE HAUTE INTL-HULMAN FIELD	RNAV	RNAV (GPS) RWY 5, ORIG-B 15 DEC 2011	AMDT: ORIG-A
				DATED: 03/10/2011

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
NAVAID  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAD        TTH   K5011530VTHA N39292019W087145647    N39292019W087145647E0020006062     NARTERRE HAUTE
```

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
WP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAEAENRT   GOZUM K50    C   L N39113906W087192154                      W0033     NAR           GOZUM
        SUSAEAENRT   IFIGO K50    C   L N39245143W087372694                      W0031     NAR           IFIGO
        SUSAEAENRT   IPEDY K50    W     N39353653W087063366                      W0036     NAR           IPEDY
        SUSAEAENRT   POKHY K50    W     N39191181W087292648                      W0032     NAR           POKHY
        SUSAEAENRT   SOXME K50    W     N39231761W087234538                      W0033     NAR           SOXME
        SUSAEAENRT   VARUY K50    W     N39251653W087205996                      W0034     NAR           VARUY
```

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KHUFK5AHUF     0     090YHN39270530W087182730W002000589         1800018000C    MNAR    TERRE HAUTE INTL-HULMAN FIELD
```

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KHUFK5FR05   AGOZUM 010GOZUMK5EA0E  A    IF                                                18000                A JS
        SUSAP KHUFK5FR05   AGOZUM 020POKHYK5EA0EE B 010TF                     31600109    + 02600                              A JS
        SUSAP KHUFK5FR05   AIFIGO 010IFIGOK5EA0E  A    IF                                                18000                A JS
        SUSAP KHUFK5FR05   AIFIGO 020POKHYK5EA0EE B 010TF                     13430084    + 02600                              A JS
        SUSAP KHUFK5FR05   ATTH   010TTH  K5D 0V       IF                                                18000                A JS
        SUSAP KHUFK5FR05   ATTH   020POKHYK5EA0EY   020TF                     23010151    + 02600                              A JS
        SUSAP KHUFK5FR05   ATTH   030POKHYK5EA0EE AR   HF                     04910040    + 02600                              A JS
        SUSAP KHUFK5FR05   R      010POKHYK5EA0E  I    IF                                  + 02600     18000                    A JS
        SUSAP KHUFK5FR05   R      020SOXMEK5EA1E  F 051TF                     04910060    + 02100                  RW05  K5PGA JS
        SUSAP KHUFK5FR05   R      020SOXMEK5EA2WALPV       ALNAV/VNAV ALNAV                                                      JS
        SUSAP KHUFK5FR05   R      021VARUYK5EA0E S  031TF                     04920029    V 0114001156        -300          A JS
        SUSAP KHUFK5FR05   R      030RW05 K5PG0GY M 031TF                     04920017      00612             -300          A JS
        SUSAP KHUFK5FR05   R      040         0  M     CA                     0492        + 00875                              A JS
        SUSAP KHUFK5FR05   R      050IPEDYK5EA0EY      DF                                  + 02400                              A JS
        SUSAP KHUFK5FR05   R      060IPEDYK5EA0EE  R   HM                     22930040    + 02400                              A JS
```

QUALITY CHECKED

CITY AND STATE	ELEVATION: 589 THRE: 572	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
TERRE HAUTE, IN	AIRPORT NAME: TERRE HAUTE INTL-HULMAN FIELD	RNAV	RNAV (GPS) RWY 5, ORIG-B 15 DEC 2011	AMDT: ORIG-A DATED: 03/10/2011

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
RUNWAY  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KHUFK5GRW05    0090200492 N39262588W087192337+0100    +0141600572000040150I

                 1         2         3         4         5         6         7         8         9         0         1         2         3
PP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KHUFK5PR05   RW05 001 0000W05A0N3926258810W08719233725+014160300N3927264600W0871758960010675000000398F400500B352AB79
        SUSAP KHUFK5PR05   RW05 002E      +01743+01743LPV       82109

                 1         2         3         4         5         6         7         8         9         0         1         2         3
MSA     123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KHUFK5SRW05 K5PG                0   18018002625                                                                        M
```

QUALITY 1 CHECKED

CITY AND STATE	ELEVATION: 589 THRE: 572	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
TERRE HAUTE, IN	AIRPORT NAME: TERRE HAUTE INTL-HULMAN FIELD	RNAV	RNAV (GPS) RWY 5, ORIG-B 15 DEC 2011	AMDT: ORIG-A DATED: 03/10/2011