US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
SBV VORTAC	TEROC (FB)	055.44 / 25.69	3000
YUDUG (IAF)	NASAE (FB)	273.69 / 6.79	3000
TEROC (IAF)	NASAE (FB)	093.56 / 5.00	3000
NASAE (IF)	OCAPI (FB)	183.61 / 6.25	2100
OCAPI (FAF)	RW18 (MAP) (FO)	183.61 / 4.87	
RW18 (MAP)	903 MSL	183.61	
903 MSL	DOCMO (FO)		3000

MISSED APPROACH

LNAV: RW18

CLIMBING LEFT TURN TO 3000 DIRECT DOCMO AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000.

ADDITIONAL FLIGHT DATA:
HOLD SW, LT, 042.67 INBOUND.
FAS OBST: 806 AAO 365108N/0783010W
OCAPI TO RW18: 3.00/45.
CHART FARMVILLE MOA

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. PROFILE STARTS AT NASAE
3. FAC: 183.61 FAF: OCAPI DIST FAF TO MAP: 4.87 THLD: 4.87
4. MIN. ALT: NASAE 3000, OCAPI 2100
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: ____ GS ALT AT: ____ OM: ____ MM: ____ IM: ____
7. GS ANGLE: ____ TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW18 2600

MAG VAR: 9W EPOCH YEAR: 2005

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: N A X

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1520	3	1017	1520	3	1017		NA			NA				
CIRCLING	1520	3	1017	1520	3	1017		NA			NA				

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: USE SOUTH HILL ALTIMETER SETTING, WHEN NOT RECEIVED USE DANVILLE ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.
(SEE FORM 8260-10)

QUALITY CHECKED

CITY AND STATE	ELEVATION: 503 THRE: 503	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
CHASE CITY, VA	AIRPORT NAME: CHASE CITY MUNI	RNAV	RNAV (GPS) RWY 18, AMDT 1 20 SEPTEMBER 2012	AMDT: ORIG-A DATED 10/21/2010

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
CHART NOTE: PROCEDURE NA AT NIGHT.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SBV VORTAC ON AIRWAY RADIALS 032 CW 086.

QUALITY 1 CHECKED

CITY AND STATE	ELEVATION: 503 THRE: 503	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
CHASE CITY, VA	AIRPORT NAME: CHASE CITY MUNI	RNAV	RNAV (GPS) RWY 18, AMDT 1 20 SEPTEMBER 2012	AMDT: ORIG-A DATED: 10/21/2010

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - **FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
NAVAID  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAD        SBV   K6011040VTL  N36403015W079005221    N36403015W079005221W0050005301     NARSOUTH BOSTON

                 1         2         3         4         5         6         7         8         9         0         1         2         3
WP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAEAENRT   DOCMO K60    C   L N36510155W078232107                      W0095     NAR           DOCMO
        SUSAEAENRT   NASAE K60    W     N36583982W078312560                      W0094     NAR           NASAE
        SUSAEAENRT   OCAPI K60    W     N36522620W078304170                      W0094     NAR           OCAPI
        SUSAEAENRT   TEROC K60    W     N36581149W078373832                      W0093     NAR           TEROC
        SUSAEAENRT   YUDUG K60    C   L N36591786W078225907                      W0095     NAR           YUDUG

                 1         2         3         4         5         6         7         8         9         0         1         2         3
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KCXEK6ACXE     0     034YHN36471801W078300559W009000503         1800018000C    MNAR    CHASE CITY MUNI

                 1         2         3         4         5         6         7         8         9         0         1         2         3
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KCXEK6FR18   ASBV   010SBV  K6D 0V       IF                                          18000                  B JS
        SUSAP KCXEK6FR18   ASBV   020TEROCK6EA0E  A 020TF                     05540257    + 03000                         B JS
        SUSAP KCXEK6FR18   ASBV   030NASAEK6EA0EE B 010TF                     09360050    + 03000                         B JS
        SUSAP KCXEK6FR18   AYUDUG 010YUDUGK6EA0E  A    IF                                          18000                  B JS
        SUSAP KCXEK6FR18   AYUDUG 020NASAEK6EA0EE B 010TF                     27370068    + 03000                         B JS
        SUSAP KCXEK6FR18   R      010NASAEK6EA0E  I    IF                                  + 03000     18000              B JS
        SUSAP KCXEK6FR18   R      020OCAPIK6EA1E  F 051TF                     18360063    + 02100                 RW18  K6PGB JS
        SUSAP KCXEK6FR18   R      020OCAPIK6EA2WN          N          ALNAV                                                JS
        SUSAP KCXEK6FR18   R      030RW18 K6PG0GY M 031TF                     18360049      00548             -300         B JS
        SUSAP KCXEK6FR18   R      040         0  M     CA                     1836        + 00903                         B JS
        SUSAP KCXEK6FR18   R      050DOCMOK6EA0EY  L   DF                                  + 03000                         B JS
        SUSAP KCXEK6FR18   R      060DOCMOK6EA0EE  L   HM                     04270040    + 03000                         B JS

                 1         2         3         4         5         6         7         8         9         0         1         2         3
RUNWAY  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KCXEK6GRW18    0034001836 N36473470W078300753-0500    +0121700503000045050R

                 1         2         3         4         5         6         7         8         9         0         1         2         3
MSA     123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KCXEK6SRW18 K6PG                0   18018002625                                                                        M
```

QUALITY CHECKED

CITY AND STATE	ELEVATION: 503 THRE: 503	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
CHASE CITY, VA	AIRPORT NAME: **CHASE CITY MUNI**	**RNAV**	**RNAV (GPS) RWY 18, AMDT 1** 20 SEPTEMBER 2012	AMDT: **ORIG-A**
				DATED: **10/21/2010**

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - **FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	SBV	SBV	010		IF		FB					
	SBV	TEROC	020	IAF	TF		FB	2.0	055.4(046.4T)	025.7	AA 03000	
	SBV	NASAE	030		TF		FB	1.0	093.6(084.6T)	005.0	AA 03000	
	YUDUG	YUDUG	010	IAF	IF		FB					
	YUDUG	NASAE	020		TF		FB	1.0	273.7(264.7T)	006.8	AA 03000	
		NASAE	010	FACF	IF		FB				AA 03000	
		OCAPI	020	FAF	TF		FB	0.5	183.6(174.6T)	006.3	AA 02100	
		RW18	030	MAP	TF		FO	0.3	183.6(174.6T)	004.9	AT 00548	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		183.6(174.6T)		AA 00903	
	DOCMO	050		DF	L	FO				AA 03000	
	DOCMO	060		HM	L	FO		042.7(033.7T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	SBV	N364030.15	W0790052.21	N3640.503	W07900.870
	DOCMO	N365101.55	W0782321.07	N3651.026	W07823.351
	NASAE	N365839.82	W0783125.60	N3658.664	W07831.427
	OCAPI	N365226.20	W0783041.70	N3652.437	W07830.695
	TEROC	N365811.49	W0783738.32	N3658.192	W07837.639
	YUDUG	N365917.86	W0782259.07	N3659.298	W07822.985
	RW18	N364734.70	W0783007.53	N3647.578	W07830.126

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW18	00503	45

QUALITY 1 CHECKED

CITY AND STATE	ELEVATION: 503 THRE: 503	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
CHASE CITY, VA	AIRPORT NAME: **CHASE CITY MUNI**	**RNAV**	**RNAV (GPS) RWY 18, AMDT 1** 20 SEPTEMBER 2012	AMDT: **ORIG-A**
				DATED: **10/21/2010**