

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: OWB VOR/DME
PXV VORTAC	OWB VOR/DME	108.15 / 30.44	2500	CLIMB TO 2500 THEN LEFT TURN DIRECT OWB VOR/DME AND HOLD.
CCT VORTAC	OWB VOR/DME	013.13 / 22.14	2500	
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 184.58 INBOUND. CHART FAS OBST: 519 ELEV 374229N/0870932W CHART VDP AT 2.02 DME; DISTANCE VDP TO THLD 1.03 MILES. BIYAC TO RW36: 2.89/56. CHART MAXIMUM 6000 AT OWB VOR/DME. FAC CROSSES RWY C/L EXTENDED 3009 FROM THLD.

1. PT R SIDE OF COURSE 184.58 OUTBOUND 2100 FT WITHIN 10 MILES OF OWB VOR/DME (IAF)
2. _____
3. FAC 004.58 FAF _____ DIST FAF TO MAP _____ THLD _____
4. MIN. ALT BIYAC/OWB 3.10 DME 1100*
8. MSA FROM: OWB VOR/DME 2600

MAG VAR: 4W EPOCH YEAR: 2015

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: NA			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-36	1100	1/2	703	1100	1/2	703	1100	1 5/8	703	1100	1 5/8	703			
CIRCLING	1100	1	693	1100	1	693	1120	2	713	1140	2 1/4	733			
BIYAC FIX MINIMUMS															
S-36	780	1/2	383	780	1/2	383	780	3/4	383	780	3/4	383			
CIRCLING	860	1	453	880	1	473	1120	2	713	1140	2 1/4	733			

NOTES:
 *1160 WHEN USING EVANSVILLE ALTIMETER SETTING. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: VDP NA WITH EVANSVILLE ALTIMETER SETTING.
 CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-36 CATS C AND D VISIBILITY TO 2 MILE AND BIYAC FIX MINIMUMS S-36 CATS C AND D TO 1 1/8 MILE.
 (SEE FORM 8260-10)



CITY AND STATE OWENSBORO, KY	ELEVATION: 407	THRE: 397	FACILITY IDENTIFIER: OWB	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 36, AMDT 19, 11/15/2012	SUP	
	AIRPORT NAME: OWENSBORO-DAVISS COUNTY				AMDT	18
					DATE	06/03/2010

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE MALSR WITH EVANSVILLE ALTIMETER SETTING, INCREASE S-36 CAT B VISIBILITY TO 1 1/4 MILE AND CATS C AND D VISIBILITY TO 2 1/2 MILE.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EVANSVILLE ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, INCREASE S-36 CAT B VISIBILITY 1/4 MILE, CATS C AND D VISIBILITY 1/8 MILE, CIRCLING CATS B AND D VISIBILITY 1/4 MILE, AND CAT C VISIBILITY 1/2 MILE; INCREASE BIYAC FIX MINIMUMS S-36 CATS C AND D VISIBILITY 1/8 MILE AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE.



CITY AND STATE OWENSBORO, KY	ELEVATION: 407 THRE: 397 AIRPORT NAME: OWENSBORO-DAVIESS COUNTY	FACILITY IDENTIFIER: OWB	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 36, AMDT 19, 11/15/2012	SUP:
				AMDT: 18
				DATED: 06/03/2010