

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: OWB VOR/DME	
PXV VORTAC	OWB VOR/DME	108.15 / 30.44	2500	CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 2500 DIRECT OWB VOR/DME AND HOLD.	
APALO/PXV 43.08 DME	OWB VOR/DME	226.69 / 21.41	2500		
CCT VORTAC	OWB VOR/DME	013.13 / 22.14	2500		
				ADDITIONAL FLIGHT DATA: HOLD SW, RT, 047.89 INBOUND. CHART FAS OBST: 539 TREE 374446N/0871053W 609 AAO 374312N/0871423W CHART VDP AT 1.72 DME; DISTANCE VDP TO THLD 1.16 MILES. CECAG TO RW06: 2.82/45. FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD.	

1. PT L SIDE OF COURSE 227.89 OUTBOUND 2100 FT WITHIN 10 MILES OF OWB VOR/DME (IAF)
 2. _____
 3. FAC 047.89 FAF _____ DIST FAF TO MAP _____ THLD _____
 4. MIN. ALT CECAG/OWB 3.00 DME 1180*
 8. MSA FROM: OWB VOR/DME 2600

MAG VAR: 4W EPOCH YEAR: 2015

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-6	1180	1	775	1180	1 1/4	775	1180	2 1/2	775	1180	2 1/2	775			
CIRCLING	1180	1	773	1180	1 1/4	773	1180	2 1/2	773	1180	2 1/2	773			

CECAG FIX MINIMUMS															
S-6	820	1	415	820	1	415	820	1 1/8	415	820	1 1/8	415			
CIRCLING	860	1	453	880	1	473	1120	2	713	1140	2 1/4	733			

NOTES:
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 *1240 WHEN USING EVANSVILLE ALTIMETER SETTING.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EVANSVILLE ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET; INCREASE CIRCLING CAT A AND D VISIBILITY 1/4 MILE; CECAG FIX MINIMUMS S-6 AND (SEE FORM 8260-10)
 @ CAT C, D 800-2 1/2
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE OWENSBORO, KY	ELEVATION: 407	THRE: 405	FACILITY IDENTIFIER: OWB	PROCEDURE NO./AMD NO./EFFECTIVE DATE: VOR RWY 6, AMDT 2, 11/15/2012	SUP	VOR RWY 5
	AIRPORT NAME: OWENSBORO-DAVISS COUNTY				AMD	1
					DATE	09/28/2006

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CIRCLING CAT C AND D VISIBILITY 1/4 MILE.

CHART NOTE: VDP NA WITH EVANSVILLE ALTIMETER SETTING.

CITY AND STATE

OWENSBORO, KY

ELEVATION: 407

THRE: 405

AIRPORT NAME:

OWENSBORO-DAVIESS COUNTY

FACILITY IDENTIFIER:

OWB

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

VOR RWY 6, AMDT 2, 11/15/2012

SUP: VOR RWY 5

AMDT: 1

DATED: 09/28/2006