

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
 OR 26R. PROCEDURE NOT AUTHORIZED WHEN GLIDE SLOPE NOT AVAILABLE. DUAL VHF COMM REQUIRED. SEE
 ADDITIONAL REQUIREMENTS ON AAUP.
 CHART PLANVIEW NOTE: RADAR REQUIRED.



CITY AND STATE ATLANTA, GA	ELEVATION: 1026 THRE: 998	FACILITY IDENTIFIER: I-PKU	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: ILS PRM RWY 28, AMDT 2A, 11/15/2012 ILS PRM RWY 28 (CAT II) (SIMULTANEOUS CLOSE PARALLEL)	SUP: ILS PRM RWY 28
	AIRPORT NAME: HARTSFIELD - JACKSON ATLANTA INTL			AMDT: 2
				DATED: 05/05/2011

