US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
COQXA (IAF)	VIDKY (NOPT) (FB)	087.02 / 6.00	3500
ERXAV (IAF)	VIDKY (NOPT) (FB)	267.16 / 6.00	3500
VIDKY (IF/IAF)	OYAVY (FB)	177.09 / 6.30	2500

MISSED APPROACH

LPV: DA
LNAV/VNAV: DA
LNAV: RW18R

CLIMB TO 3500 DIRECT SUSNE AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD S, RT, 357.08 INBOUND.
CHART FAS OBST: 680 TREE 361244N/0955347W
CHART FAS OBST: 1020 TOWER 361646N/0955539W
DISTANCE TO THLD FROM 200 HAT: 0.54 NM.
CHART VDP AT 1.59 MILES TO RW18R* *LNAV ONLY.
WAAS CHANNEL # 69614
REFERENCE PATH ID: W18B
CHART: ASR

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD N VIDKY, RT, 177.09 INBOUND, 3500 FT. IN LIEU OF PT (IAF)
3. FAC: 177.08 FAF: OYAVY DIST FAF TO MAP: 5.58 THLD: 5.58
4. MIN. ALT: VIDKY 3500, OYAVY 2500
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: 2500 GS ALT AT: OYAVY 2500 OM: ____ MM: ____ IM: ____
7. GS ANGLE: 3.00 TCH: 59.5 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: 6E EPOCH YEAR: 1990

MINIMUMS

TAKEOFF: | | STANDARD | X | SEE FAA FORM 8260-15A FOR THIS AIRPORT | ALTERNATE: N A | | STANDARD @

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	867	3/4	200	867	3/4	200	867	3/4	200	867	3/4	200	867	3/4	200
LNAV/VNAV DA	978	1 1/4	311	978	1 1/4	311	978	1 1/4	311	978	1 1/4	311	978	1 1/4	311
LNAV MDA	1160	1	493	1160	1	493	1160	1 1/4	493	1160	1 1/2	493	1160	1 3/4	493
CIRCLING	1160	1	483	1160	1	483	1160	1 1/2	483	1300	2	623	1300	2 1/4	623

NOTES:
CHART NOTE: CIRCLING NA FOR CAT E S OF RWY 8-26.
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

@ CAT E 800-2 1/4

QUALITY CHECKED

CITY AND STATE	ELEVATION: 677 TDZE: 667	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 18R
TULSA, OK	AIRPORT NAME: TULSA INTL	RNAV	RNAV (GPS) Y RWY 18R, AMDT 1A 23 SEP 2010	AMDT: 1 DATED 08/27/2009

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	087/30 CW 267/30 (NOPT)	VIDKY (IF/IAF) (FB)	3500
2.	267/30 CW 357/30	ERXAV (IAF) (FB)	3600
3.	357/30 CW 087/30	COQXA (IAF) (FB)	3500

QUALITY CHECKED

CITY AND STATE	ELEVATION: 677 TDZE: 667	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 18R
TULSA, OK	AIRPORT NAME: TULSA INTL	RNAV	RNAV (GPS) Y RWY 18R, AMDT 1A 23 SEP 2010	AMDT: 1 DATED: 08/27/2009

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD	DATA
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KTUL
RUNWAY	RW18R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18B
LTP/FTP LATITUDE	361226.0000N
LTP/FTP LONGITUDE	0955356.7300W
LTP/FTP ELLIPSOIDAL HEIGHT	+01644
FPAP LATITUDE	361125.7500N
FPAP LONGITUDE	0955400.7300W
THRESHOLD CROSSING HEIGHT (TCH)	00059.5
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
CRC REMAINDER	FF7760A5

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+01934
FPAP ORTHOMETRIC HEIGHT	+01934

QUALITY CHECKED

CITY AND STATE	ELEVATION: 677 TDZE: 667	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 18R
TULSA, OK	AIRPORT NAME: TULSA INTL	RNAV	RNAV (GPS) Y RWY 18R, AMDT 1A 23 SEP 2010	AMDT: 1 DATED: 08/27/2009

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
WP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAEAENRT   COQXA K40    W     N36243796W096003464                     E0035     NAR           COQXA
        SUSAEAENRT   ERXAV K40    W     N36235910W095454400                     E0034     NAR           ERXAV
        SUSAEAENRT   OYAVY K40    W     N36180107W095533446                     E0034     NAR           OYAVY
        SUSAEAENRT   SUSNE K40    W     N35591558W095544920                     E0035     NAR           SUSNE
        SUSAEAENRT   VIDKY K40    W     N36241876W095530929                     E0034     NAR           VIDKY

                 1         2         3         4         5         6         7         8         9         0         1         2         3
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KTULK4ATUL     0     099YHN36115420W095531720E006000677         1800018000C    MNAR    TULSA INTL

                 1         2         3         4         5         6         7         8         9         0         1         2         3
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KTULK4FR18RY ACOQXA 010COQXAK4EA0E  A    IF                                                18000                A JS
        SUSAP KTULK4FR18RY ACOQXA 020VIDKYK4EA0EE B 010TF                     08700060    + 03500                                A JS
        SUSAP KTULK4FR18RY AERXAV 010ERXAVK4EA0E  A    IF                                                18000                A JS
        SUSAP KTULK4FR18RY AERXAV 020VIDKYK4EA0EE B 010TF                     26720060    + 03500                                A JS
        SUSAP KTULK4FR18RY AVIDKY 010VIDKYK4EA0EE AR   HF                     17710040    + 03500     18000                      A JS
        SUSAP KTULK4FR18RY R      010VIDKYK4EA0E  I    IF                                + 03500     18000                      A JS
        SUSAP KTULK4FR18RY R      020OYAVYK4EA1E  F 051TF                     17710063    + 02500                                A JS
        SUSAP KTULK4FR18RY R      020OYAVYK4EA2WALPV       ALNAV/VNAV ALNAV                                                        JS
        SUSAP KTULK4FR18RY R      030RW18RK4PG0GY M 031TF                     17710056      00694            -300                A JS
        SUSAP KTULK4FR18RY R      040         0  M  010CA                     1771        + 00867                                A JS
        SUSAP KTULK4FR18RY R      050SUSNEK4EA0EY   010DF                                 + 03500                                A JS
        SUSAP KTULK4FR18RY R      060SUSNEK4EA0EE  R020HM                     35710040    + 03500                                A JS

                 1         2         3         4         5         6         7         8         9         0         1         2         3
RUNWAY  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KTULK4GRW18R   0061011771 N36122600W095535673+0700    +0164400634000060150I

                 1         2         3         4         5         6         7         8         9         0         1         2         3
PP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KTULK4PR18RY RW18R001Y0000W18B0N3612260000W09553567300+016440300N3611257500W09554007300106750000000595F400350FF7760A5
```

QUALITY & CHECKED

CITY AND STATE	ELEVATION: 677 TDZE: 667	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 18R
TULSA, OK	AIRPORT NAME: TULSA INTL	RNAV	RNAV (GPS) Y RWY 18R, AMDT 1A 23 SEP 2010	AMDT: 1 DATED: 08/27/2009

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

```
                1         2         3         4         5         6         7         8         9         0         1         2         3
PP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KTULK4PR18RY RW18R002E      +01934+01934LPV       69614
```

QUALITY CHECKED

CITY AND STATE	ELEVATION: 677 TDZE: 667	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 18R
TULSA, OK	AIRPORT NAME: TULSA INTL	RNAV	RNAV (GPS) Y RWY 18R, AMDT 1A 23 SEP 2010	AMDT: 1 DATED: 08/27/2009