

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
SARANAC LAKE, NY	ADIRONDACK RGNL	20 SEPTEMBER 2012	7

TAKEOFF MINIMUMS:

RWY 5: STANDARD WITH A MINIMUM CLIMB OF 265 FT PER NM TO 4300, OR 2500-3 FOR CLIMB IN VISUAL CONDITIONS.
RWY 9: 800-2 1/4.
RWY 23: STANDARD WITH A MINIMUM CLIMB OF 270 FT PER NM TO 3100, OR 2500-3 FOR CLIMB IN VISUAL CONDITIONS.
RWY 27: STANDARD.

TEXTUAL DEPARTURE PROCEDURES:

RWY 5: CLIMB HEADING 048.89 TO 4300 BEFORE PROCEEDING ON COURSE. OR FOR CLIMB IN VISUAL CONDITIONS: CROSS ADIRONDACK REGIONAL AIRPORT AT OR ABOVE 4000 BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.
RWY 9: CLIMBING LEFT TURN HEADING 079.12 TO INTERCEPT SLK VOR/DME R-081.00 EASTBOUND TO 3700, THEN CLIMBING LEFT TURN DIRECT SLK VOR/DME AND HOLD (N, RT, 159.26 DEGREES INBOUND). CONTINUE CLIMB IN HOLD TO DEPART SLK VOR/DME AT OR ABOVE MEA FOR ROUTE OF FLIGHT.
RWY 23: CLIMB HEADING 228.9 TO INTERCEPT SLK VOR/DME R-232.00 WESTBOUND TO 4600 BEFORE PROCEEDING ON COURSE, OR FOR CLIMB IN VISUAL CONDITIONS: CROSS ADIRONDACK REGIONAL AIRPORT AT OR ABOVE 4000 BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.
RWY 27: CLIMB HEADING 273.13 TO 3600 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 5, VEHICLE ON ROAD 178 FT FROM DER, LEFT OF CENTERLINE, UP TO 15 FT AGL/1691 FT MSL. TREES BEGINNING 1421 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/1756 FT MSL.
NOTE: RWY 9, TERRAIN 61 FT FROM DER, 421 FT LEFT OF CENTERLINE, 1643 FT MSL. TREES AND VEGETATION BEGINNING 100 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 116 FT AGL/1789 FT MSL. TOWER 7982 FT FROM DER, 1868 FT RIGHT OF CENTERLINE, 140 FT AGL/2225 FT MSL. TREE 11105 FT FROM DER, 2564 FT LEFT OF CENTERLINE, 100 FT AGL/1938 FT MSL.
NOTE: RWY 23, TREES BEGINNING 93 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/1745 FT MSL.
NOTE: RWY 27, TREES AND VEGETATION BEGINNING 109 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/1756 FT MSL.

CONTROLLING OBSTACLES:

RWY 5: 5086 FT MSL AAO, 442156.00N-0735411.00W.
RWY 9: 2225 MSL TOWER, 442254.00N-0741003.00W. 1938 MSL TREE, 442342.80N-0740932.25W.
RWY 23: 2726 MSL TREE, 441748.61N-0741518.77W.
RWY 5, 9, 23 (VCOA): 5086 MSL AAO, 441256.00N-0735411.00W
OBSTACLES MANDATING ROUTE DEVELOPMENT: RWY 5, RWY 9 - 5086 MSL AAO, 445156.00N-0735411.00W. RWY 23 - 4725 MSL AAO, 440933.80N-0741219.90W. RWY 27 - 3274 MSL AAO, 442431.47N-0741946.46W.

6/11/12
1
CHECKED