

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
 NDB STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ERI VORTAC	ESMER LOM	058.66 / 2.10	2800	MAP: 4.06 MILES AFTER ESMER LOM CLIMB TO 3200 ON ERI VORTAC R-064 TO HAMIT INT/ERI 17.67 DME AND HOLD, OR AS DIRECTED BY ATC. ALTERNATE MA: CLIMB TO 2000 THEN CLIMBING LEFT TURN TO 3000 DIRECT ESMER LOM AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 243.64 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD SW ESMER LOM, LT, 064.00 INBOUND. FAS OBST: 1050 AAO 420145N/0801320W 1070 AAO 420133N/0801350W CHART IN PLANVIEW: ESMER LOM. ESMER LOM TO RW06: 3.05/55.

1. PT R SIDE OF COURSE 244.26 OUTBOUND 2800 FT WITHIN 10 MILES OF ESMER LOM (IAF)
2. _____
3. FAC 064.26 FAF ESMER LOM DIST FAF TO MAP 4.06 THLD 4.06
4. MIN. ALT ESMER LOM 2100
8. MSA FROM: ER LOM 3200

MAG VAR: 10W EPOCH YEAR: 2015

MINIMUMS

TAKEOFF:		SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY	=====>	A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-6		1360	4000	628	1360	4000	628	1360	1 3/8	628	1360	1 3/8	628			
CIRCLING		1360	1	628	1360	1	628	1380	1 3/4	648	1380	2	648			

NOTES:

CHART NOTE: CIRCLING TO RWY 02 AND 20 NA AT NIGHT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ASHTABULA, OH ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET, S-6 CATS C AND D VISIBILITY 1/4 MILE AND CIRCLING CATS C AND D VISIBILITY 1/2 MILE.
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 @ NA WHEN CONTROL TOWER CLOSED.

QUALITY
2
3/2/13

CITY AND STATE ERIE, PA	ELEVATION: 732 THRE: 732	FACILITY IDENTIFIER: ER	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 6, AMDT 2 7 MARCH 2013	SUP
	AIRPORT NAME: ERIE INTL/TOM RIDGE FIELD			AMDT 1
				DATE 07/02/2009

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-6 CATS C AND D VISIBILITY TO 1 3/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW RVR 4000 NOT AUTHORIZED.

CHART NOTE: FOR INOPERATIVE MALSR, WHEN USING ASHTABULA, OH ALTIMETER SETTING, INCREASE S-6 CATS C AND D VISIBILITY TO 2 MILE.



CITY AND STATE ERIE, PA	ELEVATION: 732	THRE: 732	FACILITY IDENTIFIER: ER	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			NDB RWY 6, AMDT 2	AMDT: 1
	ERIE INTL/TOM RIDGE FIELD			7 MARCH 2013	DATED: 07/02/2009