US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
BARET (IAF)	ZUSUB (FB)	229.00 / 7.62	5300
ZUSUB	LYNDI (FB)	230.11 / 3.84	5000
LYNDI	VYDDA (FB)	236.77 / 3.00	4000
VYDDA (IF)	OKAIN (FB)	272.14 / 2.00	3600
OKAIN	CIJHI (FB)	272.12 / 3.50	2500
CIJHI	REEBO (FB)	272.09 / 2.20	1800
REEBO (FAF)	RW27 (MAP) (FO)	272.06 / 5.20	
(SEE FORM 8260-10)			

MISSED APPROACH

LP: RW27
LNAV: RW27

CLIMBING LEFT TURN TO 2500 DIRECT SARGS AND HOLD.

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. PROFILE STARTS AT VYDDA
3. FAC: 272.06 FAF: REEBO DIST FAF TO MAP: 5.20 THLD: 5.20
4. MIN. ALT: VYDDA 4000, OKAIN 3600, CIJHI 2500, REEBO 1800
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: ____ GS ALT AT: ____ OM: ____ MM: ____ IM: ____
7. GS ANGLE: ____ TCH: 50.0 34:1 IS NOT CLEAR
8. MSA FROM: RW27 5400

ADDITIONAL FLIGHT DATA:
HOLD W, RT, 092.00 INBOUND.
CHART FAS OBST: 502 LIGHT 324306N/1170928W
CHART 803 TOWER 324314N/1170417W.
WAAS CHANNEL # 82527
REFERENCE PATH ID: W27A
REEBO TO RWY 27 3.14/50.
LTP HAE: -30.5 M

MAG VAR: 14E EPOCH YEAR: 1980

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A @

CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	680	5500	665	680	5500	665	680	1 7/8	665	680	1 7/8	665			
LNAV MDA	760	5500	745	760	6000	745	760	2	745	760	2	745			
CIRCLING	820	1	803	820	1 1/4	803	820	2 1/4	803	820	2 1/2	803			

NOTES:
CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY.
CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 27 PROCEDURE NA AT NIGHT.
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
(SEE FORM 8260-10)

@ CAT A, B 900-2, CAT C 900-2 1/4, CAT D 900-2 1/2

CITY AND STATE	ELEVATION: 17 THRE: 15	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
SAN DIEGO, CA	AIRPORT NAME: SAN DIEGO INTL	RNAV	RNAV (GPS) RWY 27, AMDT 2 PY &%" 201T	AMDT: 1
				DATED 11/20/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW27 (MAP)	417 MSL	272.06	
417 MSL	SARGS (FO)		2500

NOTES, (CONT.):
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BARET ON V66-460-514 EASTBOUND.

CITY AND STATE	ELEVATION: 17 THRE: 15	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
SAN DIEGO, CA	AIRPORT NAME: SAN DIEGO INTL	RNAV	RNAV (GPS) RWY 27, AMDT 2 PŸ &%" 201T	AMDT: 1
				DATED: 11/20/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD	DATA
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSAN
RUNWAY	RW27
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W27A
LTP/FTP LATITUDE	324352.9235N
LTP/FTP LONGITUDE	1171050.2495W
LTP/FTP ELLIPSOIDAL HEIGHT	-00305
FPAP LATITUDE	324417.5360N
FPAP LONGITUDE	1171231.7850W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.14
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0440
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
CRC REMAINDER	DEF90080

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+00045
FPAP ORTHOMETRIC HEIGHT	+00045

QUALITY CHECKED

CITY AND STATE	ELEVATION: 17 THRE: 15	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
SAN DIEGO, CA	AIRPORT NAME: SAN DIEGO INTL	RNAV	RNAV (GPS) RWY 27, AMDT 2 PŸ &%" 201T	AMDT: 1
				DATED: 11/20/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

```
                1         2         3         4         5         6         7         8         9         0         1         2         3
WP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAEAENRT   BARET K20    C   L N32462679W116403887                      E0121     NAR          BARET
        SUSAEAENRT   CIJHI K20    C     N32414993W117022448                      E0121     NAR          CIJHI
        SUSAEAENRT   LYNDI K20    W     N32411760W116524750                      E0121     NAR          LYNDI
        SUSAEAENRT   OKAIN K20    C     N32405156W116582541                      E0121     NAR          OKAIN
        SUSAEAENRT   REEBO K20    C     N32422655W117045479                      E0121     NAR          REEBO
        SUSAEAENRT   SARGS K20    C   L N32465419W117232234                      E0122     NAR          SARGS
        SUSAEAENRT   VYDDA K20    C     N32401815W116560884                      E0121     NAR          VYDDA
        SUSAEAENRT   ZUSUB K20    W     N32425844W116484198                      E0121     NAR          ZUSUB

                1         2         3         4         5         6         7         8         9         0         1         2         3
AIRPORT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KSANK2ASAN     0     094YHN32440080W117112280E014000017         1800018000C    MNAR    SAN DIEGO INTL

                1         2         3         4         5         6         7         8         9         0         1         2         3
SEGMENT 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KSANK2FR27   ABARET 010BARETK2EA0E  A    IF                                                18000                A JS
        SUSAP KSANK2FR27   ABARET 020ZUSUBK2EA0E S  010TF                     22900076    + 05300                              A JS
        SUSAP KSANK2FR27   ABARET 030LYNDIK2EA0E S  010TF                     23010038    + 05000                              A JS
        SUSAP KSANK2FR27   ABARET 040VYDDAK2EA0EE B 010TF                     23680030    + 04000                              A JS
        SUSAP KSANK2FR27   R      010VYDDAK2EA0E  I    IF                                 + 04000     18000                    A JS
        SUSAP KSANK2FR27   R      011OKAINK2EA0E S  051TF                     27210020    + 03600                              A JS
        SUSAP KSANK2FR27   R      012CIJHIK2EA0E S  051TF                     27210035    + 02500                              A JS
        SUSAP KSANK2FR27   R      020REEBOK2EA1E  F 051TF                     27210022    + 01800                  RW27  K2PGA JS
        SUSAP KSANK2FR27   R      020REEBOK2EA2WALP        N          ALNAV                                                      JS
        SUSAP KSANK2FR27   R      030RW27 K2PG0GY M 031TF                     27210052      00065             -314            A JS
        SUSAP KSANK2FR27   R      040          0  M     CA                    2721        + 00417                              A JS
        SUSAP KSANK2FR27   R      050SARGSK2EA0EY  L   DF                                 + 02500                              A JS
        SUSAP KSANK2FR27   R      060SARGSK2EA0EE  R   HM                     09200040    + 02500                              A JS

                1         2         3         4         5         6         7         8         9         0         1         2         3
RUNWAY  123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        ------------------------------------------------------------------------------------------------------------------------------------
        SUSAP KSANK2GRW27    0094012720 N32435292W117105025+0000    -0030500015181050200R
```

QUALITY CHECKED

CITY AND STATE	ELEVATION: 17 THRE: 15	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
SAN DIEGO, CA	AIRPORT NAME: SAN DIEGO INTL	RNAV	RNAV (GPS) RWY 27, AMDT 2 PŸ &%" 201T	AMDT: 1
				DATED: 11/20/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above aiport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

```
                 1         2         3         4         5         6         7         8         9         0         1         2         3
PP      123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KSANK2PR27   RW27 001 0000W27A0N3243529235W11710502495-003050314N3244175360W11712317850106750440000500F400000DEF90080
        SUSAP KSANK2PR27   RW27 002E      +00045+00045LP        82527

                 1         2         3         4         5         6         7         8         9         0         1         2         3
MSA     123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        --------------------------------------------------------------------------------------------------------------------------------
        SUSAP KSANK2SRW27 K2PG                0   18018005425                                                                       M
```

CITY AND STATE	ELEVATION: 17 THRE: 15	FACILITY IDENTIFIER:	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:	SUP:
SAN DIEGO, CA	AIRPORT NAME: SAN DIEGO INTL	RNAV	RNAV (GPS) RWY 27, AMDT 2	AMDT: 1
			PŸ &%" 201T	DATED: 11/20/2008