U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
HILEY (40E)	MANTY (TF)(FB)(RNP 1.00) (40E)(43A)	155.97/20.89	3000
MANTY (IAF)(40E)(43A)	ZILBI (TF)(FB)(RNP 1.00)(40E) (41E)	233.12/12.16	3000
FLIPR (IAF)(40E)(43A)	ZILBI (TF)(FB)(RNP 1.00)(40E) (41E)	335.46/28.91	3000
ZILBI (IF)(40E)(43I)	BASHO (TF)(FB)(RNP 1.00)(40E) (42S)	272.52/5.85	3000
BASHO (40E)(42S)	AGLER (TF)(FB)(RNP 1.00)(40E) (43F)	272.52/4.40	1600
AGLER (FAF)(40E)(43F)	RW26L (TF)(FO)(40G)(41Y)(43M)	272.44/4.75	
RW26L (MAP)(40G)(41Y)(43M)	LAWNN (DF)(FB)(40E)		
LAWNN (40E)	BRBRA (TF)(FO)(40E)(41E) (43H)	344.63/10.85	2000

MISSED APPROACH

MAP: DA

CLIMB TO 2000 DIRECT LAWNN AND VIA 344.83 TRACK TO BRBRA AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD NW, RT, 155.68 INBOUND
CHART FAS OBST: 126 BLDG 254830N/0801523W, 208 BLDG 254739N/0801441W
DISTANCE TO THLD FROM 399 HAT: 1.07 NM
ROUTE TYPE: A, R
ROUTE TYPE QUALIFIER 1: P
ROUTE TYPE QUALIFIER 2: S
CHART MANDATORY 3,000 AT MANTY
#TCH 65.8 MSL (DO NOT CHART)

1. PT NA SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
2. PROFILE STARTS AT ZILBI
3. FAC: 272.44 FAF: _____ DIST FAF TO MAP: _____ THLD: _____
4. MIN. ALT: ZILBI 3000, BASHO 3000
5. DIST TO THLD FROM OM: 4.75 MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
6. MIN GS INCPT: 1600 GS ALT AT: AGLER 1600 OM: _____ MM: _____ IM: _____
7. GS ANGLE: 3.00 TCH: 57.7# 34:1 IS NOT CLEAR
8. MSA FROM: RW26L 2900

MAG VAR: 5W EPOCH YEAR: 2000

MINIMUMS

TAKEOFF: | STANDARD | X | SEE FAA FORM 8260-15A FOR THIS AIRPORT | ALTERNATE: N A | X

CATEGORY ======>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
SPECIAL AIRCRAFT AND AIRCREW AUTHORIZATION REQUIRED															
RNP 0.20 DA	407	4500	399	407	4500	399	407	4500	399	407	4500	399			
RNP 0.30 DA	564	1 1/2	556	564	1 1/2	556	564	1 1/2	556	564	1 1/2	556			

NOTES: CHART NOTES: GPS REQUIRED. FOR INOPERATIVE MALSR, INCREASE RNP 0.20 ALL CATS VISIBILITY TO RVR 6000, RNP 0.30 ALL CATS VISIBILITY TO 2. FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW 6C (42F) OR ABOVE 48C (119F). CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT. CHART PLANVIEW NOTE AT HILEY: (RNP 1.00).

CITY AND STATE	ELEVATION: 8 TDZE: 8 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
MIAMI, FL	MIAMI INTL	RNAV	AUG 30 2007 RNAV (RNP) Y RWY 26L, ORIG	AMDT: NONE DATE

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (RNP) **STANDARD INSTRUMENT APPROACH PROCEDURE**

FLIGHT STANDARDS SERVICES TITLE 14 CFR FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-17

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	FLIPR	FLIPR	010	IAF	IF		FB				
	FLIPR	ZILPI	020	IF	TF		FB	1.0	335.5 (331T)	028.9	03000
	HILEY	HILEY	010		IF		FB				
	HILEY	MANTY	020	IAF	TF		FB	1.0	156.0 (151T)	020.9	03000 MAN
	HILEY	ZILPI	030	IF	TF		FB	1.0	233.1 (228T)	012.2	03000
		ZILPI	010	FACF	IF		FB				03000
		BASHO	011	SDF	TF		FB	1.0	272.5 (268T)	005.9	03000
		AGLER	020	FAF	TF		FB	1.0	272.5 (268T)	004.4	01600
		RW26L	030	MAP	TF		FO	0.3	272.4 (267T)	004.8	00066 MAN

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	LAWNN	040		DF		FB	1.0			
	BRBRA	050		TF		FO	1.0	344.6 (340T)	010.9	02000
	BRBRA	060		HM	R	FO	2.0	155.7 (151T)	004.0	02000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	AGLER	N254820.15	W0801054.53	N2548.336	W08010.909
	BASHO	N254831.89	W0800602.52	N2548.532	W08006.042
	BRBRA	N255802.23	W0802710.87	N2558.037	W08027.181
	FLIPR	N252334.49	W0794346.44	N2523.575	W07943.774
	HILEY	N261515.81	W0800047.11	N2615.264	W08000.785
	LAWNN	N254750.14	W0802302.07	N2547.836	W08023.035
	MANTY	N255655.99	W0794932.31	N2556.933	W07949.539
	ZILBI	N254847.26	W0795934.02	N2548.788	W07959.567
	RW26L	N254807.26	W0801610.33	N2548.121	W08016.172

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW26L	00008	58

CITY AND STATE	ELEVATION: 8 TDZE: 8 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
MIAMI, FL	MIAMI INTL	RNAV	AUG 30 2007 RNAV (RNP) Y RWY 26L, ORIG	AMDT: NONE
				DATED: