

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
SNS VORTAC	RIGDE INT/SNS 17.98 DME	261.80 / 17.98	3500	MAP: 5.00 MILES AFTER OLMIE INT/12.98 DME OR AT SNS 7.98 DME FIX CLIMB TO 1200 THEN CLIMBING LEFT TURN TO 3300 ON HEADING 230 AND ON SNS VORTAC R-262 TO RIGDE INT/SNS 17.98 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 081.80 INBOUND. CHART FAS OBST: 369 TOWER 364128N/1214804W CHART VDP AT 9.53 DME; DISTANCE VDP TO THLD 1.55 MILES. OLMIE TO RW11: 3.06/40.
SAGUE INT/SNS 25.19 DME (IAF)	RIGDE INT/SNS 17.98 DME (NOPT)	081.80 / 7.21 (SNS R-262)	3300	
RIGDE INT/SNS 17.98 DME (IF/IAF)	OLMIE INT/SNS 12.98 DME	081.80 / 5.00 (SNS R-262)	1800	

1. PT L SIDE OF COURSE 261.80 OUTBOUND 3300 FT WITHIN 10 MILES OF RIGDE (IAF)
- 2.
3. FAC 081.80 FAF OLMIE INT/SNS 12.98 DME DIST FAF TO MAP 5.00 THLD 5.00
4. MIN. ALT RIGDE 3300, OLMIE 1800
8. MSA FROM: SNS VORTAC 100-220 6300, 220-310 4200, 310-100 5200

MAG VAR: 17E EPOCH YEAR:1965

MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: NA		X		D			E		
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-11	680	1	544	680	1	544		NA			NA					
CIRCLING	680	1	543	700	1	563		NA			NA					

NOTES:
 CHART NOTE: ADF OR DME REQUIRED.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SAGUE ON V27 NORTHWEST BOUND.
 CHART PLANVIEW NOTE: ADF OR DME REQUIRED.
 (SEE FORM 8260-10)

QUALITY
1
CHECKED

CITY AND STATE	ELEVATION: 137 AIRPORT NAME:	THRE: 136	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
MARINA, CA	MARINA MUNI		SNS	20 SEPTEMBER 2012 VOR RWY 11, AMDT 2	AMDT 1
					DATE 02/11/2010

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VDP NA WITH MONTEREY ALTIMETER SETTING.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MONTEREY ALTIMETER SETTING AND INCREASE ALL MDA 40 FT.

QUALITY
 1
 CHECKED

CITY AND STATE MARINA, CA	ELEVATION: 137 THRE: 136 AIRPORT NAME: MARINA MUNI	FACILITY IDENTIFIER: SNS	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: 20 SEPTEMBER 2012 VOR RWY 11, AMDT 2	SUP:
				AMDT: 1
				DATED: 02/11/2010