

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
HARKE INT	GTP NDB	126.85 / 12.37	2000	MAP: 3.97 MILES AFTER GTP NDB
OTK VOR/DME	GTP NDB	292.72 / 30.17	2000	CLIMBING LEFT TURN TO 2000 DIRECT GTP NDB AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2000.
GEF VORTAC	GTP NDB	353.72 / 24.42	2500	
SZW VORTAC	GTP NDB	047.53 / 37.12	2400	
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 222.16 INBOUND. CHART FAS OBST: 399 TREE 305606N/0835005W GTP NDB TO RW22: 3.11/59.

1. PT L SIDE OF COURSE 042.16 OUTBOUND 2000 FT WITHIN 10 MILES OF GTP NDB (IAF)
 2. _____
 3. FAC 222.16 FAF GTP NDB DIST FAF TO MAP 3.97 THLD 3.97
 4. MIN. ALT GTP NDB 1600
 8. MSA FROM: GTP NDB 3300

MAG VAR: 2W EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	<input checked="" type="checkbox"/>								
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-22	700	3/4	470	700	3/4	470	700	1 1/8	470	700	1 1/8	470				
CIRCLING	700	1	436	720	1	456	720	1 1/2	456	840	2	576				

NOTES:
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VALDOSTA ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET, INCREASE S-22 AND CIRCLING CAT C AND D VISIBILITY 1/4 MILE.
 (SEE FORM 8260-10)

QUALITY
1
CHECKED

CITY AND STATE THOMASVILLE, GA	ELEVATION: 264	THRE: 230	FACILITY IDENTIFIER: GTP	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 22, AMDT 6 2 MAY 2013	SUP	
	AIRPORT NAME: THOMASVILLE RGNL				AMDT	5
					DATE	09/25/2008

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE MALSF, INCREASE S-22 ALL CATS 1/4 MILE.

6/12/11
1
09/25/08

CITY AND STATE THOMASVILLE, GA	ELEVATION: 264 THRE: 230 AIRPORT NAME: THOMASVILLE RGNL	FACILITY IDENTIFIER: GTP	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 22, AMDT 6 2 MAY 2013	SUP:
				AMDT: 5
				DATED: 09/25/2008