

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

| TERMINAL ROUTES | | | | MISSED APPROACH |
|-----------------|-------------|---------------------|----------|--|
| FROM | TO | COURSE AND DISTANCE | ALTITUDE | MAP: FAH VOR/DME |
| NEROE INT | MTW VOR/DME | 221.00 / 13.52 | 3000 | CLIMB TO 2000 THEN CLIMBING RIGHT TURN TO 3000 DIRECT FAH VOR/DME AND HOLD. |
| MTW VOR/DME | FAH VOR/DME | 200.79 / 22.79 | 3000 | |
| | | | | ADDITIONAL FLIGHT DATA: HOLD NE, RT, 208.83 INBOUND. FAS OBST: 999 AAO 435356N/0874919W CHART R-6903. CHART VDP AT 2.83 DME; DISTANCE VDP TO THLD 2.22 MILES. FAC CROSSES RWY C/L EXTENDED 3005 FROM THLD. |

1. PT L SIDE OF COURSE 028.83 OUTBOUND 2700 FT WITHIN 10 MILES OF FAH VOR/DME (IAF)
 2. _____
 3. FAC 208.83 FAF _____ DIST FAF TO MAP _____ THLD _____
 4. MIN. ALT _____
 8. MSA FROM: FAH VOR/DME 2700

MAG VAR: 2W EPOCH YEAR: 1990

MINIMUMS

| TAKEOFF: | SEE FAA FORM 8260-15A FOR THIS AIRPORT | | | | | | ALTERNATE: N/A | STANDARD @ | | | | | | | | |
|-----------------|--|-----|---------|------|-----|---------|----------------|------------|---------|------|-------|---------|-----|-----|---------|--|
| CATEGORY =====> | A | | | B | | | C | | | D | | | E | | | |
| | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | MDA | VIS | HAT/HAA | |
| S-22 | 1500 | 1/2 | 757 | 1500 | 3/4 | 757 | 1500 | 1 3/4 | 757 | 1500 | 1 3/4 | 757 | | | | |
| CIRCLING | 1500 | 1 | 745 | 1500 | 1 | 745 | 1500 | 2 1/4 | 745 | 1500 | 2 1/2 | 745 | | | | |
| | | | | | | | | | | | | | | | | |

NOTES:
 CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 13/31 NA AT NIGHT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MANITOWOC ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET, INCREASE S-22 CAT C/D VISIBILITY 1/4 MILE.
 CHART NOTE: VDP NA WITH MANITOWOC ALTIMETER SETTING.
 @ CAT C 800-2 1/4, CAT D 800-2 1/2
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.



| | | | | |
|--|---|------------------------------------|---|--------------------|
| CITY AND STATE SHEBOYGAN, WI | ELEVATION: 755 THRE: 743 | FACILITY IDENTIFIER: FAH | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 22, AMDT 9 10 JANUARY 2013 | SUP VOR RWY 21 |
| | AIRPORT NAME: SHEBOYGAN COUNTY MEMORIAL | | | AMDT 8B |
| | | | | DATE 12/15/2011 |