

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
LADIN INT	HTL VOR/DME	097.55 / 21.40	4000
BANJO INT	HTL VOR/DME	310.13 / 25.78	3100

MISSED APPROACH

MAP: HTL VOR/DME

CLIMB TO 2000 THEN CLIMBING RIGHT TURN TO 3000 DIRECT HTL VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:
 HOLD E, RT, 261.90 INBOUND.
 CHART FAS OBST: 1329 TREE 442309N/0843712W
 1345 AAO 442320N/0843649W
 1559 AAO 442438N/0843346W.
 DIDMY TO RW27: 3.08/32.
 CHART MAXIMUM 6000 AT HTL VOR/DME.
 FAC CROSSES RWY C/L EXTENDED 3002 FROM THLD.

- PT L SIDE OF COURSE 081.90 OUTBOUND 2800 FT WITHIN 10 MILES OF HTL VOR/DME (IAF)
-
- FAC 261.90 FAF _____ DIST FAF TO MAP _____ THLD _____
- MIN. ALT DIDMY/HTL 2.28 DME 1840*
- MSA FROM: HOUGHTON LAKE VOR/DME 3300

MAG VAR: 5W EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	STANDARD @								
CATEGORY ==>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-27	1840	1	695	1840	1	695	1840	2	695	1840	2	695				
CIRCLING	1840	1	690	1840	1	690	1840	2	690	1840	2 1/4	690				
DIDMY FIX MINIMUMS (DME REQUIRED)																
S-27	1580	1	435	1580	1	435	1580	1 1/4	435	1580	1 1/4	435				
CIRCLING	1600	1	450	1600	1	450	1600	1 1/2	450	1700	2	550				

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 *1960 WHEN USING GAYLORD ALTIMETER SETTING.
 (SEE FORM 8260-10)

@ CAT D 800-2 1/4
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE HOUGHTON LAKE, MI	ELEVATION: 1150 THRE: 1145	FACILITY IDENTIFIER: HTL	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
	AIRPORT NAME: ROSCOMMON COUNTY - BLODGETT MEMORIAL		VOR RWY 27, AMDT 4 7 MARCH 2013	AMDT 3
				DATE 10/25/2007

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GAYLORD ALTIMETER SETTING AND INCREASE

ALL MDA 120 FT. INCREASE S-27 CAT B VISIBILITY 1/4, INCREASE CAT C/D VISIBILITY 1/2. DIDMY FIX

MINIMUMS WHEN USING GAYLORD ALTIMETER SETTING INCREASE CAT C 3/8 AND CIRCLING CAT C 1/8.

CHART NOTE: CAT D STRAIGHT-IN MINIMUMS NA WHEN USING GAYLORD ALTIMETER SETTING.



CITY AND STATE HOUGHTON LAKE, MI	ELEVATION: 1150 THRE: 1145 AIRPORT NAME: ROSCOMMON COUNTY - BLODGETT MEMORIAL	FACILITY IDENTIFIER: HTL	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 27, AMDT 4 7 MARCH 2013	SUP:
				AMDT: 3
				DATED: 10/25/2007