

**SANDY VALLEY****SKY RANCH** (3L2) 2 SW UTC-8(-7DT) N35°47.58' W115°37.59'**LAS VEGAS**

2599 NOTAM FILE RNO

L-7D

**RWY 03-21:** H3340X45 (ASPH) RWY LGTS(NSTD)**RWY 03:** Rgt tfc.**RWY 21:** Thld dsplcd 180'. Road.**RWY 12-30:** 3300X105 (DIRT)**RWY 12:** Rgt tfc.**SERVICE:** LGT Rwy 03-21 rwy lgts NSTD. Rwy 03-21 thld lgts only.**NOISE:** Avoid noise sensitive residential area 1.5 miles NE of arpt.**AIRPORT REMARKS:** Attended irregularly. Low flying military acft in area. Ultralight activity on and infov arpt. Ocnl wild horses on and infov acft movement areas. Rwy 03-21 obstacle free area ltd to 96' either side of centerline. Unmarked and unlighted power poles/lines NW/SE of Rwy 03-21. No line of sight between rwy ends. Arpt is a residential airpark, auto tfc is on and across rwys and twys. Rwy 21 dsplcd thld marked with 8' white lines. RWY 03-21 RTHL only. RWY edges marked with reflectors. Rwy 12-30 thld not marked.**AIRPORT MANAGER:** 702-420-3559**COMMUNICATIONS:** CTAF/UNICOM 123.0**CLEARANCE DELIVERY PHONE:** For CD ctc Las Vegas Apch at 725-200-4432.**RADIO AIDS TO NAVIGATION:** NOTAM FILE LAS.**LAS VEGAS (VH) (H) VORTACW** 116.9 LAS Chan 116 N36°04.78' W115°09.59' 218° 28.5 NM to fld. 2136/15E.

No NOTAM MP: 1600-1800Z± Sat

VOR unusable:

025°-160° byd 20 NM blo 6,000'

029°-033° byd 40 NM

034°-047° byd 40 NM blo 15,000'

034°-047° byd 80 NM

060°-071° byd 40 NM blo 10,000'

060°-071° byd 51 NM

078°-203° byd 40 NM

160°-200° byd 20 NM blo 9,000'

200°-025° byd 25 NM blo 11,000'

200°-220° byd 15 NM blo 9,000'

204°-214° byd 40 NM blo 14,000'

204°-214° byd 46 NM

215°-245° byd 40 NM

220°-245° byd 35 NM blo 15,000'

245°-260° byd 35 NM blo 14,000'

246°-256° byd 40 NM blo 14,000'

246°-256° byd 47 NM

257°-008° byd 40 NM

260°-275° byd 35 NM blo 14,000'

275°-310° byd 35 NM blo 16,500'

TACAN AZIMUTH unusable:

025°-160° byd 20 NM blo 6,000'

160°-200° byd 20 NM blo 9,000'

200°-025° byd 25 NM blo 11,000'

200°-220° byd 15 NM blo 9,000'

220°-245° byd 35 NM blo 15,000'

245°-260° byd 35 NM blo 14,000'

260°-275° byd 35 NM blo 14,000'

275°-310° byd 35 NM blo 16,500'

DME unusable:

025°-160° byd 20 NM blo 6,000'

160°-200° byd 20 NM blo 9,000'

200°-025° byd 25 NM blo 11,000'

200°-220° byd 15 NM blo 9,000'

220°-245° byd 35 NM blo 15,000'

245°-260° byd 35 NM blo 14,000'

260°-275° byd 35 NM blo 14,000'

275°-310° byd 35 NM blo 16,500'