HELICOPTER ROUTE CHART
DETROIT
LEGEND

Consult Airport/Facility Directory (A/FD) for details concerning airport lighting, navigation aids and services.
All times are local. For additional symbol information refer to the Chart User's Guide.

AIRPORTS

- Hard-surface runways 1500 ft. or greater
- Open dot within hard-surface runway configuration indicates approximate VOR, VORTAC or VOR/DME location
- All recognizable hard-surface runways, including those closed, are shown for visual identification.
- Other than hard-surface paved runway
- Private use

HELIPORTS

- Heliport - public use
- Heliport - private use
- Helipad
- Trauma Center
- Helipad located on building
- Existing airport heliport in operation Sunset to Sunrise

OBJECTIONABLE - Airport may adversely affect airspace use.

OTHER

- Obstacle Free Zone
- Emergency Flight Path Corridor
- Seaplane Base

AIRPORT DATA

Box indicates FAR 91, Special Air Traffic Rules & Airport Traffic Patterns.

FSS — NO SVFR — FAR 91

NAME — NAME.PNAME — (ICAO) Location Identifier

CT - 118.3 ✆ ATIS 123.8 — Shown when location identifier differs from contiguous U.S.

285 L 122.95 — (Unverified) — UNICOM

Unverified Heliport — Airport of Entry — ADE

FSS - Flight Service Station
NO SVFR - Fixed-wing special VFR flight is prohibited.
CT - 118.3 - Control Tower and primary frequency.
✆ - Box indicates operation and time. See name frequencies tabulation for hours of operation.
◐ - Follows the Common Traffic Advisory Frequency (CTAF)
ATIS 123.8 - Automatic Terminal Information Service
ASOS/AWOS 135.42 - Automated Surface Weather Observing Systems shown where full-time ATIS not available). Some ASOS/AWOS facilities may have voice capability.
UNICOM - Aeronautical advisory station
285 - Elevation in feet
L - Lighting in operation Sunset to Sunrise
*L - Lighting limitations exist; refer to Airport/Facility Directory.
Lighting codes refer to runway edge lights. If no runway character is replaced by a dash, lighting codes refer to runway edge lights.

RADIO AIDS TO NAVIGATION AND COMMUNICATION BOXES

- VHF OMNI RANGE (VOR)
- VORTAC
- VOR-DME
- Other facilities, i.e., TACAN, NDB, RCO, etc.
- Non-Directional Radio Beacon (NDB)
- NDB - OMNI

Example: 120.1R 122.6 123.8 — CHICAGO HEIGHTS — 360° 116.8 OAK — 120.1R — CHICAGO CHI

Underline indicates Part-time frequency.
Omnibearing indicates Shutdown status.
Arrowhead indicates Continuous or On-Request.
A - ASOS/AWOS
V - VRA/S
FSS radio providing voice communication.

Heavy line box indicates Flight Service Station (FSS). Normal hours are 0700-2300 EST. FSS may be unattended at many FSSs and are not shown above boxes. All other frequencies are shown.
Refer to Airport/Facility Directory, Airport Advisory Service, see A/FD.
R - Receive only
Frequencies above this line box are rerouted to NAVAID box. Other FSS frequencies providing voice communication may be available as determined by Airport/Facility Directory. Consult Airport/Facility Directory for complete information.

AIRPORT TRAFFIC SERVICE AND AIRSPACE INFORMATION

Only the controlled and reserved airspace effective below 14,500 ft. MSL are shown on this chart.

HELICOPTER ROUTES

PRIMARY — MARRIOTT — 118.3 — Compulsory - Non - Compulsory
SECONDARY (MILITARY)
TRANSITION
ROUTE SEGMENT

Route Name — Tower Frequency — Arrow Indicates One-way Route — Altitude Assigned — Reporting or Holding Points

ZONE — Maximum Altitude — 500 Minimum — 500 Recommended — Recommended Route Altitude

Class D Airspace
Class E Airspace (Mode C - see FAR 91.215(b&c))
36 — Class B/Class C Airspace Surface Area
MODE C Veil (see FAR 91.215(b&c))

Class D Airspace
Ceiling of Class D Airspace in hundreds of feet (a minus sign indicates class D surface up to but not including that value)
Class E Airspace
MTR - Military Training Route
VR21 L — Route Segment

Prohibited, Restricted, and Warning Areas
Alert Area and MOA - see Chart Supplement
Special Airport Traffic Area (see FAR 93 for details.)
ADIZ - Air Defense Identification Zone

OBSTRUCTIONS

1000 ft and higher AGL. Below 1000 ft AGL.
Group Obstruction
Obstruction with high intensity white strobe may operate part-time
Wind Turbine Farm
Elevation of the top above mean sea level
Wind Turbine
1049 (1148)
Under construction or reported position and existence unverified
NOTICE: Guy wires may extend outward from structures.
UC

TOPOGRAPHIC INFORMATION

Power Transmission Line
Aerial Cable
Landmark Tower
616 (Elevation Base of Tower)
CABLES
Pictorial Symbol

MISCELLANEOUS

Glider Activity
Ultralight Activity
Glider Operations
Unmanned Aircraft Activity
VFR Waypoints (See chart tabulation for coordinates/symbols)
Parachute Jumping Area (See Airport/Facility Directory)
VPSYZ
NAME (VPSYZ)

DETROIT HELICOPTER
HELICOPTER ROUTE CHART SCALE 1:125,000

Federal Aviation Administration

2ND EDITION EFFECTIVE 0901Z **3 APR 2014**
Chart will become OBSOLETE FOR USE IN NAVIGATION upon publication of the next edition. See Dates of Latest Editions

Includes airspace amendments effective **3 APR 2014** and all other aeronautical data received by **6 FEB 2014**

Information on this chart will change; consolidated updates of chart changes are available every 56 days in the AIRPORT/FACILITY DIRECTORY Chart Bulletin section (online at http://aeronav.faa.gov). Also consult appropriate NOTICES TO AIRMEN (NOTAMs) and other FLIGHT INFORMATION PUBLICATIONS (FLIPs) for the latest changes.

PUBLISHED IN ACCORDANCE WITH INTERAGENCY AIR CARTOGRAPHIC COMMITTEE SPECIFICATIONS AND AGREEMENTS, APPROVED BY: DEPARTMENT OF DEFENSE * FEDERAL AVIATION ADMINISTRATION

Warning: Refer to current foreign charts and flight information publications for information within foreign airspace.

FAA Product ID: HELDET
NSN 7641015286487
NGA REF. NO.: HELOXDETROIT
EFF. DATE 14093

CONTROL TOWER FREQUENCIES ON DETROIT HELICOPTER ROUTE CHART

Airports with control towers are indicated on the face of the chart by the letters CT followed by the primary VHF local control frequency (last 3 decimals for each tower is listed in the table below. Operational hours are local time. The primary VHF and UHF local control frequencies are listed. An asterisk (*) indicates the part-time tower frequency is remoted to a collocated full-time FSS for use as Airport/Facility Service (A/FS) when the tower is closed. The primary VHF and UHF ground control frequencies are listed.
Automatic Terminal Information Service (ATIS) frequencies shown on the face of the chart are primary aircraft VHF/UHF frequencies.
All ATIS frequencies are listed in the table below. ATIS operational hours may differ from tower operational hours.
"NON-FR" indicates Monday through Friday.
OJT indicates other times.

CONTROL TOWER	OPERATES	TWR FREQ	GND CON	ATIS
ANN ARBOR	0800-2000	120.1	121.6	134.55
DETROIT METRO WAYNE CO	CONTINUOUS	118.4 (A/D) 119.2 (A/D) 121.65 (A/D) 317.725	119.25 (GE) 121.9 (NW) 121.8 (SW) 120.75 (SW)	133.975
OAKLAND CO INTL	0600-2400	120.5	121.9	125.025
ROMEO - SELFRIDGE ANGB	0700-2300, HOL	118.0 124.4	121.75 370.8	128.375.1
WILLOW RUN	CONTINUOUS	120.25 269.7	121.23	127.425
WINDSOR	0630-2230	124.7	121.7	134.3
YOUNG	CONTINUOUS	121.2 257.8	121.93	124.875

CLASS B, CLASS C, TRSA, AND SELECTED APPROACH CONTROL FREQUENCIES

FACILITY	FREQUENCIES	SERVICE AVAILABILITY
DETROIT CLASS B	127.2 239.2(S) (WAYNE) 128.75 239.2(N) 118.95 239.2(S) (SW) 124.85 ABOVE 3000' MSL (EAST) 120.9 239.2(N) ABOVE 3000' MSL CLASS B: CTL ZONE OR BELOW 3000' MSL CONTACT WINDSOR APP CON	CONTINUOUS
SELFRIDGE ANGB	124.8 338.4 O/T: 127.7, 290.425 (CLEVELAND CNTR)	0700-2300

REPORTING CHART ERRORS

You are requested to inform us of chart errors and/or additions that come to your attention while using this chart. Telephone toll free at 1-800-626-3677, or email us at 9-AMC-AeroProducts@faa.gov. Suggestions may be submitted via the Aeronautical Publications website at http://aeronav.faa.gov. See the FAQs prior to contact via toll free number or email. When a chart change or data is required, such information should be depicted clearly and accurately on a current chart, and a replacement copy will be returned. Mail to: FAA, AeroNav Products, SSMC-4 Sta. #4603, 1305 East West Highway, Silver Spring, MD 20910-3281.

FOR PROCUREMENT:

Contact an Authorized FAA Chart Sales Agent. Visit our website at http://aeronav.faa.gov for an agent near you.
For digital products, contact FAA, AeroNav Products at 1-800-638-9972.

Lambert Conformal Conic Projection Standard Parallels 33° and 45°
Horizontal Datum: North American Datum of 1983 (World Geodetic System 1984)

Published by the U.S. Department of Transportation
Federal Aviation Administration
AeroNav Products
http://aeronav.faa.gov



EXAMPLES OF CLASS B ALTITUDES

70 - - - Ceiling in hundreds of feet MSL
30 - - - Floor in hundreds of feet MSL

Class G Airspace within the United States extends up to but not including 1,200 feet above the surface of the earth within Class E Airspace, excluding the airspace less than 1000 feet above the terrain and certain special use airspace areas.

Features normally used as checkpoints for controlling VFR traffic are emphasized on this series of charts so they may be readily identified.

Example: ⊙ POWER PLANT.

The name shown is that used by the controlling personnel and is not necessarily the official name of the feature.

DESCRIPTION OF ROUTES AND ALTITUDES

ALL ROUTES MAY BE ALTERED AT PILOT'S REQUEST OR AS DIRECTED BY ATC. ROUTE ALTITUDES ARE MAXIMUM.

BELLEVILLE: NOVI TO BELLEVILLE VIA I-275.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY DETROIT METRO WAYNE CO TOWER.

CITY BYPASS: ANN ARBOR TO GRAND RIVER AVE VIA M-14 AND I-96.
ALTITUDES: AT OR BELOW 1500 FEET MSL.

CROSSTOWN: NOVI TO LAKE ST. CLAIR VIA I-96 AND I-696.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY DETROIT METRO WAYNE CO TOWER.

DEARBORN: SOUTHFIELD TO I-75 VIA GOLD BLDG. SOUTHFIELD FREEWAY (M-39) TO FORD WORLD HEADQUARTERS (GLASS HOUSE) TO FORD FACTORY.
ALTITUDES: AT OR BELOW 1500 FEET MSL.

DETROIT METRO: WYANDOTTE TO DETROIT METRO WAYNE CO AIRPORT VIA GODDARD ROAD.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY DETROIT METRO WAYNE CO TOWER.

M-59 CROSSTOWN: HOWELL TO MT. CLEMENS VIA M-59.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY OAKLAND CO INTL TOWER OR SELFRIDGE ANGB TOWER.

MIDDLEBELT: FLAT ROCK TO METRO AIRPORT VIA MIDDLEBELT ROAD.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY DETROIT METRO WAYNE CO TOWER.

MOTOWN: PONTIAC SILVERDOME TO DOWNTOWN DETROIT VIA I-75 AND WOODWARD AVE (M-1).
ALTITUDES: AT OR BELOW 1500 FEET MSL.

SHORELINE: MT. CLEMENS TO MONROE VIA THE SHORELINE SOUTH AND I-75.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY YOUNG TOWER.

SPARTAN: HOWELL TO DOWNTOWN DETROIT VIA I-96 NOVI THEN GRAND RIVER AVE (M-5).
ALTITUDES: AT OR BELOW 1500 FEET MSL.

WILLOW RUN: ANN ARBOR TO DETROIT METRO WAYNE CO AIRPORT VIA I-94.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY ANN ARBOR TOWER, WILLOW RUN TOWER OR DETROIT METRO WAYNE CO TOWER.

WOLVERINE: BRIGHTON (M-59) TO DUNDEE VIA US-23 THRU ANN ARBOR.
ALTITUDES: AT OR BELOW 1500 FEET MSL UNLESS OTHERWISE AUTHORIZED BY ANN ARBOR TOWER.

CAUTION
PILOTS ARE REQUESTED TO SELF ANNOUNCE ON 123.025 2 MILES PRIOR TO CROSSING ANY ROUTE.

ALL ROUTES ARE RECOMMENDED ROUTES WHICH PILOTS MAY EXPECT TO RECEIVE WHEN AUTHORIZED TO OPERATE IN THE CLASS B AIRSPACE. UNLESS OTHERWISE INDICATED, ALTITUDES WILL BE ASSIGNED WHEN CONTACTING AIR TRAFFIC CONTROL. HELICOPTER ROUTE AND ALTITUDE ASSIGNMENTS DO NOT RELIEVE PILOTS FROM THEIR DUTY TO COMPLY WITH FAR 91.119 AND 135.203(b). PILOTS ARE EXPECTED TO REQUEST AN ALTERNATE CLEARANCE IF NECESSARY FOR COMPLIANCE.

CAUTION: ROUTES DEPICTED AND ALTITUDES ASSIGNED DO NOT PROVIDE OBSTACLE CLEARANCE PROTECTION. PILOTS ARE RESPONSIBLE FOR SEEING AND AVOIDING TERRAIN AND OBSTACLES. THIS CHART DOES NOT DEPICT COMPLETE OBSTACLE INFORMATION DUE TO THE HIGH CONCENTRATION OF OBJECTS IN THE AREA. OBSTACLES AND OTHER FEATURES SUCH AS POWER TRANSMISSION LINES AND PROMINENT STRUCTURES ARE DEPICTED FOR LANDMARK VALUE ONLY.

ATTENTION
THIS CHART CONTAINS MAXIMUM ELEVATION FIGURES (MEF). The Maximum Elevation Figures shown in quadrangles bounded by ticked lines of latitude and longitude are represented in THOUSANDS and HUNDREDS of feet above mean sea level. The MEF is based on information available concerning the highest known feature in each quadrangle, including terrain and obstructions (trees, towers, antennas,etc.).
Example: 12,500 feet 125

CAUTION: This chart is primarily designed for VFR navigational purposes and does not purport to indicate the presence of all power transmission and telecommunication lines, terrain or obstacles which may be encountered below reasonable and safe altitudes.

NORTH AMERICAN AEROSPACE DEFENSE COMMAND (NORAD) PROCEDURES
All aircraft operating in the U.S. national airspace, if capable, will maintain a listening watch on guard frequencies VHF 121.5 or UHF 243.0. It is incumbent upon all aviators to know and understand their responsibilities if intercepted. Review "AIM" section 5-6-2 for intercept procedures. Additionally, if U.S. military fighter jets intercept an aircraft and flares are dispensed in the area of that aircraft, aviators will pay strict attention, contact air traffic control immediately on the local frequency or on VHF guard 121.5 or UHF 243.0 and follow the intercept visual ICAO signals. Be advised that non-compliance may result in the use of force.

NOTE: REFER TO CURRENT CANADIAN CHARTS AND FLIGHT INFORMATION PUBLICATIONS FOR INFORMATION WITHIN CANADIAN AIRSPACE.

AIRSPACE CLASSIFICATION (SEE CANADA FLIGHT SUPPLEMENT) AND OPERATIONAL REQUIREMENTS (DOD USERS, SEE DOD AREA PLANNING AP1) MAY DIFFER BETWEEN CANADA AND UNITED STATES

REGULATIONS REGARDING FLIGHTS OVER CHARTED NATIONAL PARK SERVICE AREAS, U.S. FISH AND WILDLIFE SERVICE AREAS, AND U.S. FOREST SERVICE AREAS

The landing of aircraft is prohibited on lands or waters administered by the National Park Service, U.S. Fish and Wildlife Service or U.S. Forest Service without authorization from the respective agency. Exceptions include: 1) aircraft engaged in official business of the respective agency that operates, 2) at officially designated landing sites, or 3) on approved official business of the Federal Government.
All aircraft are requested to maintain a minimum altitude of 2,000 feet above the surface of the following: Boundary of National Park Service areas, Fish and Wildlife Service areas, and U.S. Forest Service areas administered by the National Park Service, National Wildlife Refuges, Big Game Refuges, Game Ranges and Wildlife Ranges administered by the U.S. Fish and Wildlife Services and Wilderness and Primitive areas administered by the U.S. Forest Service. FAA Advisory Circular (AC) 91-36, "Visual Flight Rules (VFR) Flight Near Noise-Sensitive Areas," defines the surface as: the highest terrain within 2,000 feet laterally of the route of flight, or the upper-most rim of a canyon or valley.
Federal regulations also prohibit airdrops by aircraft or parachutes or other means of persons, cargo, or objects from aircraft on lands administered by the three agencies without authorization from the respective agency. Exceptions include: 1) emergencies involving the safety of human life, or 2) threat of serious property loss.

Boundary of National Park Service areas, U.S. Fish and Wildlife Service areas, and U.S. Forest Service Wilderness and Primitive areas.

MAPLE GROVE (6SQ) 908 °L 122.8
MAPLE GROVE (6W6) 906 °L 122.8
YOUNG (DET) CT 118.3 ATIS 123.8 285 L 122.95
CTC DETROIT APP ON 127.5 OR 239.275
HOWELL 243 CQW 76.75°
LIVINGSTON CO HARDY (OZW) AWOS-3 118.875 962 °L 123.0
ST JOSEPH MERCY (YIP) LIVINGSTON CO
HAIGH (PVI) 1000
JOHNSTON (PVI) 1000
MCKENZIES (PVI) 895
PONDEROSA (13G) 1017 °L 123.025
BRIGHTON (45G) 973 °L 122.9
RAETHER (6Y8) 982 °L 122.9
MCAULEY (PVI)
OAKLAND/SOUTHWEST (VLK) 926 °L 122.7
HELIPUTT 900
CACKLEBERRY (2E8) 890 °L 122.9
RICHMOND (69G) 821 °L 122.9
MEYERS-DIVERS (9TE) 815 °L 122.9
MERRILLAT (34G) 820 °L 122.8
GRADOLPH (88G) 673 °L 122.9
GODDING (PVI) 920
CANTON-PLYMOUTH-METTETAL (1D5) 698 °L 122.7
WESTLAND
GARDEN CITY OSTEO (Unverified)
DEARBORN HEIGHTS
INKSTER
DETROIT METRO
TAYLOR
SOUTHGATE
WYANDOTTE
LINCOLN PARK
ALLEN PARK
OAKWOOD HERITAGE
FORD WORLD HEADQUARTERS
DEARBORN
DEARBORN (6D6)
FARE AND PLAZA
HENRY FORD
MICHIGAN HEALTH & MEDICAL CENTER
DETROIT MEDICAL CENTER
FISHER BUILDING
NORTHWEST GENERAL (Unverified)
NORTH DETROIT GENERAL (Unverified)
RIVERVIEW (Unverified)
HENRY FORD WYANDOTTE
NORTHWEST GENERAL (Unverified)
CHRYSLER PROVING GROUND
WHITE OAKORN 960
ANN ARBOR (ARB) CT 120.1 ✆ ATIS 134.55 835 °L 122.95
ANN ARBOR MUNICIPAL
See NOTAMs/Directory for Class G UHF hrs
UMMC ARRIVE/DEP ROUTES
WILLOW RUN (YIP) CT 128.375 ATIS 127.425 716 °L
VOR/DME DETROIT 113.6 CB 81 DXO
INC SVFR DETROIT METRO WAYNE CO (DTW) CT 118.4, 135.9 ATIS 119.2 L 122.95
PRIOR TO ENTERING CANADIAN C CLASS C CTE ZONE ALL ACFT CTC WINDSOR TWR ON 124.7
CTC DETROIT APP ON 126.85 within Class B
CAUTION HEAVY VFR TRAFFIC BELOW FLOOR OF CLASS B AIRSPACE
Magnetic disturbance of as much as 7° exists at ground level in this vicinity
See NOTAMs/Directory for Class D aff hrs
PILOTS ARE REQUESTED TO SELF-ANNOUNCE ON 122.025 2 MILES PRIOR TO CROSSING ANY ROUTE
CTC DETROIT APP ON 127.5 OR 239.275
CTC DETROIT APP ON 134.3 OR 239.275
WINDSOR 353 GQ
WINDSOR (CYQG) CT 118.7 ATIS 134.5 ✆ 1425 L 122.8
Class G CZ
WINDSOR 113.6 CB 65 YQG
123.37 WINDSOR 113.6 CB 65 YQG (LONDON)
SARGEL 126 VQ 60.25
CAUTION RIVERSIDE DESCENT AREA BELOW 3000 MSL SEE RIVERSIDE DESCENT AREA INSET
UNITED STATES CANADA
TORONTO FIR CLYZ
LAKE ERIE
CAUTION PILOTS ARE REQUESTED TO SELF ANNOUNCE ON 123.025 2 MILES PRIOR TO CROSSING ANY ROUTE
VFR AIRSPACE RESTRICTIONS
No VFR flight within Canadian Class B Airspace is permitted unless ATC clearance is obtained.
A flight is, by but not including 19,500' AGL, unless being controlled by ATC. For additional details see appropriate Canadian publications.
NOTE: REFER TO CURRENT CANADIAN CHARTS AND FLIGHT INFORMATION PUBLICATIONS FOR INFORMATION WITHIN CANADIAN AIRSPACE.
CARLEL
CARLEL 122.55 122.2 DETROIT RDO LANSING
YOUNG (DET) CT 118.3 ATIS 123.8 285 L 122.95
CARLEL 124.8 338.4
CARLEL 120.1 ✆ ATIS 134.55 835 °L 122.95
CARLEL 118.4 ✆ ATIS 119.2 L 122.95
CARLEL 121.2 257.8
CARLEL 124.7 ✆ ATIS 134.3 1425 °L 122.8
CARLEL 120.25 269.7 ATIS 127.425 716 °L
CARLEL 118.0 124.4 ✆ ATIS 128.375.1 962 °L 123.0
CARLEL 120.5 ✆ ATIS 125.025 1414 °L 122.95
CARLEL 120.9 239.2(N) ABOVE 3000' MSL
CARLEL 124.85 ABOVE 3000' MSL (EAST)
CARLEL 118.95 239.2(S) (SW)
CARLEL 128.75 239.2(N)
CARLEL 127.2 239.2(S) (WAYNE)
CARLEL 120.1R 122.6 123.8 CHICAGO HEIGHTS
CARLEL 120.1R 122.6 123.8 CHICAGO CHI
CARLEL 118.3 ✆ ATIS 123.8 285 L 122.95