LAKE HURON
LEGEND

Airports having Control Towers are shown in Blue, all others in Magenta. Consult Chart Supplement for details involving airport lighting, navigation aids, and services. All roads are local. For additional symbol information refer to the Chart User's Guide.

AIRPORTS

Other than Heliport/Helistop
Seaplane Base
Hard-surface runways 1500 ft. to 8999 ft. in length
Hard-surface runways greater than 8999 ft. or some multiple runways less than 8999 ft.
Hard-surface runways less than 1500 ft. in length
Soft-surface runways
Heliport/Helistop
Military Airport
Military Heliport
Private Airport
Private Heliport
Seaplane Base
Ultralight Flightpark
Glider Site
Hang Glider Site
Parachute Jumping Site
Balloon Site
Abandoned Airport
Closed Airport
Landing Strip
Airport with operational control tower (may not operate 24 hours)
VOR/DME, or VORTAC location

All military airports are shown in blue. Some military airports may be closed, and shown for visual identification. Airports may be public or private.

ADDITIONAL AIRPORT INFORMATION

Private - PVT - Ownership, use restricted, landing emergency or permission required
Military - Other than hard-surface, all military airports, and some hard-surface runways at civil airports. Use restrictions may exist, contact controlling agency.
Abandoned - ABD - Airport no longer in use.
Closed - CLSD - Airport temporarily closed.
Right Traffic - Unless otherwise indicated, all turns are to the left.

Hard-surface runways 1500 ft. to 4200 ft. (specified by use of 3 digits around basic airport symbol). Consult Supplement for complete runway information. Runways less than 1500 ft. are not graphically represented.

Non-hard-surface runways less than 1500 ft.

OBJECTIONABLE - Airport may adversely affect airspace use.

AIRPORT TRAFFIC SERVICE AND AIRSPACE INFORMATION

Class B Airspace
Class C Airspace
Class D Airspace
Class E Airspace (Class E surface area begins at the surface, unless otherwise designated as shown above.)
Class E Airspace with floor greater than 700 ft. above surface
Class E Airspace with floor greater than 1200 ft. above surface
Class E Airspace with floor greater than 14,500 ft. msl
Class G Airspace (Uncontrolled airspace extending upward from the surface to the overlying controlled airspace.)
Special Use Airspace
Military Operations Area (MOA)
Restricted, Prohibited, Restricted - Public Use, Canadian Advisory Danger Area, Canadian Military Operations Area
Special Airport Traffic Area
Special Use Airspace
Special Airport Traffic Area
MTR - IR Military Training Route
MTR - VR Military Training Route
Alert Area
Caution Area
National Security Area
Other Airspace Area (Miscellaneous)
Training Area

Class B Airspace
Class C Airspace
Class D Airspace
Class E Airspace
Class E Airspace with floor greater than 700 ft. above surface
Class E Airspace with floor greater than 1200 ft. above surface
Class E Airspace with floor greater than 14,500 ft. msl
Class G Airspace (Uncontrolled airspace extending upward from the surface to the overlying controlled airspace.)

Dimensions from or above MSL unless otherwise indicated. Class B airspace, with ceiling and floor altitudes, consists of 3 000' MSL areas unless otherwise designated as shown above. Class C airspace, with ceiling and floor altitudes, consists of 4 000' MSL areas unless otherwise designated as shown above. Class D airspace, with ceiling and floor altitudes, consists of 2 500' MSL areas unless otherwise designated as shown above.

Class E airspace extends upward from the overlying controlled airspace to the base of the overlying controlled airspace.

Class G airspace extends upward from the surface to the base of the overlying controlled airspace.

Special Use Airspace, Other Airspace Area, and Military Training Route boundaries are shown in blue.

Total voltage (kilovolts) of wires above Class E Airspace but without Class E Surface Area

Obstruction Mark (Flashing)
Obstruction Mark (Steady Burning)
Group Obstruction
Obstruction with High Intensity White Strobe Lights (Flashing)
Obstruction with Synchronized Red Obstruction Lights (Flashing)

COMMUNICATION BOXES

CHICAGO CTR
135.35 132.6 125.2
346° 25NM 046° 25NM
ABOVE 12,000
ABOVE 17,000

Frequencies in boxes are normally those of the controlling agency. Frequencies in shaded boxes are those of a remote communications outlet. Controlling agency is shown in parentheses.

Flight Watch (EFAS) is available on 122.0 MHz (Canada - 123.5, 126.7 and 255.0) are available at 1,000 AGL or above, unless otherwise indicated. Use Flight Watch for en route weather information, enroute flight assistance, and search and rescue initiation.

Communication frequencies above this line are remoted to NAVAID site. Other FSS frequencies providing communications are shown on the airport. Consult Supplement for complete information.

135.35
FSS radio communications
122.2 (LRN)

RADIO AIDS TO NAVIGATION

VHF OMNI-RANGE (VOR)
VOR/DME
VORTAC
Non-Directional Radio Beacon (NDB)
NDB (HW)
Other facilities, i.e., FSS (ILM), etc.
VOR - DME

OBSTRUCTIONS

1000 ft and higher AGL
Mast - Height above ground
Mast - Height above ground, elevation of the highest terrain within 4 nm of the mast
Height above ground (AGL) and elevation above mean sea level (MSL) of the highest obstacle and of the highest terrain within 4 nm of the obstacle
Obstruction with High Intensity White Strobe Lights (Flashing) and Synchronized Red Obstruction Lights (Flashing)

MISCELLANEOUS

Aeronautical Reporting Point
Aeronautical Reporting Point (Compulsory)
Aeronautical Reporting Point (Non-Compulsory)
Aeronautical Reporting Point (Undesignated)
Special Aircraft Facility
Parachute Jumping Area
Space Launch Activity
Hazard Beacon

TOPOGRAPHIC INFORMATION

Ocean Topography
Coastline
Land Contour
Spot Elevation
Spot Elevation-Base of Tower
Shoreline Feature
Intermittent Water
Depth Curve
Rapids
Dam
Levee
Marina
Lighthouse
Beacon Light

LAKE HURON SECTIONAL
SECTIONAL AERONAUTICAL CHART SCALE 1:500,000

Federal Aviation Administration

91ST EDITION EFFECTIVE 0901Z **31 MAR 2016**
TO 0901Z **15 SEP 2016**

Includes airspace amendments effective **31 MAR 2016**
and all other aeronautical data received by **4 FEB 2016**

Information on this chart will change; consolidated major updates of chart changes are available every 56 days in the NOTICE TO AIRMEN (NOTAM) publication. Current or future NOTAM information may be found on the Internet at http://www.faa.gov/NOTAMS. Also consult appropriate NOTICE TO AIRMEN SECTIONS and other FLIGHT INFORMATION PUBLICATIONS (FLIPs) for the most current data.

PUBLISHED IN ACCORDANCE WITH INTERNATIONAL AIR CARTOGRAPHIC COMMITTEE SPECIFICATIONS AND AGREEMENTS APPROVED BY DEPARTMENT OF DEFENSE / FEDERAL AVIATION ADMINISTRATION

Warning: Refer to current foreign charts and flight information publications for information within foreign airspace.

FAA Product ID: SLH
NSN 7641014100141
Item Mfr. SECXOLAKEHURON

BIC DATE 16091

PLOTTING DIRECT ROUTE ON NORTH/SOUTH SIDE

There are approximately two minutes of latitude overlap between the north and south sides of each sectional/IFR/EC chart. To plot a course line from one side to the other, the user must first locate two identical points of reference, one point on each side of the chart, and follow the steps below.

STEP 1 – Draw a horizontal line (MATCH LINE).
STEP 2 – Select a point (POINT A) on the course line that clearly displays on each side of the chart just to the left or right of the vertical edge of the chart. (Figure 1)
STEP 3 – Decide which side of the chart has the most departure or destination point closer to the edge of the chart. Place the straight edge of a piece of paper along the MATCH LINE and the point should be visible on the edge of the paper. Mark point A on the paper.
STEP 4 – Slide the paper sideways left or right so that point A is positioned on the opposite side of the chart. Rotate the paper as necessary to align the course line with point A. Make a MARK A on edge of the paper where it meets that edge.
STEP 5 – Without moving the paper, on the same side of the chart, make a MARK B on the edge of the paper that the corner of the paper where it meets the MATCH LINE out to the edge of the chart. Make a LINE B.
STEP 6 – Turn the chart over and transfer the end of LINE B to the opposite side of the chart. Align it with the MATCH LINE. (Figure 2)
STEP 7 – Place the straight edge of the paper with MARK A and align the top or bottom edge of the paper with LINE B. Make a MARK C on the edge of the paper at the side of the chart extending off of the chart. This represents the distance from LINE B to point A. (Figure 3)
STEP 8 – Where your plot line crosses the MATCH LINE make a MARK C. Extend a line straight from point A to MARK C.
STEP 9 – Turn the chart back over and transfer MARK C to that side and extend it to the MATCH LINE. Plot a line from MARK C to the destination. (Figure 3)

CONTROL TOWER FREQUENCIES ON LAKE HURON SECTIONAL CHART

Airports with control towers are indicated on the face of the chart by the letters CT followed by the primary VHF local control frequency. Operators should use the tower frequency to taxi, takeoff, land, or transit the airport area. Ground control frequencies are listed in the communications box for each tower or, if not in the box, on the face of the chart. Pre-taxi clearance (PTC) and Departure Clearance (DCL) procedures are in effect at selected towers. Consult the Chart Supplement for participating towers and procedures. Automatic Terminal Information Service (ATIS) broadcasts are provided at many busy towers. Where ATIS is provided, pilots should monitor the ATIS broadcast prior to contacting the tower or ground control. Where Airport Advisory Service (AAS) during hours the tower is closed. The primary VHF and UHF ground control frequencies are listed.

All UHF frequencies are listed in the middle letter. ATIS frequencies are listed in the bottom letter. All AAS frequencies are listed in the middle letter. ATIS frequencies are listed only where they differ from tower operational hours.

ASR and/or RAR indicates Radar Instrument Approach available.

Tower hours are local time, H24 indicates continuous operation through Friday.

CONTROL TOWER	OPERATES	TWR FREQ	GND CON	ATIS	ASR/PAR
HURON CO INTL	0900-2100 ANN(W)		121.9	128.2	
	SAT-SUN 1000-1800				
OWOSSO, MAP	0800-1700 ANN(W)	134.2	121.9		
	SAT-SUN 1000-1600				
TRAVERSE CITY, MAP	0700-2300	118.3	121.9	135.05	
WIXOM, 3MDI	CONTINUOUS		124.4	121.9	125.45 257.7

CLASS B, CLASS C, TRSA, AND SELECTED APPROACH CONTROL FREQUENCIES

FACILITY	FREQUENCIES	SERVICE AVAILABILITY
GRAYLING, AAR	118.3	

SPECIAL USE AIRSPACE ON LAKE HURON SECTIONAL CHART

Unless otherwise noted altitudes are MSL and Time is Local.
SFC - Surface; GND - Ground Level; AGL - Above Ground Level; U - Unlimited; H - 24 Hours; Sunset to Sunrise; Sunset-2 - 2 Hours After Sunset; Sunset+30 - 30 Minutes After Sunset; Sunrise-60 - 60 Minutes Before Sunrise; Sunrise+30 - 30 Minutes After Sunrise; Sunrise to Sunset+30 - Sunrise to 30 Minutes After Sunset; Sunset-30 to Sunrise - 30 Minutes Before Sunset to Sunrise; Sunset-30 to Sunrise+30 - 30 Minutes Before Sunset to 30 Minutes After Sunrise; Sunset-60 to Sunrise+60 - 60 Minutes Before Sunset to 60 Minutes After Sunrise; Sunset-60 to Sunrise+30 - 60 Minutes Before Sunset to 30 Minutes After Sunrise; Sunset-30 to Sunrise+60 - 30 Minutes Before Sunset to 60 Minutes After Sunrise; Sunset-60 to Sunrise+60 - 60 Minutes Before Sunset to 60 Minutes After Sunrise; Sunset-30 to Sunrise+30 - 30 Minutes Before Sunset to 30 Minutes After Sunrise; Sunset-60 to Sunrise+60 - 60 Minutes Before Sunset to 60 Minutes After Sunrise; Sunset-30 to Sunrise+60 - 30 Minutes Before Sunset to 60 Minutes After Sunrise; Sunset-60 to Sunrise+30 - 60 Minutes Before Sunset to 30