LAS VEGAS

HI,HOS

NORTH

LEGEND

Airports having Control Towers are shown in Blue; all others in Magenta. Consult Chart Supplement for details involving airport lighting, navigation aids, services, & hours of operation. For additional airport information refer to the Chart User's Guide.

AIRPORTS

- Other than hard-surfaced runways
- Hard-surface runways 1500 ft. to 8069 ft. in length
- Hard-surface runways greater than 8069 ft. or with some multiple runways less than 8069 ft.
- Other than active hard-surfaced runway, Helicopter Only, Closed, Landing Strip, Private, Gliderport, or ARFOR, Incomplete
- Airport of entry. Customs landing rights airport, see Chart Supplement for hours of operation.

AIRPORT DATA

Data includes FAR 91 operational requirements, Control Tower & Airport Traffic Service (ATS) hours of operation, CTAF/UNICOM frequency, runway length, runway lighting, fuel availability, and operation limitations.

CTAF/UNICOM 123.0 | ATIS 135.4 | 120.1 (T) | 257.8 (H)

Airport name, elevation, and type of fuel available. 100LL = blue, Jet A = black, Mogas = green. Consult Chart Supplement for complete list of available fuels.

Airport beacon. White-green = civil airport. Alternating white-green-yellow = lighted heliport. Flashing white = military airport.

Segmented circle. Aligned with landing direction(s). Some have wind direction indicator.

Rotating beacon in operation Sunset to Sunrise

ADDITIONAL AIRPORT INFORMATION

Power "PPR" - Permissible only by permission of airport management.

Military - Other than hard-surfaced, all military airports are shown in blue. Consult Chart Supplement for details.

Parachute jumping activity within 5 statute miles of airport. Inquire locally for exact area and altitudes.

Rotating beacon in operation Sunset to Sunrise

AIRPORT TRAFFIC SERVICE AND AIRSPACE INFORMATION

Only the controlled and national airspace classes that apply to VFR operations are shown.

- Class B Airspace
- Class C Airspace (Mode C Veils)
- Class D Airspace
- Class E Airspace with floor of 700 feet AGL used in transition to and from the terminal environment.
- Class E Airspace with floor of 1200 feet AGL used to transition to/from the en route environment.

CLASS G Airspace from the surface to the overlying controlled airspace.

- Class E Airspace with floor of 1200 feet AGL designated in conjunction with Class G Airspace
- Class E Airspace with floor of 14,500 feet MSL designated in conjunction with Class A Airspace

2400 - 600 Obstructions found on the chart. Altitudes are MSL unless otherwise designated as shown above. Obstructions lighted at night or during periods of reduced visibility are indicated by solid line.

1149 Obstructions not charted on the chart, but reported to the FAA after the chart was published.

Total obstruction clearance and altitude for charted Class E Airspace over obstacles or terrain are indicated as follows:

- 1700 (1200) Feet MSL
- Feature
- Height above ground, Rounded up to nearest 100 feet.

Differentiates floors of Class E Airspace. Floors at 1200 feet AGL and above are charted.

Differentiates floors of Class E Airspace. Floors at 700 feet AGL and above are charted.

Class E Airspace with floor of 1200 feet AGL designated in conjunction with Class G Airspace

Total obstruction clearance and altitude for uncharted obstacles or terrain which exceed criteria for charted obstructions.

- 1700 (1200) Feet MSL
- Height above ground, Rounded up to nearest 100 feet.

Differentiates floors of Class E Airspace. Floors at 700 feet AGL and above are charted.

Class E Airspace with floor of 1200 feet AGL designated in conjunction with Class G Airspace

Class E Airspace with floor of 14,500 feet MSL designated in conjunction with Class A Airspace

COMMUNICATION BOXES

- 122.95 Frequency for communicating with aircraft.
- 122.8 Frequency for communicating with aircraft and ground station.
- 122.1R Receive only.
- 122.1T Transmit only.

Frequencies above this line are remoted to MIAMI ctlr. Elev 7720 frequencies providing Flight Following service are underlined.

Frequencies above this line are remoted to MIAMI ctlr. Elev 7720 frequencies providing Flight Following service are NOT underlined.

RADIO AIDS TO NAVIGATION

- VOR (VHF OMNI-RANGE)
- VORTAC
- VOR/DME
- DME
- Other facilities, i.e., TVOR (Dual), MCO (H), ...
- NDB
- NDB - DME

OBSTRUCTIONS

- 1000 ft and higher AGL
- Mean Sea Level
- Above 1000 ft. AGL
- Above 2000 ft. AGL
- Above 5000 ft. AGL
- Mean Sea Level
- Wind Turbine Farm
- Elevation of the top above mean sea level. Where multiple obstructions are charted, the highest obstruction determines the elevation value shown.
- Obstruction lighted. Where multiple obstructions are charted, the highest obstruction determines the lighting status shown. Red lights may be flashing.
- Group Obstruction. Where multiple obstructions are charted, the highest obstruction determines the elevation value shown.

MISCELLANEOUS

- Aerial Refueling Track (See Supplement)
- Aerial Refueling Track Anchor
- Aerial Refueling Track Direction
- Unmanned Aircraft Activity
- Aerial Refueling Area
- Parachute Jumping Area
- Marine Light
- Skydiving Area
- Glider Launch Activity, Winch or Towplane
- Hang Glider Activity
- Ultralight Activity
- Weather Reporting Station
- Weather Reporting Station with Radar
- Weather Reporting Station - Military
- Weather Reporting Station - Military with Radar

TOPOGRAPHIC INFORMATION

- Ridge
- Pass
- Normal Contour
- Index Contour
- 8191 Elevation Base of Feature

Mount Whitney 14,505

Shaded Relief

Flight Following Service is available on request and highly recommended in and around Class B, C, and TRSA areas.

Class G Airspace within the United States extends up to 14,500 feet MSL. At and above this altitude all airspace is within Class E Airspace, excluding the airspace less than 1200 feet above the terrain and certain special use airspace areas.

ATTRIBUTION ---

THIS CHART CONTAINS MAXIMUM ELEVATION FIGURES WITH-IN QUADRANGLES bounded by ticked latitude and longitude lines. The MEF is based on information available concerning the highest known feature in each quadrangle, including terrain and obstructions (towers, buildings, etc.).

Example: 12,500 feet 125

Published from digital files compiled in accordance with Interagency Air Cartographic Committee specifications and agreements approved by Department of Defense - Federal Aviation Administration.

Warning: Refer to current foreign charts and flight information publications for information within foreign airspace.

FAA Product ID: SLV

NSN 7641014100156

NGA SEC: SECSLVLASVEGAS

DAFIF SEC: 16231

LAS VEGAS SECTIONAL

HI,HOS

NORTH

SECTIONAL AERONAUTICAL CHART SCALE 1:500,000

Federal Aviation Administration

96TH EDITION EFFECTIVE 0901Z **18 AUG 2016**

TO 0901Z **2 MAR 2017**

Includes airspace amendments effective **21 JUL 2016**

and all other aeronautical data received by **23 JUN 2016**

Information on this chart will change. Unrestricted major updates of chart changes are available every 56 days in the CHART SUPPLEMENT Aeronautical Chart Bulletin section online at http://aeronav.faa.gov/index.asp?xml=aeronav/productcatalog. Also consult appropriate NOTAM publication. See the Publication Availability section in the Publications Policy for the latest changes. Consult/Subscribe to FAA Safety Alerts and Charting Notices at: https://www.faa.gov/air_traffic/flight_info/aeronav/safety_alerts/

Published from digital files compiled in accordance with Interagency Air Cartographic Committee specifications and agreements approved by Department of Defense - Federal Aviation Administration.

Warning: Refer to current foreign charts and flight information publications for information within foreign airspace.

FAA Product ID: SLV

NSN 7641014100156

NGA SEC: SECSLVLASVEGAS

DAFIF SEC: 16231

CONTROL TOWER FREQUENCIES ON LAS VEGAS SECTIONAL CHART

Airports with control towers are listed in alphabetical order. Frequencies are listed in order of use. Where more than one frequency is published, information for each tower is listed in the table below. Operational hours are listed first. The primary VHF and UHF tower and ground control frequencies are listed.

The Automatic Terminal Information Service (ATIS) frequencies shown on the face of the chart are arrival VHF/UHF frequencies. All ATIS frequencies are listed in the table below. ATIS operational hours may differ from tower operational hours.

AWI and/or VHF Omni-directional Range Approach available.

H24 = Continuous 24 Hours Per Day

(ex) indicates other hours.

CONTROL TOWER (OPERATES)	TOWER	GND. CON	ATIS	ASR/PAR
BAKER (0800-1700 LOCAL)	123.7	121.9	120.25	
BEATTY (0800-1700 LOCAL)	120.5 ALSO 396.8 (T) 347.8000 (H)			
CREECH AFB (0600-0000 L (0700-0000 L SAT-SUN))	118.8 344.025	128.0 370.8	290.45	
GRAND CANYON (0600-0000 L (0700-0000 L SAT-SUN))	123.95	121.9	134.3	
HENDERSON (H24)	120.1		135.15	
MCCARRAN INTL (H24)	CONTROLLED	(NORTH) 121.75 (EAST) 118.7 (SOUTH) 124.3 (WEST) 119.1 (SE OF RWY 01L/19R) 118.3 (SE OF RWY 01R/19L) 124.35 (SW OF RWY 01L/19R) 120.9 (SW OF RWY 01R/19L)	135.9	
MESQUITE (H24)	CONTROLLED	120.7 (H) 257.8 (T)	125.8 (H) 370.8 (T)	278.1
NORTH LAS VEGAS (0600-2300 (varied) (0700-2300 SAT-SUN))	120.7 389.75	121.7	118.55	
TONOPAH TEST RANGE (0600-1700 LOCAL)	124.05 257.95	127.25 330.5		

CLASS B, CLASS C, TRSA, AND SELECTED APPROACH CONTROL FREQUENCIES

FACILITY	FREQUENCIES	SERVICE AVAILABILITY
LAS VEGAS CLASS B	118.6 (NELLIS ARP CSN)	CONTINUOUS
	120.95 (NELLIS ARP SAT-SUN)	
	124.65 (NELLIS ARP SUN-MON)	
	126.65 (NELLIS ARP SUN-MON)	
NELLIS AFB	118.6 (NELLIS ARP CSN)	CONTINUOUS
	120.95 (NELLIS ARP SAT-SUN)	
	124.65 (NELLIS ARP SUN-MON)	
	126.65 (NELLIS ARP SUN-MON)	

SPECIAL USE AIRSPACE ON LAS VEGAS SECTIONAL CHART

Unless otherwise noted altitudes are:

"SFC" is surface level

"UNL" is altitudes above 75 mile including "

"MEAN" is mean sea level

"AGL" is altitudes above ground level

"Other times by NOTAM."

"Other times by NOTAM."

"Other times when not activated by the controlling agency."

"Other times when not in use."

"Other times when not in use by the controlling agency."

"Other times when not in use by the controlling agency."

"Other times when not in use by the controlling agency