

U.S. Department of Transportation  
Federal Aviation Administration  
Aeronautical Information Services  
<http://www.faa.gov/go/ais>

## **FAA/Aeronautical Information Services CIFP Readme**

**Volume: 2402**

Effective: 0901Z

**22 Feb 2024**

To: 0901Z

**21 Mar 2024**

Last Transmittal Letter: **19 Jan 2024**

### **Customer Agreement Form**

Please note: When downloading the CIFP, you have agreed to the Customer Agreement for Error Notification by clicking “I Agree” on the FAA Website.

As a recipient of the CIFP, you agree to the following:

- You must notify all your customers who receive or download the CIFP, or CIFP-derived data product, of the subject and nature of the reported error.
- You must notify the FAA contact listed below if you discover an error in the CIFP, or if one of your customers notifies you of an error.
- Upon notification and verification of any CIFP error that is discovered and reported by you or any of your customers, the FAA will in turn notify all CIFP customers of the error.

The FAA contact is:

FAA, Aeronautical Information Services

SSMC-4 Sta. #4445

1305 East West Highway

Silver Spring, MD 20910-3281

Telephone: 1-800-626-3677

[https://www.faa.gov/air\\_traffic/flight\\_info/aeronav/aero\\_data/](https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/)

By subscribing to [http://www.faa.gov/air\\_traffic/flight\\_info/aeronav/safety\\_alerts/](http://www.faa.gov/air_traffic/flight_info/aeronav/safety_alerts/) you will be notified by email of any errors discovered and reported to the FAA.

## ARINC 424 Standard

The CIFP adheres to ARINC 424-18 specifications, with exceptions noted forthwith.

### Record types

**The Coded Instrument Flight Procedures (CIFP)** currently provides the following record types:

- Airports and heliports (PA and HA)
- Runways (PG)
- VHF Nav aids (D)
- NDB Nav aids (DB)
- Terminal Nav aids (PN)
- Localizer and Glide Slope Records (PI)
- Path Point Records, Primary and Continuation (PP)
- MSA Records (PS and HS)
- Enroute Waypoints (EA)
- Terminal Waypoints (PC and HC)
- SIDs (PD)
- STARs (PE)
- Approaches, including Level of Service continuation records (PF and HF)
- Airways (ER)
- Class B, C, and D Airspace (UC)
- Special Use Airspace, Primary and Continuation (UR)
- Grid MORA (AS)

**Airports and Heliports:** The published ICAO Airport Identifier will be used (5.6). If there is no published ICAO Airport Identifier, then the published FAA Airport Identifier will be used. The IATA code field in the Airport Record will contain the FAA Airport Identifier. If the Airport Identifier is four characters in length, the field will be left blank.

The Longest Runway (5.54) field may not always represent the longest hard-surface runway at the airport.

**Runways:** Suffixes for water runways (W), soft-surface runways (S), glider runways (G), ultralight runways (U) and assault strips (numeric) will be included (5.46).

Non-numeric runway identifiers (5.46) are included and will not carry the prefixed 'RW' characters.

Runway gradient (5.212) and ellipsoid height (5.225) are included in the runway record when available.

If a magnetic variation is not available to help determine Runway Magnetic Bearings (5.58), one will be calculated using the WMM calculator.

**Waypoints and Fixes:** Domestic fixes include the following types: Reporting point, Waypoint, RNAV Waypoint, VFR Waypoint, Computer Navigation, Terminal Waypoint, ATC Coordination, GPS Waypoint, Military Reporting Point, Military Waypoint, NRS Waypoint, and Radar. Waypoints with all-numeric identifiers will not be included.

Fixes classified as “Offshore” in the NASR database may be assigned a Customer/Area Code (5.3) of ‘USA’ and an ICAO Code (5.14) of “K “ or “P “ (Character “K” or “P” followed by blank or NULL value).

Waypoint Type (5.42, col 27) designates fixes with an “R” for ground-based components, a “W” for satellite-based components, and a “C” for both. Fixes that can only be defined with RADAR will be designated with an “R.”

Waypoint Name Format Indicator (5.196) will not be populated.

PC records (4.1.4.1) may be used for named terminal waypoints if used at only one airport in the CIFP, and not used on an Enroute Airway. Otherwise, EA records will be used. In some cases, PC records also are used for unnamed terminal waypoints.

PC Waypoints will carry the Customer/Area Code (5.3) of the parent airport, regardless of its location. PC waypoints, however, will maintain their distinct ICAO Code (5.14), even if it differs from that of the parent airport.

**Nav aids:** A PN Record may be used for NDBs when only used at one airport in the CIFP, when not used on an Enroute Airway, and when assigned a five-letter name. Otherwise, DB records will be used.

DME only facilities are not assigned station declination values in the NASR NAV.txt subscriber file. A magnetic variation is computed using the WMM calculator to support ERAM requirements.

If a VOR frequency is unavailable, the VOR Frequency field (5.34) will contain ‘00000’ in columns 23-27. For all other Nav aids, an unavailable frequency will result in blank coding.

Nav aid Class 3 (5.35) will be coded as ‘H’ for high, ‘L’ for low, and ‘T’ for terminal altitude description. Where undetermined, the field will be coded with ‘U’. Nav aid Class 5 will carry an ‘N’ for VORTACs if the VOR coordinates and the TACAN coordinates are 0.1 NM or greater distance from each other.

DME elevation (5.40) is not available in NASR NAV.txt subscriber file when it differs from an associated VOR or TACAN facility. In these instances, the VOR elevation will be populated.

The Figure of Merit (5.149) is determined from the NAV AID Class. If the Nav aid Class is undetermined, the Figure of Merit will be coded as ‘3’

Weather Capability codes for Hazardous Inflight Weather Advisory Service (HIWAS) and Automatic Transcribed Weather Broadcast (TWEB), will be coded with an “A” (5.35).

**Airways:** U.S. Airways include Enroute Airways, Area Navigation Routes, Area Navigation Instrument Flight Rules Terminal Transition Routes, and ATS Routes. Non-US airways, including Canadian Airways, will no longer be included in the dataset.

Route Type (5.7) will employ “O” for conventional and “R” for RNAV routes. The point-to-point MEA value in the Minimum Altitude (5.30) field will be coded. If the airway is a conventional route, the conventional MEA will be coded. If the airway is an RNAV route, the GNSS MEA will be coded. If a GNSS MEA value is not provided, the conventional MEA will be used.

Airways and ATS Routes will contain a Level entry (5.19) if the route begins with V or T (Level = L) and J or Q (level =H). Otherwise, the Level will be blank.

ATS Routes will not contain directional restrictions (5.115).

**Approaches:** Standard instrument approach procedures include ILS and/or LOC (Category 1 only), VOR and NDB-related procedures including GPS overlays, GPS, RNAV (GPS), RNAV (RNP), as well as GPS and RNAV (GPS) helicopter approaches. ILS component records (PI records) will only be added for those procedures that are included in the CIPF.

For LDA approaches with both LDA and Glide Slope minima, the procedure will be coded to LDA minimums only.

Version 19 of the ARINC 424 specifications will be applied with regard to SID/STAR/Approach Identifier (5.9, 5-10, col 14-19), Route Type (5.7, col 20), and Route Qualifier 1 (5.7, col 119). For RNAV (RNP) approaches, Column 20 will be populated with an H, and column 119 will be populated with an F. In addition, the route identifier for the final and missed approach segments of these procedures will be identified with an H (5.10, col 14). RF legs will be coded as fly by except when followed by a Hx leg type.

Version 19 of the ARINC 424 specifications will be applied with regard to the level of the service continuation record (5.297)

Version 19 of the ARINC 424 specifications, Attachment 5, para 6.10.3.2 will be applied with regard to the altitude 1 field for circling procedures that are not straight-in aligned with a runway.

**Controlled Airspace:** Controlled Airspace Names (5.216) are those found in the legal description.

Airspace Center (5.214) uses the ICAO identifier for the primary airport for the airspace.

Unit Indicator (5.133) for all altitudes described as “GND” contain an A for AGL.

**Special Use Airspace:** Time Code (5.131) uses a “C” to indicate continuous and is blank to indicate part-time.

Special Use Airspace Altitudes (5.121) are only coded on the first record of each area. Upper altitudes are described as "to and including". The Unit Indicator (5.133) for all altitudes described as “GND” contains an A for AGL.

Positions within UR records that result in a gap (greater than *0.02NM*) between an arc end and its adjoining leg may have been recalculated. The revised coordinate positions more accurately reflect the arc radius published in the legal description but may differ from the published coordinates. The lower and upper limits (5.121) of a totally excluded volume from within an airspace will be coded as GND A0000A.

Continuation Records for UR records are included only for Controlling Agencies (5.140).

Special Air Traffic Rules Areas described under Part 93 of Title 14 of the CFR are included as UR Records if their spatial dimensions can be coded. These are classified as “U” in the Restricted Airspace Type (5.128). Please refer to Part 93 of the CFR for the specific air traffic rules governing these areas.

Restrictive Airspace Designation (5.129) listed as follows include published names in parentheses.

ANC SATR (Anchorage, Alaska, Terminal Area)

KTN SATR (Ketchikan International Airport Traffic Rule)

GCNPSFRA E and GCNPSFRA W (Grand Canyon Special Flight Rules) See below for details

LUKE SATR (Special Air Traffic Rules in vicinity of Luke AFB, AZ)

DC SFRA (Washington, DC Metropolitan Area Special Flight Rules Area) includes DC FRZ

NIAGFLSATR (Special Air Traffic Rules in vicinity of Niagara Falls, New York)

NY SFRA (New York Class B Airspace Hudson River and East River Exclusion SFRA)

VALPO SATR (Valparaiso, Florida Terminal Area)

VUO SFRA (Special Air Traffic Rules in vicinity of Portland Intl, OR)

National Security Areas are included as UR records with a “U” coded in the Restrictive Airspace Type field (5.128)

The GRAND CANYON SFRA is divided into East and West sections. The internal boundaries for Sectors and Flight Free Zones (FFZ) are included. All boundary names and their altitudes are included in the Restrictive Airspace Name Field (5.216). The Restrictive Airspace Designation (5.129) is "GCNPSFRA E" or "GCNPSFRA W". Please refer to the Part 93 Subpart U of the CFR for the specific air traffic rules governing the Grand Canyon SFRA.

UR airspace involving nautical/maritime limits are in the process of being standardized to the official NOAA source, while maintaining the coordinates given in the airspace legal description. This sometimes results in the given points not meeting the nautical boundary.

### **Coding information**

**Waypoint Descriptor:** Compulsory waypoints will not be indicated in Waypoint Descriptor 3 (5.17) for all routes. An “R” is coded in Waypoint Descriptor 3 (5.17) when a fix marks a course change in the final approach. The ‘S’ attribute in Waypoint Descriptor 3 (5.17) will not be coded for step down fixes between the FACF and the FAF. For RNAV (RNP) procedures, the ‘S’ attribute will not be coded for step down fixes between the FAF and the MAP.

**Final Approach Course Fix (FACF):** The FACF may be designated as the Initial Fix (IF). This may result in Step-down Fixes between the FACF and the FAF.

**Minimum Safe Altitude (MSA):** The MSA Center Fix (5.144) is normally coded on the FAF record. If the FAF record is an RF leg, then the MSA Center Fix is coded on the FAF record. If there is no FAF record, a center fix will not be coded.

**Vertical Angle:** Circling and Dive-and-Drive procedures are coded with “000” in the vertical angle field (5.70). Additionally, “000” will be coded for straight in aligned procedures as directed by Flight Inspection when obstacles are identified in the visual areas.

**Missed Approach:** Course-to-Altitude (CA) path terminator segments may be used as the first leg of the missed approach. If there is no mandatory altitude specified in the missed approach instructions, the CIFP will code the lowest of the DA, the MDA, or 400 feet above airport elevation.

Alternate missed approaches (Route Type Z) (5.7) are not included in the CIFP. Route type for the missed approach will reflect the route type of the final approach.

**Required Navigation Performance (RNP):** For standardization of CIFP RNP Value coding (para 5.211), NAVSPEC values found in FAAO 8260.58C, Table 1-2-1 will be populated using the following methods:

1. Day-forward procedures, HF and HM legs will not be coded with RNP Values in the CIFP.
2. For amendments and abbreviated amendments, RNP Values will match those published in FAA Form 8260-3 Terminal Routes section.
3. For P-NOTAMs that require coding changes, RNP Values will match FAA Form 8260-3 Terminal Routes section. If no RNP Values are documented, RNP Values will be coded to reflect current NAVSPEC without regard to RNP Values that may be on an accompanying FAA Form 8260-10.
4. For P-NOTAMs that do not require coding changes, coding will be updated on a time permitting basis and RNP Values will be coded using the standard in #3.
5. Day-back procedures already in the CIFP will be updated as workload permits. If one or more procedures at an airport are updated to current NAVSPEC, an effort will be made to update other procedures at the airport at the same time.

**Route Qualifier 2:** Route Qualifier 2 (5.7) of “H” will be shown for copter approaches using helipads.

**File Record Number (5.31)** A unique number is assigned for each record rather than consecutively for the entire dataset. Some file record numbers will have alphabetic characters or blank fields.

**Cycle Date (5.32)** Cycle dates will be updated to the most recent cycle on all new records in the CIFP, or on those records with modifications.

### **General information:**

**Header Records (6.2.1)** The Creation Date on Header Record 1 will not contain a leading ‘zero’ or <blank> if the date is only one digit. As a result, the Creation Date, Creation Time, and Data Supplier fields will be shifted one space to the left.

**Procedure types that are not yet included in the CIFP:** ILS CAT II, ILS CAT III, PRM, Converging ILS, GLS, and Visual procedures are not included in the CIFP.

**Not-In-CIFP Spreadsheet:** ILS (Category 1 only), LOC, SDF, LDA, VOR, NDB, GPS, RNAV (GPS), RNAV (RNP), GPS Overlays, GPS and RNAV (GPS) helicopter approaches, GLS, SIDs and STARs that do not appear in the CIFP will be listed in the Not-In-CIFP spreadsheet.

Only FAA-approved public use procedures are included in the CIFP. Approach types listed above that are developed outside the FAA, such as Navy or Air Force procedures, will not appear in this spreadsheet.

**Magnetic Variation:** Calculations are derived from the World Magnetic Model, 2020 epoch year. For more information on the WMM, and access to the 2020-2025 coefficients go to:

<https://www.ngdc.noaa.gov/geomag/WMM/DoDWMM.shtml>

To align CIFP dynamic magnetic variation calculations with NASR subscriber AWY.txt and ATS.txt files, if there is no magnetic variation assigned by official government source, the CIFP dynamic magnetic variation will be calculated based on the magnetic epoch of the first 56-day cycle following the first 56-day cycle whose data processing falls fully within the calendar year. For 2024, this occurs in CIFP 2403 (effective 21 March 2024).

Dynamic magnetic variation values for Waypoint Records and DME Only facilities will be calculated using the magnetic epoch in CIFP 2403 (effective 21 March 2024).

**Canadian data:** Refer to current Canadian charts and flight information publications for information within Canadian airspace.

### **Cyclic Redundancy Check (CRC), Data Replication Integrity**

The Coded Instrument Flight Procedures is wrapped with a 32-bit CRC, calculated as described in ARINC Report 665.

### **Comments**

Aeronautical Information Services welcomes any comments, suggestions and inquiries regarding specific coding practices that could improve the Coded Instrument Flight Procedures.

Please contact Aeronautical Information Services at:

FAA, Aeronautical Information Services  
SSMC-4 Sta. #4445  
1305 East West Highway  
Silver Spring, MD 20910-3281  
Telephone 1-800-638-8972  
Email [9-AMC-Aerochart@faa.gov](mailto:9-AMC-Aerochart@faa.gov)