

[Print](#)

Project Name: KACJ NEW CIRCLING RADII APPLIED

Project Reason: NEW CIRCLING AREA APPLIED. CIRCLING OBSTRUCTIONS: CAT A/B: 630 TANK (13-020801) 320655.03N/0841159.04W (1A) 630+300=930 ROUNDED TO 940, CAT C: 702 TOWER (13-000679) 320418.98N/0841309.69W (1A) 702+300=1002 ROUNDED TO 1020, CAT D: 911 TOWER (13-002145) 320325.50N/0841028.83W (4D) 911+300+50=1261 ROUNDED TO 1280. PRIMARY VIS CK: 1, 1, 1 1/2, 2 3/4. BACK UP VIS CK: 1, 1, 2, 3. RADII: 1.30, 1.82, 2.86, 3.74. UPDATE BACKUP ALTIMETER NOTE TO INCLUDE CIRCLING VISIBILITY INCREASES OF 1/2 SM FOR CAT C AND 1/4 SM FOR CAT D. ALTERNATE MINIMUMS NOT DEVELOPED. ALL CURRENT PROCEDURES ARE ALTERNATE MINIMUMS: NA. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-03-17 14:16:20.469721

Status: Draft

1/1741

!FDC X/XXXX ACJ IAP JIMMY CARTER RGNL, AMERICUS, GA. RNAV (GPS) RWY 23, AMDT 1B... CIRCLING CAT C MDA 1020/HAA 552, CAT D MDA 1280/HAA 812, VIS CAT D 2 3/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLUMBUS ALTIMETER SETTING AND INCREASE LPV DA TO 874, LNAV/VNAV DA TO 879 FEET AND ALL VISIBILITIES 5/8 SM, INCREASE ALL MDAS 120 FEET AND LNAV CATS C/D VISIBILITY 3/8 SM AND CIRCLING CAT C VISIBILITY 1/2 SM, CAT D 1/4 SM. THIS IS RNAV (GPS) RWY 23, AMDT 1C. 2103171416-PERM

Digitally signed by  
**DAVID TEFFETELLER**  
Apr 01, 2021

