

[Print](#)

Project Name: LCQ NEW CIR RADII

Project Reason: APPLY NEW CIRCLING CRITERIA IN ACCORDANCE WITH ORDER 8260.3, CHAPTER 2: CATEGORY RADII: CAT A: 1.30, CAT B: 1.81, CAT C: 2.85 AND CAT D: 3.72. CONTROLLING OBSTACLE CAT A 353 MSL TOWER (12-001249) 301117.00N/0823502.00W (5D), OBS 353 + ROC 300 + AC 50 = 703 (720). CONTROLLING OBSTACLE CAT B 358 MSL TANK (12-001429) 31119.00N/0823725.00W (4D), OBS 358 + ROC 300 + AC 50 = 708 (720). CONTROLLING OBSTACLE CAT C 470 MSL TOWER (12-003771) 301137.76N/0823804.80W (1C), OBS 470 + ROC 300 = 770 (780). CONTROLLING OBSTACLE CAT D 596 MSL TOWER (12-001366) 301307.00N/0823841.00W (5D), OBS 596+ ROC 300 + AC 50 = 946 (960). UPDATED NOTES, VISIBILITIES, AND ALTERNATE MINIMUMS WHERE REQUIRED.

Last Updated By: Andre Marsh

Last Updated At: 2021-04-19 16:33:28.634328

Status: Verified **1/7907**

!FDC X/XXXX LCQ IAP LAKE CITY GATEWAY, LAKE CITY, FL. RNAV (GPS) RWY 28, AMDT 1B... LPV VIS 1. LNAV/VNAV VIS 1. CIRCLING CAT C MDA 780/HAA 579, CAT D MDA 960/HAA 759, CAT D VIS 2 1/2. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: CIRCLING TO RWY 10 NA AT NIGHT. CHART NOTE: CIRCLING RWY 10 NA AT NIGHT. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C (0F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C OR ABOVE 54C. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NA. CHART NOTE: RWY 13 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: BARO-VNAV AND VDP NA WITH GAINESVILLE ALTIMETER SETTING. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING GAINESVILLE ALTIMETER SETTING. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GAINESVILLE ALTIMETER SETTING AND INCREASE ALL DA TO 624 FEET, LNAV/VNAV DA TO 640 AND ALL MDA 100 FEET; INCREASE LPV ALL CATS VISIBILITY 1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE, LNAV CAT C/D VISIBILITY 1/4 MILE AND CIRCLING CAT C VISIBILITY 1/8 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GAINESVILLE ALTIMETER SETTING: INCREASE LPV DA TO 624 FEET AND ALL VISIBILITY 1/4 SM; LNAV/VNAV DA TO 640 FEET AND ALL VISIBILITY 3/8 SM; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C AND D 1/4 SM AND CIRCLING VISIBILITY CAT C 1/2 SM AND CIRCLING CAT D 1/4 SM. ALTERNATE MINIMUMS STANDARD EXCEPT CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 28, AMDT 1C. 2104191633-PERM

Digitally signed by
JASON KRETSCHMER
Apr 29, 2021

QUALITY
30
CHECKED