

[Print](#)

Project Name: LOZ - RNAV GPS RWY 6 NEW CIRCLING AREA

Project Reason: CIRCLING CONTROLLING OBSTACLES: CAT A: 1479 TREE 370622.00N/0840451.00W (2C) (1479 MSL + 300 ROC = 1779 (1780 MDA), CAT B/C/D: 1680 TOWER 370650.00N/0840310.00W (4D) (1680 MSL + 300 ROC + 50 AC = 2030 (2040 MDA). RADII: 1.31, 1.85, 2.91, 3.80. UPDATED BACKUP ALTIMETER SETTING, EQUIPMENT AND BARO-VNAV NOTES. UPDATED ALTERNATE MINIMUMS. ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED.

Last Updated By: Steven Dougherty

Last Updated At: 2021-02-16 17:07:38.484922

Status: Verified **1/2546**



!FDC X/XXXX LOZ IAP LONDON/CORBIN/MAGEE, LONDON, KY. RNAV (GPS) RWY 6, ORIG-A... CIRCLING CAT B MDA 2040/HAA 828, VISIBILITY 1 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SOMERSET ALTIMETER SETTING: INCREASE LPV DA TO 1566 FEET AND VISIBILITY ALL CATS 1/4 SM; INCREASE LNAV/VNAV DA TO 1702 FEET AND VISIBILITY ALL CATS 1/2 SM; INCREASE ALL MDAS 100 FEET AND LNAV CAT C VISIBILITY 1/4 SM, CAT D VISIBILITY 1/2 SM, AND CIRCLING CAT C/D VISIBILITY 1/4 SM. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHANGE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 46C. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT B 900-2, CAT C 900-2 1/2, CAT D 900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 6, ORIG-B. 2102161707-PERM

*Digitally signed by*  
**JASON KRETSCHMER**  
Mar 30, 2021