

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
DORMR	THREE	DORMR3.DORMR	TWO	05/19/2022	
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 1L: CLIMB ON HEADING 006.73 TO 540, THEN ON HEADING 003.00 OR AS ASSIGNED BY ATC, FOR VECTORS TO SYKES, THENCE...

TAKEOFF RWY 1R: CLIMB ON HEADING 006.73 TO 540, THEN ON HEADING 003.00 OR AS ASSIGNED BY ATC, FOR VECTORS TO SYKES, THENCE...

TAKEOFF RWY 10: CLIMB ON HEADING 096.73 TO 540, THEN ON HEADING 093.00 OR AS ASSIGNED BY ATC, FOR VECTORS TO SYKES, THENCE...

TAKEOFF RWY 19L: CLIMB ON HEADING 186.73 TO 540, THEN ON HEADING 213.00 OR AS ASSIGNED BY ATC, FOR VECTORS TO SYKES, THENCE...

TAKEOFF RWY 19R: CLIMB ON HEADING 186.73 TO 540, THEN ON HEADING 203.00 OR AS ASSIGNED BY ATC, FOR VECTORS TO SYKES, THENCE...

TAKEOFF RWY 28: CLIMB ON HEADING 276.74 TO 540, THEN ON HEADING 273.00 OR AS ASSIGNED BY ATC, FOR VECTORS TO SYKES, THENCE...

...ON TRACK 269.13 TO DORMR, THEN ON ASSIGNED TRANSITION. MAINTAIN 6000, EXPECT FILED ALTITUDE WITHIN 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
CIGAR	DORMR3.CIGAR	DORMR	PSTOL	TRACK 269.03	47.80	16000	1300	
			CIGAR	TRACK 268.46	33.19	FL180	1300	
FROOT	DORMR3.FROOT	DORMR	PSTOL	TRACK 269.03	47.80	16000	1300	
			FROOT	TRACK 285.40	61.58	FL180	1300	

PROCEDURAL DATA NOTES:

NOTE: JETS ONLY.

PBN REQUIREMENTS NOTES:

RNAV 1 - GPS.

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED.

TAKEOFF MINIMUMS:

RWY 1L/R, 19R, 28: STANDARD.

RWY 10: STANDARD WITH MINIMUM CLIMB OF 243 FT PER NM TO 800.

RWY 19L: 200-1 1/2 OR STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 300.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
DORMR	THREE	DORMR3.DORMR	TWO	05/19/2022	

CONTROLLING OBSTACLES:

MSA:

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART: TOP ALTITUDE: 6000.

DME/DME ASSESSMENT: NOT CONDUCTED.

AIRPORT MV: TPA 5W/2010.

ENVIRONMENTAL REVIEW UNDER ORDER 1050.1 (LATEST EDITION). REQUIREMENTS WORKSHEET AND NOISE SCREENING HAVE BEEN ACCOMPLISHED.

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
KTPA	TAMPA	FL

COMMUNICATIONS:

CHART: ATIS, ATCT, CLNC DEL, GND CON, CPDLC.

FIXES AND/OR NAVAIDS:

REMARKS:

ABBREVIATED AMENDMENT.

RWY 10 & 19L TAKEOFF MINIMUMS DIRECTED BY AFS PRB DATED 05/02/2022.

WAIVER ON FILE PERMITTING THE DELETION OF A CROSSING ALTITUDE AT SYKES FOR AIRCRAFT RECEIVING VECTORS TO JOIN AN RNAV ROUTE.

FLIGHT INSPECTED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021, SUBJECT, GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

Digitally signed by

ALLAN WILL

Nov 29, 2022

OFFICE

DATE

DEVELOPED BY

Digitally signed by

MICHAEL R. GARRITY JR. **MICHAEL GARRITY**

Nov 01, 2022

OFFICE

AJV-A423

DATE

09/26/2022

APPROVED BY

MARLON ROBINSON

Digitally signed by

ALLAN WILL

Nov 29, 2022

OFFICE

AJV-A420

DATE

TITLE

MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒ **OTHER:** ZJX, ZMA, TPA APP CON, KTPA ATCT, AMGR



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
DORMR	THREE	DORMR3.DORMR	TWO	05/19/2022	

CHANGES - REASONS:

- 1. TAKEOFF MINIMUMS: CHANGED RWY 10 FROM "STANDARD" TO "STANDARD WITH MINIMUM CLIMB OF 243 FT PER NM TO 800" - AFS PRB REQUEST.
- 2. TAKEOFF MINIMUMS: CHANGED RWY 19L FROM "STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 300" TO "200-1 1/2 OR STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 300" - AFS PRB REQUEST.
- 3. ADDITIONAL FLIGHT DATA: CHANGED "MAG/VAR: KTPA 05W/2010" TO "AIRPORT MV: TPA 5W/2010" - MEMO 283 DATED 6/2/2022.
- 4. REMARKS: ADDED "RWY 10 & 19L TAKEOFF MINIMUMS DIRECTED BY AFS PRB DATED 05/02/2022" - EXPLANATORY INFORMATION FOR FUTURE DEVELOPMENT.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME						NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
DORMR						THREE	DORMR3.DORMR	TWO	05/19/2022	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS	
RWY01L (AER)	275747.86N/0823232.48W	N	-	-	-	-				
540 MSL	-	-	-	VA	001.73	-				
-	-	-	-	VM	358.00	-				
RW01R (AER)	275751.52N/0823144.37W	N	-	-	-	-				
540 MSL	-	-	-	VA	001.73	-				
-	-	-	-	VM	358.00	-				
RW10 (AER)*	275814.84N/0823204.35W*	N	-	-	-	-			*DISPL THLD (498 FT)	
540 MSL	-	-	-	VA	091.73	-			CG 243 FT PER NM TO 800	
-	-	-	-	VM	088.00	-				
RW19L (AER)	275913.66N/0823141.57W	N	-	-	-	-				
540 MSL	-	-	-	VA	181.73	-			CG 220 FT PER NM TO 300	
-	-	-	-	VM	208.00	-				
RW19R (AER)	275936.74N/0823228.78W	N	-	-	-	-				
540 MSL	-	-	-	VA	181.73	-				
-	-	-	-	VM	198.00	-				

QUALITY
8

QUALITY
8
CHECKED

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
DORMR		THREE		DORMR3.DORMR		TWO		05/19/2022	
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW28 (AER)	275812.89N/0823051.88W	N	-	-	-	-			
540 MSL	-	-	-	VA	271.74	-			
-	-	-	-	VM	268.00	-			
SYKES	273952.96N/0830259.22W	Y	-	IF	-	-			
DORMR	273838.50N/0831625.71W	Y	FB	TF	264.13	12.00			
DORMR	273838.50N/0831625.71W	Y	-	IF	-	-			DORMR3.CIGAR
PSTOL	273329.00N/0840955.00W	Y	FB	TF	264.03	47.80			
CIGAR	272936.61N/0844659.51W	Y	FB	TF	263.46	33.19			
DORMR	273838.50N/0831625.71W	Y	-	IF	-	-			DORMR3.FROOT
PSTOL	273329.00N/0840955.00W	Y	FB	TF	264.03	47.80			
FROOT	274421.02N/0851810.43W	Y	FB	TF	280.40	61.58			

