

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
XAVRR	TWO	XAVRR2.XAVRR	ONE	03/21/2024	
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 3: CLIMB ON HEADING 025.01 TO 983, THEN DIRECT HOPRR, THEN ON TRACK 025.35 TO CROSS XAVRR AT OR ABOVE 2100, THENCE ...

...ON (TRANSITION). MAINTAIN 2500, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
SLLAM	XAVRR2.SLLAM	XAVRR	SLLAM	TRACK 025.50	2.62	2600	2100	

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME/IRU OR GPS

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED FOR NON-GPS EQUIPPED AIRCRAFT

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 3: STANDARD WITH MINIMUM CLIMB OF 384 FT/NM TO 1100.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

RWY 3: 875 MSL TREE (39-060429) 390756.42N/0842435.99W

MSA:

MSA FROM KLUK, 3000.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

AIRPORT MV: LUK 4W/1990

CHART: TOP ALTITUDE: 2500

DME/DME ASSESSMENT: SAT (RNP 2.0).



AIRPORTS SERVED:

AIRPORT ID	CITY	STATE
KLUK	CINCINNATI MUNI/LUNKEN FLD	OH

COMMUNICATIONS:

CHART: ATIS, GND CON, TWR, CLNC DEL

FIXES AND/OR NAVAIDS:

REMARKS:

ABBREVIATED AMENDMENT

FLIGHT INSPECTED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION.

DEVELOPED BY

JOSEPH BLANCO
Jul 09, 2024

APPROVED BY

BEV BORDY
Jul 19, 2024

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A ALPA AOPA APA HAI NBAA OTHER:ZID, LUK DEP CON, AMGR

CHANGES - REASONS:

1. REMOVED ALL REFERENCES TO RWY 3R AND REPLACED IT WITH RWY 3 - RWYS 3L/21R ARE BEING DECOMMISSIONED, AND RWYS 3R/21L ARE BEING RENUMBERED AS RWY 3/21.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
XAVRR		TWO		XAVRR2.XAVRR		ONE		03/21/2024	
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW03 (AER)	390533.79N/0842510.18W	N	-	-	-	-			
983 MSL	-	-	-	VA	021.01	-	AT/ABOVE 983		
HOPRR	390827.52N/0842344.46W	Y	FO	DF	-	-			
XAVRR	390938.08N/0842309.04W	Y	FB	TF	021.35	1.26	AT/ABOVE 2100		
XAVRR	390938.08N/0842309.04W	Y	-	IF	-	-			XAVRR2.SLLAM
SLLAM	391204.28N/0842155.01W	Y	FB	TF	021.50	2.62			

