

[Print](#)

Project Name: WORCHESTER RGNL, MA KORH, ILS OR LOC RWY 29

Project Reason: UPDATED CIRCLING AREA ICON IAW 8260.3 Volume 1, Chapter 2, new circling criteria applied. CIRCLING MINIMUMS CAT A: REMAINS MDA 1560/HAA 551, CAT B: CHANGED TO MDA 1720/HAA 711, CAT C: CHANGED TO MDA 2000/HAA 991, VIS CAT C 3, CAT D: CHANGED TO MDA 2000/HAA 991. CIRCLING CONTROLLING OBSTACLES: CAT A: 1247 TREE (25-049497) 421709.35N/0715418.21W (1A), CAT B: 1406 TREE (25-030131) 421801.86N/0715347.40W (1A), CAT C/D: ANTENNA (25-030076) 721833.99N/0715411.29W (1A). RADII: 1.30, 1.84, 2.91, 3.80. UPDATED ALTERNATE MINIMUMS DUE TO NEW MDA/HAA. CIRCLING BASED OFF OF RNAV (GPS) RWY 29 PROCEDURE.

Last Updated By: Steven Dougherty

Digitally signed by

DAVID DANNER

Jan 21, 2020

Last Updated At: 2020-01-09 18:49:10.362384

Status: Verified

!FDC 0/5469 ORH IAP WORCESTER RGNL, WORCESTER, MA. ILS OR LOC RWY 29, AMDT 4C... CHART CIRCLING ICON. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BEDFORD ALTIMETER SETTING AND INCREASE ALL DA 189 FEET AND ALL MDA 200 FEET; INCREASE S-ILS ALL CATS VISIBILITY TO 1 1/4, INCREASE S-LOC CATS C/D VISIBILITY TO 1 3/4, AND CIRCLING CAT B TO 1 1/4, CAT C TO 2 3/4. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BEDFORD ALTIMETER SETTING AND INCREASE ALL DA 189 FEET AND ALL MDA 200 FEET; INCREASE S-ILS ALL CATS VISIBILITY TO 1 1/4 SM, INCREASE S-LOC CATS C/D VISIBILITY TO 1 3/4 SM, AND CIRCLING CAT B TO 1 1/4 SM. CIRCLING CAT B MDA 1720/HAA 711, CIRCLING CAT C MDA 2000/HAA 991, VIS CAT C 3, CIRCLING CAT D MDA 2000/HAA 991. ALTERNATE MINIMUMS: ILS: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED.; LOC: STANDARD - CAT C, D 1000-3, NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED. DELETE NOTE: DME REQUIRED. EQUIPMENT REQUIREMENTS NOTE: DME REQUIRED. THIS IS ILS OR LOC RWY 29, AMDT 4D. 2001091849-PERM

QUALITY
31
CHECKED