

[Print](#)

Project Name: IAD - NEW CIRCLING CRITERIA APPLIED

Project Reason: NEW CIRCLING CRITERIA APPLIED. CIRCLING OBSTRUCTIONS: CAT A/B/C: 640 CONTROL TOWER (51-002134) 385620.68N/0772655.19W (1A) 640+300=940 CAT D: 695 BUILDING (51-022893) 385736.00N/0772124.00W (4D) 695+300+AC50=1045 ROUNDED TO 1060. VISIBILITY CHECK COMPLETE, RESULT: 1, 1, 1 3/4, 2 1/2. ALTERNATE MINIMUMS UPDATED TO ADD CAT D: 800-2 1/2. CIRCLING RADIIS: 1.30, 1.82, 2.85, 3.73. AIRPORT ELEVATION UPDATED TO 313. HAAS UPDATED AS APPLICABLE TO EACH PROCEDURE. REMOVE F DESIGNATIONS FROM BARO-VNAV NOTE AS APPLICABLE. REMOVE DME/DME NOTE, ADD PBN REQUIREMENTS NOTE.

Last Updated By: Ralph Miller

Last Updated At: 2021-06-01 13:55:00.719253

Status: Active

IFDC 1/4961 IAD IAP WASHINGTON DULLES INTL, WASHINGTON, DC. ILS OR LOC RWY 1R, AMDT 24B... CIRCLING CAT A/B/C HAA 627, CIRCLING CAT D MDA 1060/HAA 747. VISIBILITY CIRCLING CAT D 2 1/2. CHART APT ELEV 313, DELETE APT ELEV 312. ALTERNATE MINIMUMS: ILS STANDARD, LOC STANDARD EXCEPT CAT D 800-2 1/2. THIS IS ILS OR LOC RWY 1R, AMDT 24C, THIS IS ILS RWY 1R (CAT II AND CAT III), AMDT 24C. 2106011345-PERM

Digitally signed by

JOHN BORDY

Jun 01, 2021

