

[Print](#)

Project Name: DNS NEW CIR RADII

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED: CATEGORY RADII: CAT A: 1.31, CAT B: 1.85 AND CAT C: 2.91. CONTROLLING OBSTACLE CAT A 1520 MSL TREE 415741.70N/0952143.21W (2C), OBS 1520 + ROC 300 + XP 20/ (XP 40 - RNAV RWY 12) = 1820 (1840/(1860)). CONTROLLING OBSTACLE CAT B 1577 MSL TREE 415708.37N/0952150.18W (2A), OBS 1577 + ROC 300 = 1877 (1880). CONTROLLING OBSTACLE CAT C 1750 MSL TOWER (19-000064) 420200.00N/0952331.00W (4D), OBS 1750 + ROC 300 + AC 50 = 2100. OBSTACLE XP'ed TO MAINTAIN CURRENT CMDA. UPDATED NOTES, VISIBILITIES AND ALTERNATE MINIMUMS WHERE REQUIRED.

Last Updated By: Andre Marsh

Last Updated At: 2021-03-24 13:54:33.303005

Status: Verified **1/5754**

!FDC X/XXXX DNS IAP DENISON MUNI, DENISON, IA. RNAV (GPS) RWY 12, AMDT 1B... CIRCLING CAT C MDA 2100/HAA 826, CAT C VIS 2 1/2. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH-GPS. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 900-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 12, AMDT 1C. 2103241354-PERM

*Digitally signed by*  
**JASON KRETSCHMER**  
Apr 06, 2021

