

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

| <u>DP NAME</u>           | <u>NUMBER</u>            | <u>DP COMPUTER CODE</u>             | <u>SUPERSEDED NUMBER</u> | <u>DATED</u>             | <u>ACTUAL EFFECTIVE DATE</u>        |
|--------------------------|--------------------------|-------------------------------------|--------------------------|--------------------------|-------------------------------------|
| YODUH                    | TWO                      | YODUH2.YODUH                        | ONE                      | 01/25/2024               |                                     |
| <u>TYPE:</u>             | <u>OBSTACLE</u>          | <u>COPTER</u>                       | <u>SID</u>               | <u>SPECIAL</u>           | <u>RNAV</u>                         |
| <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |

**DP ROUTE DESCRIPTION:**

SAN ANTONIO INTL (SAT):

TAKEOFF RWY 4: CLIMB ON HEADING 036.78 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 13L: CLIMB ON HEADING 127.63 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 13R: CLIMB ON HEADING 127.60 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 22: CLIMB ON HEADING 216.79 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 31L: CLIMB ON HEADING 307.61 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 31R: CLIMB ON HEADING 307.64 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...

...ON TRACK 002.38 TO YODUH, THEN ON TRANSITION. MAINTAIN 5000. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

BOERNE STAGE FLD (5C1):

TAKEOFF RWY 17: CLIMB ON HEADING 169.01 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 35: CLIMB ON HEADING 349.01 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...

CASTROVILLE MUNI (CVB):

TAKEOFF RWY 16: CLIMB ON HEADING 156.98 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 34: CLIMB ON HEADING 336.98 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...

KELLY FLD (KSKF):

TAKEOFF RWY 16: CLIMB ON HEADING 158.15 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 34: CLIMB ON HEADING 338.15 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...

NEW BRAUNFELS NTL (BAZ):

TAKEOFF RWY 13: CLIMB ON HEADING 127.73 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 17: CLIMB ON HEADING 172.71 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 31: CLIMB ON HEADING 307.74 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 35: CLIMB ON HEADING 352.71 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...

PLEASANTON MUNI (PEZ):

TAKEOFF RWY 16: CLIMB ON HEADING 157.10 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 34: CLIMB ON HEADING 337.10 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...

RANDOLPH AFB (RND):

TAKEOFF RWY 15L: CLIMB ON HEADING 145.03 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 15R: CLIMB ON HEADING 145.03 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 33L: CLIMB ON HEADING 325.03 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 33R: CLIMB ON HEADING 325.04 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...

STINSON MUNI (SSF):

TAKEOFF RWY 10: CLIMB ON HEADING 099.53 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 14: CLIMB ON HEADING 142.36 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 28: CLIMB ON HEADING 279.53 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...  
TAKEOFF RWY 32: CLIMB ON HEADING 322.36 OR AS ASSIGNED BY ATC, FOR VECTORS TO SITHH, THENCE...



...ON TRACK 002.38 TO YODUH, THEN ON TRANSITION. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

| TRANSITION NAME | TRANSITION COMPUTER CODE | FROM FIX/NAVAID | TO FIX/NAVAID | COURSE       | DISTANCE | MEA   | MOCA | CROSSING ALTITUDE/FIXES |
|-----------------|--------------------------|-----------------|---------------|--------------|----------|-------|------|-------------------------|
| KLNGR           | YODUH2.KLNGR             | YODUH           | KLNGR         | TRACK 010.80 | 71.25    | 10000 | 3000 |                         |
| PRTZY           | YODUH2.PRTZY             | YODUH           | GJACK         | TRACK 328.70 | 83.00    | 10000 | 3400 |                         |
|                 |                          | GJACK           | PRTZY         | TRACK 328.32 | 79.79    | 10000 | 3900 |                         |

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME IRU OR GPS.

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED FOR NON-GPS EQUIPPED AIRCRAFT.  
RADAR REQUIRED

PROCEDURAL DATA NOTES:

NOTE: AIRCRAFT DESTINED FOR AIRPORTS NORTH/NORTHEAST OF DFW TERMINAL AREA MUST FILE THE KLNGR TRANSITION.

TAKEOFF MINIMUMS:

SAN ANTONIO INTL (SAT)  
RWY 4, 13L, 13R, 22, 31L, 31R: STANDARD

BOERNE STAGE FLD (5C1)  
RWY 17: STANDARD WITH MINIMUM CLIMB OF 210 FT/NM TO 2200.  
RWY 35: STANDARD WITH MINIMUM CLIMB OF 250 FT/NM TO 3800.

CASTROVILLE MUNI (CVB)  
RWY 16, 34: STANDARD

KELLY FLD (SKF)  
RWY 16, 34: STANDARD

NEW BRAUNFELS NTL (BAZ)  
RWY 13, 17, 31, 35: STANDARD

PLEASANTON MUNI (PEZ)  
RWY 16, 34: STANDARD

RANDOLPH AFB (RND)  
RWY 15L, 15R, 33L, 33R: STANDARD

STINSON MUNI (SSF)  
RWY 10: STANDARD WITH MINIMUM CLIMB OF 230 FT/NM TO 1900  
RWY 14: STANDARD WITH MINIMUM CLIMB OF 220 FT/NM TO 1900  
RWY 28: 300-1 5/8 OR STANDARD WITH MINIMUM CLIMB OF 230 FT/NM TO 900, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1800 FEET PRIOR TO DER.  
RWY 32: STANDARD WITH MINIMUM CLIMB OF 230 FT/NM TO 1700

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).



| <u>DP NAME</u> | <u>NUMBER</u> | <u>DP COMPUTER CODE</u> | <u>SUPERSEDED NUMBER</u> | <u>DATED</u> | <u>ACTUAL EFFECTIVE DATE</u> |
|----------------|---------------|-------------------------|--------------------------|--------------|------------------------------|
| YODUH          | TWO           | YODUH2.YODUH            | ONE                      | 01/25/2024   |                              |

**CONTROLLING OBSTACLES:**  
BOERNE STAGE FIELD (5C1):  
RWY 17: 1942 AAO 294015.00N/0984345.00W (CLIMB GRADIENT, CLIMB-TO ALTITUDE)  
RWY 35: 3048 MSL TOWER (48-005697) 295027.00N/0984933.00W (CLIMB GRADIENT, CLIMB-TO ALTITUDE).

STINSON MUNI (SSF):  
RWY 10, 14: 1546 MSL TOWER (48-004668) 291938.75N/0982117.63W (CLIMB GRADIENT, CLIMB GRADIENT TERMINATION ALTITUDE).  
RWY 28: 802 MSL TANK (48-169742) 292048.87N/0983016.57W (CEILING), (CLIMB GRADIENT), (CLIMB GRADIENT TERMINATION ALTITUDE), (VISIBILITY).  
RWY 32: 1379 MSL TOWER (48-001577) 292509.00N/0982901.00W (CLIMB GRADIENT, CLIMB-TO ALTITUDE).

**MSA:**  
SAT: MSA FROM SAT, 4100  
5C1: MSA FROM 5C1, 4100  
CVB: MSA FROM CVB, 4100  
SKF: MSA FROM SKF, 4100  
BAZ: MSA FROM BAZ, 3100  
PEZ: MSA FROM PEZ, 3100  
RND: MSA FROM RND, 3200  
SSF: MSA FROM SSF, 4100

**LOST COMMUNICATIONS PROCEDURES:**

**ADDITIONAL FLIGHT DATA:**  
CHART: TOP ALTITUDE: SAT: 5000; 5C1, CVB, SKF, BAZ, PEZ, RND, SSF: ASSIGNED BY ATC.  
AIRPORT MV: SAT (P) 4E/2020, 5C1 5E/2010, CVB 4E/2020, SKF 4E/2020, BAZ 8E/1975, PEZ 6E/2000, RND 5E/2010, SSF 03E/2025.  
CHART: MINIMUM CROSSING ALTITUDE AT SITHH-5000.  
DME/DME ASSESSMENT: SAT (RNP 2.0).

**AIRPORTS SERVED:**

| <u>AIRPORT ID</u> | <u>CITY</u>    | <u>STATE</u> |
|-------------------|----------------|--------------|
| SAT               | SAN ANTONIO    | TX           |
| 5C1               | SAN ANTONIO    | TX           |
| CVB               | CASTROVILLE    | TX           |
| SKF               | SAN ANTONIO    | TX           |
| BAZ               | NEW BRAUNFELS  | TX           |
| PEZ               | PLEASANTON     | TX           |
| RND               | UNIVERSAL CITY | TX           |
| SSF               | SAN ANTONIO    | TX           |

**COMMUNICATIONS:**  
SAN ANTONIO INTL (SAT): CHART: ATIS, GND CON, CLNC DEL, ATCT  
BOERNE STAGE FIELD (5C1): CHART: ATIS, CLNC DEL  
CASTROVILLE MUNI (CVB): CHART: ATIS, CLNC DEL  
KELLY FLD (SKF): CHART: ATIS, GND CON, ATCT  
NEW BRAUNFELS NTL (BAZ): CHART: ATIS, ATCT, GND CON, CLNC DEL



PLEASANTON MUNI (PEZ): CHART: CLNC DEL  
RANDOLPH AFB (RND): CHART: ATIS, ATCT, GND CON, CLNC DEL  
STINSON MUNI (SSF): CHART: ATIS, GND CON, CLNC DEL, ATCT

FIXES AND/OR NAVAIDS:

REMARKS:  
ENVIRONMENTAL REVIEW UNDER ORDER 1050.1 (LATEST EDITION) AND THE NOISE SCREENING HAVE BEEN ACCOMPLISHED.  
VEGETATION HEIGHT: 75FT - BASED ON SAT AND FPT.  
MEA - 10000 BASED ON DME/DME COVERAGE FROM ESV'S AND ATC REQUEST.

FLIGHT INSPECTED BY

SIGNATURE

Digitally signed by

ALLAN WILL

Mar 20, 2025

OFFICE

DATE

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMORANDUM 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

DEVELOPED BY

SIGNATURE

Digitally signed by

RICHARD E CAMPBELL

Feb 18, 2025

OFFICE

DATE

RICHARD CAMPBELL

AJV - A423

01/29/2025

APPROVED BY

SIGNATURE

Digitally signed by

ALLAN WILL

Mar 20, 2025

OFFICE

DATE

TITLE

ALLAN WILL

AJV - A423

MANAGER

REQUIRED EFFECTIVE DATE  
ROUTINE

COORDINATED WITH:

A4A ☒ ALPA ☒ AOPA ☒ APA ☒ HAI ☐ NBAA ☒ OTHER:ZHU, SAT APP CON, SAT ATCT, AMGR, STATE AVIATION DIRECTOR

- CHANGES - REASONS:
1. DP DEPARTURE ROUTE DESCRIPTION: ADDED EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE - IAW 8260.46J, FIGURE E-1.
  2. SSF RUNWAY CHANGED FROM 9/27 TO 10/28 - SSF MAG VAR UPDATED TO 3.0E
  3. SSF RUNWAY HEADINGS CHANGED - RWY 10: FROM 094.53 TO 099.53, RWY 14: FROM 137.36 TO 142.36, RWY 28: FROM 274.53 TO 279.53, RWY 32: FROM 317.36 TO 322.36 - MAG VAR UPDATE.
  4. PBN REQUIREMENTS: CHANGED FROM RNAV 1 - GPS TO RNAV 1 - DME/DME/IRU OR GPS - DME SCREENS AND APPROVED ESVS PROVIDE DME/DEME/IRU SOLUTIONS.
  5. EQUIPMENT REQUIREMENT NOTES: CHANGED FROM RADAR REQUIRED TO RADAR REQUIRED FOR NON-GPS EQUIPPED AIRCRAFT AND RADAR REQUIRED - DME SCREENS AND APPROVED ESVS PROVIDE DME/DEME/IRU SOLUTIONS.
  6. ADDITIONAL FLIGHT DATA: MAG VAR CHANGED FOR SSF FROM 8E/1980 TO 03E/2025.
  7. ADDITIONAL FLIGHT DATA: CHANGED DME ASSESSMENT FROM UNSAT TO SAT (RNP 1.0).
  8. ALL LOCATION IDENTIFIERS REMOVED K'S FROM BEGINNING OF IDENTIFIER.
  9. COMMUNICATIONS: ADDED BOERNE STAGE FIELD (5C1) AND CASTROVILLE MUNI (CVB).
  10. REMARKS: ADDED VEGETATION HEIGHT.



**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)**

| <u>DP NAME</u>    |                        | <u>NUMBER</u> |              | <u>DP COMPUTER CODE</u> |           | <u>SUPERSEDED NUMBER</u> |                 | <u>DATED</u> | <u>ACTUAL EFFECTIVE DATE</u> |
|-------------------|------------------------|---------------|--------------|-------------------------|-----------|--------------------------|-----------------|--------------|------------------------------|
| YODUH             |                        | TWO           |              | YODUH2.YODUH            |           | ONE                      |                 | 01/25/2024   |                              |
| <u>FIX/NAVAID</u> | <u>LAT/LONG</u>        | <u>C</u>      | <u>FO/FB</u> | <u>LEG TYPE</u>         | <u>TC</u> | <u>DIST (NM)</u>         | <u>ALTITUDE</u> | <u>SPEED</u> | <u>REMARKS</u>               |
| SITHH             | 295126.66N/0982512.91W | Y             | -            | IF                      | -         | -                        | AT/ABOVE 5000   |              |                              |
| YODUH             | 300423.70N/0982333.05W | Y             | FB           | TF                      | 006.38    | 13.00                    |                 |              |                              |
| YODUH             | 300423.70N/0982333.05W | Y             | -            | IF                      | -         | -                        |                 |              |                              |
| KLNGR             | 311324.79N/0980219.85W | Y             | FB           | TF                      | 014.80    | 71.25                    |                 |              | YODUH2.KLNGR                 |
| YODUH             | 300423.70N/0982333.05W | Y             | -            | IF                      | -         | -                        |                 |              |                              |
| GJACK             | 311811.56N/0990759.23W | Y             | FB           | TF                      | 332.70    | 83.00                    |                 |              |                              |
| PRTZY             | 322852.23N/0995148.18W | Y             | FB           | TF                      | 332.32    | 79.79                    |                 |              | YODUH2.PRTZY                 |

QUALITY  
23  
CHECKED