

[Print](#)

Project Name: ETB - NEW CIRCLING AREA - P NOTAM

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED CIRCLING CONTROLLING OBSTACLES: CAT A: 1109 TREE 432438.00N/0880538.00W (2C) 1109+300 ROC=1409 ROUNDED TO 1420. CAT B: 1156 TOWER (55-000184) 432441.00N/0881021.00W (1D) 1156+300 ROC+50AC=1506 ROUNDED TO 1520. CAT C/D: 1258 TOWER (55-001000) (1A) 1258+300 ROC=1558 ROUNDED TO 1560. CIRCLING VISIBILITY PRIMARY: 1, 1, 2, 2 1/4. CIRCLING VISIBILITY BACKUP: 1, 1, 2 1/4, 2 1/2. RADII: 1.30, 1.84, 2.89, 3.77. CHANGES: RNAV (GPS) RWY 31: UPDATED ALTERNATE MINIMUMS. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS.

Last Updated By: Ralph Miller

Last Updated At: 2021-08-04 12:43:33.244056

Status: Verified **1/5342**

!FDC X/XXXX ETB IAP WEST BEND MUNI, WEST BEND, WI. RNAV (GPS) RWY 31, ORIG-A... CIRCLING CAT B MDA 1520/HAA 633, CAT C/D MDA 1560/HAA 673. CIRCLING CAT C VISIBILITY 2, CAT D VISIBILITY 2 1/4. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: DME/DME RNP-0.3 NA. THIS IS RNAV (GPS) RWY 31, ORIG-B. 2108041243-PERM

Digitally signed by
JASON KRETSCHMER
Aug 11, 2021

QUALITY
45
CHECKED