

[Print](#)

Project Name: KSDL NEW CIRCLING RADII APPLIED

Project Reason: APPLY NEW CIRCLING CRITERIA IN ACCORDANCE WITH ORDER 8260.3, CHAPTER 2: CATEGORY RADII: CAT A: 1.31, CAT B: 1.86, CAT C: 2.93 AND CAT D: 3.89. CONTROLLING OBSTACLE CAT A 1732 MSL TRANSMISSION LINE (04-022270) 333856.39N/1115319.69W (1C), OBS 1732 + ROC 300 = 2032 (2040). CONTROLLING OBSTACLE CAT B 1788 MSL TRANSMISSION LINE (04-042867) 333935.27N/1115354.74W (1B), OBS 1788 + ROC 300 = 2088 (2100), CONTROLLING OBSTACLE CAT C 2160 TREE 333849.45N/1115050.59W (2C), OBS 2160 + ROC 300 = 2460, CONTROLLING OBS CAT D 3000 AAO 333922.51N/1114957.06W (2C), OBS 3000 + ROC 300 = 3300. UPDATE ALTERNATE MINIMUMS NOTES AS REQUIRED. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-06-09 17:39:13.15431

1/1494

Status: Draft

!FDC X/XXXX SDL IAP SCOTTSDALE, SCOTTSDALE, AZ. VOR/DME-A, AMDT 3... CAT C MDA 2460/HAA 950, CAT D MDA 3300/HAA 1790, VIS CAT C 2 3/4, VIS CAT D 3. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PHOENIX SKY HARBOR INTL ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND INCREASE VISIBILITY CAT C 1/4 SM. ALTERNATE MINIMUMS: CAT A/B 900-2, CAT C 1000-2 3/4, CAT D 1800-3, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS VOR/DME-A, AMDT 3A. 2106091739-PERM

Digitally signed by  
**DAVID TEFFETELLER**  
Jun 11, 2021

