

U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
O'HARE	TWO	ORD2.ORD	ONE	4 FEB 16	

TYPE: SID

DP ROUTE DESCRIPTION:

ALL AIRCRAFT: EXPECT RADAR VECTORS TO FIRST ENROUTE NAVAID/FIX. EXPECT CLEARANCE TO REQUESTED ALTITUDE/FLIGHT LEVEL TEN MINUTES AFTER DEPARTURE.
ALL DME EQUIPPED AIRCRAFT: CROSS 5 DME ARC OF ORD VOR/DME AT OR ABOVE 3000 MSL, CROSS 8 DME ARC OF ORD VOR/DME AT OR ABOVE 4000, MAINTAIN 5000 OR ASSIGNED ALTITUDE. IF UNABLE TO COMPLY ADVISE ATC AS SOON AS POSSIBLE PRIOR TO DEPARTURE.
NON-DME PROCEDURES: AIRCRAFT INITIALLY ASSIGNED HEADING 120 CW 220, CROSS DPA VOR/DME R-093 AT OR ABOVE 4000, MAINTAIN 5000 OR ASSIGNED ALTITUDE. IF UNABLE TO COMPLY ADVISE ATC AS SOON AS POSSIBLE PRIOR TO DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

NOTE: RADAR REQUIRED.

NOTE: ALL TURBO-JET DEPARTURES IN ALL DIRECTIONS, MAINTAIN 250 KNOTS UNTIL ADVISED BY ATC.

SPECIAL INSTRUCTIONS: FOR APPROPRIATE DEPARTURE CONTROL FREQUENCY, SEE GRAPHIC. USE FREQUENCY DEPICTED WITHIN THE SECTOR WHERE FIRST NAVAID/FIX FOR YOUR ROUTE IS LOCATED (SECTORS INDICATED BY DASHED LINES; FREQUENCIES IN DASHED BOX WITHIN).

TAKEOFF MINIMUMS:

RWY 4L, 4R, 9L, 9R, 10C, 10L, 10R, 15, 22L, 22R, STANDARD.

RWY 27L, STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 900, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1400 FT PRIOR TO DER.

RWY 27R, STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 1800.

RWY 28C, STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 1700.

RWY 28L, STANDARD WITH MINIMUM CLIMB OF 235 FT PER NM TO 1000, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1900 FT PRIOR TO DER.

RWY 28R, STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 1700.

RWY 33, STANDARD WITH MINIMUM CLIMB OF 240 FT PER NM TO 1700.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 4L, TOWER ON BUILDING 3301 FT FROM DER, 1207 FT RIGHT OF CENTERLINE, 109 FT AGL/750 FT MSL.

NOTE: RWY 4R, TAXIING AIRCRAFT 152 FT FROM DER, 328 FT LEFT OF CENTERLINE, UP TO 80 FT AGL/735 FT MSL. TREES 809 FT FROM DER, 611 FT RIGHT OF CENTERLINE, UP TO 36 FT AGL/675 FT MSL.

NOTE: RWY 9L, BUILDING 2771 FT FROM DER, 1233 FT RIGHT OF CENTERLINE, 94 FT AGL/745 FT MSL.

NOTE: RWY 9R, POLE 876 FT FROM DER, 688 FT RIGHT OF CENTERLINE, 29 FT AGL/673 FT MSL.

NOTE: RWY 10C, GLIDESLOPE ANTENNA 1170 FT FROM DER, 777 FT LEFT OF CENTERLINE, 41 FT AGL/694 FT MSL.

NOTE: RWY 10L, TAXIING AIRCRAFT 32 FT FROM DER, 440 FT LEFT OF CENTERLINE, UP TO 80 FT AGL/735 FT MSL. SIGN AND TOWER ON BUILDING BEGINNING 2517 FT FROM DER, 731 FT RIGHT OF CENTERLINE, UP TO 88 FT AGL/732 FT MSL. TOWER 3957 FT FROM DER, 1289 FT RIGHT OF CENTERLINE, 127 FT AGL/771 FT MSL.



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
O'HARE	TWO	ORD2.ORD	ONE	4 FEB 16	

NOTE: RWY 10R, FENCES BEGINNING 10 FT FROM DER, 44 FT RIGHT OF CENTERLINE, UP TO 12 FT AGL/665 FT MSL. BUSH, FENCES, AND POLES BEGINNING 34 FT FROM DER, 195 FT LEFT OF CENTERLINE, UP TO 26 FT AGL/686 FT MSL. TREES BEGINNING 2202 FT FROM DER, 587 FT RIGHT OF CENTERLINE, UP TO 71 FT AGL/724 FT MSL. TOWER 4381 FT FROM DER, 1537 FT RIGHT OF CENTERLINE, 138 FT AGL/783 FT MSL.

NOTE: RWY 15, TAXIING AIRCRAFT 1105 FT FROM DER, 766 FT RIGHT OF CENTERLINE, UP TO 80 FT AGL/736 FT MSL.

NOTE: RWY 22R, TAXIING AIRCRAFT 34 FT FROM DER, 429 FT LEFT OF CENTERLINE, UP TO 80 FT AGL/736 FT MSL.

NOTE: RWY 27L, TAXIING AIRCRAFT 70 FT FROM DER, 407 FT LEFT OF CENTERLINE, UP TO 80 FT AGL/740 FT MSL. POLE 5553 FT FROM DER, 1833 FT LEFT OF CENTERLINE, 143 FT AGL/805 FT MSL.

NOTE: RWY 27R, OBSTRUCTION LIGHT ON TANK 1509 FT FROM DER, 887 FT LEFT OF CENTERLINE, 56 FT AGL/726 FT MSL. ELEVATOR 2778 FT FROM DER, 1021 FT LEFT OF CENTERLINE, 111 FT AGL/776 FT MSL.

NOTE: RWY 28C, TREES BEGINNING 2373 FT FROM DER, 696 FT LEFT OF CENTERLINE, UP TO 89 FT AGL/768 FT MSL. TREES 2559 FT FROM DER, 256 FT RIGHT OF CENTERLINE, UP TO 58 FT AGL/737 FT MSL.

NOTE: RWY 28L, TERRAIN AND BUSH BEGINNING 5 FT FROM DER, 352 FT RIGHT OF CENTERLINE, UP TO 4 FT AGL/692 FT MSL. POLES BEGINNING 244 FT FROM DER, 471 FT RIGHT OF CENTERLINE, UP TO 38 FT AGL/707 FT MSL. RAILROAD BEGINNING 590 FT FROM DER, 639 FT LEFT OF CENTERLINE, UP TO 23 FT AGL/700 FT MSL. POLES AND TREES BEGINNING 1500 FT FROM DER, 721 FT LEFT OF CENTERLINE, UP TO 79 FT AGL/758 FT MSL.

NOTE: RWY 33, POLE 1993 FT FROM DER, 790 FT LEFT OF CENTERLINE, 45 FT AGL/716 FT MSL.

CONTROLLING OBSTACLES:

RWY 27L: 812 FT MSL POLE 415844.00N/0875620.00W.

RWY 27R: 1468 FT MSL TOWER 420042.49N/0880206.93W.

RWY 28C: 1413 FT MSL TOWER 415926.00N/0880139.00W.

RWY 28L: 852 FT MSL TANK 415732.96N/0875658.25W.

RWY 28R: 1413 FT MSL TOWER 415926.00N/0880139.00W.

RWY 33: 1413 FT MSL TOWER 415926.00N/0880139.00W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART: DASHED LINE DEPICTING CHICAGO DEP CON EAST/NORTH SECTOR FROM ORD VOR/DME 340 DEGREES CLOCKWISE TO 139 DEGREES.

CHART: DASHED LINE DEPICTING CHICAGO DEP CON SOUTH SECTOR FROM ORD VOR/DME 140 DEGREES CLOCKWISE TO 219 DEGREES.

CHART: DASHED LINE DEPICTING CHICAGO DEP CON WEST SECTOR FROM ORD VOR/DME 220 DEGREES CLOCKWISE TO 339 DEGREES.

CHART IN A BOX: CHICAGO DEP CON EAST/NORTH FREQUENCY IN EAST/NORTH SECTOR.

CHART IN A BOX: CHICAGO DEP CON SOUTH FREQUENCY IN SOUTH SECTOR.

CHART IN A BOX: CHICAGO DEP CON WEST FREQUENCY IN WEST SECTOR.

AIRPORTS SERVED:

CHICAGO O'HARE INTL

CHICAGO, IL



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer	Superseded Number	Dated	Effective Date
O'HARE	TWO	Code ORD2.ORD	ONE	4 FEB 16	

COMMUNICATIONS:

CLNC DEL.

FIXES AND/OR NAVAIDS:

NAVAIDS: BAE VORTAC, EON VORTAC, RBS VOR/DME, IOW VORTAC, PLL VOR/DME, DPA VOR/DME, ORD VOR/DME, ELX VOR/DME, GIJ VORTAC.
FIXES: PETTY, SIMMN, ACITO, BACEN, CMSKY, DENNT, EARND, MOBLE, DUFEE, EBAKE, MYKIE, NOONY, OLINN, PEKUE, PMPKN, RAYNR.



U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
O'HARE	TWO	ORD2.ORD	ONE	4 FEB 16	

REMARKS:

1. AIRBUS 380 (80 FT AGL) USED AS WORST CASE FOR TAXIING AIRCRAFT.
2. RWY 27L CLIMB GRADIENT ROUNDED UP TO 220 FT PER NM FOR PUBLICATION (COMPUTED VALUE IS 213 FT PER NM).
3. RWY 27R CLIMB GRADIENT ROUNDED UP TO 220 FT PER NM FOR PUBLICATION (COMPUTED VALUE IS 216 FT PER NM).
4. RWY 28C CLIMB GRADIENT ROUNDED UP TO 220 FT PER NM FOR PUBLICATION (COMPUTED VALUE IS 217 FT PER NM).
5. RWY 28L CLIMB GRADIENT ROUNDED UP TO 235 FT PER NM FOR PUBLICATION (COMPUTED VALUE IS 234 FT PER NM).
6. RWY 28R CLIMB GRADIENT ROUNDED UP TO 220 FT PER NM FOR PUBLICATION (COMPUTED VALUE IS 219 FT PER NM).
7. RWY 33 CLIMB GRADIENT ROUNDED UP TO 240 FT PER NM FOR PUBLICATION (COMPUTED VALUE IS 237 FT PER NM).
8. ATC REQUESTS THAT TOP ALTITUDE NOT BE CHARTED. THEY DO NOT USE "CLIMB VIA" PHRASEOLOGY ON THIS SID (NO CODED ALTITUDES).

FLIGHT INSPECTED BY:

ELIZABETH WHALEY FICO 3/22/2016

REQUIRED EFFECTIVE DATE:

ROUTINE

DEVELOPED BY: *Digitally signed by*

KELLY DEAN **KELLY D DEAN** AJV-5411 01/12/2015

Jan 12, 2016

APPROVED BY:

GEORGE GONZALEZ AJV-5420

COORDINATED WITH:

ATA, ALPA, APA, AOPA, NBAA, ZAU, ORD DEP CON, ORD ATCT, ARPT MGR.

CHANGES: ABREV AMDT

1. CHANGED ALL REFERENCES FOR RWY 14R / 32L TO RWY 15 / 33 IN TAKEOFF MINIMUMS AND TAKEOFF OBSTACLE NOTES.
2. CHANGED RWY 32L TO RWY 33 IN CONTROLLING OBSTACLES AND REMARKS.
3. DELETED RWY 14L / 32R FROM TAKEOFF MINIMUMS AND TAKEOFF OBSTACLE NOTES.

REASONS:

- 1-3. RWY 14L / 32R IS BEING DECOMMISSIONED, RWY 14R / 32L IS BEING RENUMBERED RWY 15 / 33.

