

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>CITY, STATE</u>	<u>AIRPORT</u>	<u>EFFECTIVE DATE</u>	<u>AMDT NO</u>
AMBLER, AK	AMBLER		1

TAKEOFF MINIMUMS:

RWY 10, 28: NA-OBSTACLES.

RWY 1, STANDARD WITH MINIMUM CLIMB OF 260 FT PER NM TO 2400 OR 3400-3 FOR VCOA.

RWY 19, STANDARD.

TEXTUAL DEPARTURE PROCEDURES:

RWY 1: CLIMBING RIGHT TURN, THENCE...

RWY 19: CLIMBING LEFT TURN, THENCE...

...CLIMB SOUTHEAST BOUND ON 156 BEARING FROM AMF NDB TO 2600, THEN CLIMB ON COURSE.

VISUAL CLIMB OVER AIRPORT:

RWY 1: OBTAIN ATC APPROVAL FOR VCOA WHEN REQUESTING IFR CLEARANCE. CLIMB IN VISUAL CONDITIONS TO CROSS AMBLER AIRPORT AT OR ABOVE 3500 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 1: TREE 1772 FT FROM DER, 936 FT LEFT OF CENTERLINE, 51 FT AGL/315 FT MSL.

CONTROLLING OBSTACLES:

RWY 1: 1799 FT MSL AAO 670612.96N/1573232.94W.

RWY 1 (VCOA): 1199 MSL AAO 671002.58N/1575350.93W, 3599 MSL AAO 671249.22N/1575608.67W.

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT:

RWY 1, 19: 3599 FT MSL AAO 671249.22N/1575608.67W



Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

AMDT NO

1

Page 2 of 2