

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

| DP NAME | NUMBER | DP COMPUTER CODE | SUPERSEDED NUMBER | DATED | EFFECTIVE DATE |
|---------|--------|------------------|-------------------|-------|----------------|
| ARCHZ | ONE | ARCHZ1.ARCHZ | NONE | | |

| TYPE: | OBSTACLE | COPTER | SID | SPECIAL | RNAV |
|-------|--------------------------|--------------------------|-------------------------------------|--------------------------|-------------------------------------|
| | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |

DP ROUTE DESCRIPTION:

TAKEOFF RW34L, 34R, 35: CLIMBING LEFT TURN ON A HEADING BETWEEN 320 CCW 260 AS ASSIGNED BY ATC, THENCE...

...ON RADAR VECTORS TO CROSS SCANT AT OR ABOVE 10000, THEN ON TRACK 177.82 TO CROSS ARCHZ AT OR ABOVE 13000, THEN ON (TRANSITION). MAINTAIN FL230 OR LOWER FILED ALTITUDE. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

| TRANSITION NAME | TRANSITION COMPUTER CODE | FROM FIX/NAVAID | TO FIX/NAVAID | COURSE | DISTANCE | MEA | MOCA | CROSSING ALTITUDE/FIXES |
|-----------------|-----------------------------|--------------------|------------------|--------------|----------|-------|------|----------------------------|
| MILFORD | ARCHZ1.MLF | ARCHZ | TRILA | TRACK 186.37 | 23.97 | FL190 | | TRILA AT/ABOVE FL190 |
| | | TRILA | EDETH | TRACK 197.43 | 34.23 | FL190 | | |
| | | EDETH | SEVYR | TRACK 175.61 | 27.92 | FL190 | | |
| | | SEVYR | MLF VORTAC | TRACK 175.56 | 51.71 | FL190 | | |
| WINEN | ARCHZ1.WINEN | ARCHZ | TRILA | TRACK 186.37 | 23.97 | FL190 | | TRILA AT/ABOVE FL190 |
| | | TRILA | EDETH | TRACK 197.43 | 34.23 | FL190 | | |
| | | EDETH | WINEN | TRACK 186.17 | 109.47 | FL190 | | |
| KROST | ARCHZ1.KROST | ARCHZ | TRILA | TRACK 186.37 | 23.97 | FL190 | | TRILA AT/ABOVE FL190 |
| | | TRILA | EDETH | TRACK 197.43 | 34.23 | FL190 | | |
| | | EDETH | GAROT | TRACK 210.42 | 30.33 | FL190 | | |
| | | GAROT | KROST | TRACK 239.06 | 147.89 | FL240 | | |

PROCEDURAL DATA NOTES:

NOTE: RNAV 1.
NOTE: DME/DME/IRU OR GPS REQUIRED.
NOTE: RADAR REQUIRED.
NOTE: TURBOJET AIRCRAFT ONLY.

TAKEOFF MINIMUMS:

RWY 34L, 34R, 35: STANDARD WITH A MINIMUM CLIMB OF 260 FT PER NM TO 7800.
RWYS 14, 32, 16L, 16R, 17:NA-ATC

QUALITY
3
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

| <u>DP NAME</u> | <u>NUMBER</u> | <u>DP COMPUTER CODE</u> | <u>SUPERSEDED NUMBER</u> | <u>DATED</u> | <u>EFFECTIVE DATE</u> |
|----------------|---------------|-------------------------|--------------------------|--------------|-----------------------|
| ARCHZ | ONE | ARCHZ1.ARCHZ | NONE | | |

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 34R, POST 13 FT FROM DER, 349 FT RIGHT OF CENTERLINE, 3 FT AGL/4227 FT MSL.

NOTE: RWY 35, POST 56 FT FROM DER, 249 FT LEFT OF CENTERLINE, 2 FT AGL/4220 FT MSL.

CONTROLLING OBSTACLES:

RWY 34L, 34R, 35: 6796 FT MSL, AAO 405742.89N/1121257.40W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KSLC 11E EPOCH YEAR:2020

DME/DME/IRU ASSESSMENT:SAT(RNP 2.0)

CHART: TOP ALTITUDE FL230.

CHART MINIMUM CROSSING ALTITUDE AT SCANT 10000.

AIRPORTS SERVED:

| <u>AIRPORT NAME</u> | <u>CITY</u> | <u>STATE</u> |
|---------------------|----------------|--------------|
| SALT LAKE CITY INTL | SALT LAKE CITY | UT |

COMMUNICATIONS:

ATIS, CLNC DEL, CPDLC, GND CON, SLC ATCT, SLC DEP CON

FIXES AND/OR NAVAIDS:

REMARKS:

FLIGHT INSPECTED BY:

OFFICE SYMBOL:

DATE:

DEVELOPED BY:

DUSTIN DAVIDSON

Digitally signed by

DUSTIN DAVIDSON

Nov 21, 2017

OFFICE SYMBOL:

AJV-5422

DATE:

11/09/2017

APPROVED BY:

JULIE MORGAN

OFFICE SYMBOL:

AJV-5420

DATE:

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

| DP NAME | | | | | | NUMBER | DP COMPUTER CODE | SUPERSEDED NUMBER | DATED | EFFECTIVE DATE |
|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|--------------------------|-------------------------------------|--------|------------------|-------------------|-------|----------------|
| ARCHZ | | | | | | ONE | ARCHZ1.ARCHZ | NONE | | |
| A4A | ALPA | AOPA | APA | HAI | NBAA | | | | | |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | | | |

OTHER:

ZLC, SLC APP CON, SLC ATCT, AMGR

CHANGES - REASONS:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

| <u>DP NAME</u> | | <u>NUMBER</u> | | <u>DP COMPUTER CODE</u> | | <u>SUPERSEDED NUMBER</u> | | <u>DATED</u> | <u>EFFECTIVE DATE</u> |
|-------------------|------------------------|---------------|--------------|-------------------------|-----------|--------------------------|-----------------|--------------|-----------------------|
| ARCHZ | | ONE | | ARCHZ1.ARCHZ | | NONE | | | |
| <u>FIX/NAVAID</u> | <u>LAT/LONG</u> | <u>C</u> | <u>FO/FB</u> | <u>LEG TYPE</u> | <u>TC</u> | <u>DIST (NM)</u> | <u>ALTITUDE</u> | <u>SPEED</u> | <u>REMARKS</u> |
| SCANT | 404513.69N/1121623.71W | Y | - | IF | - | - | AT/ABOVE 10000 | | ARCHZ1.ARCHZ |
| ARCHZ | 403352.03N/1121842.39W | Y | FB | TF | 188.82 | 11.49 | AT/ABOVE 13000 | | |
| ARCHZ | 403352.03N/1121842.39W | Y | - | IF | - | - | AT/ABOVE 13000 | | ARCHZ1.KROST |
| TRILA | 401058.03N/1122802.59W | Y | FB | TF | 197.37 | 23.97 | AT/ABOVE FL190 | | |
| EDETH | 394048.65N/1124908.88W | Y | FB | TF | 208.43 | 34.23 | | | |
| GAROT | 391800.00N/1131500.00W | Y | FB | TF | 221.42 | 30.33 | | | |
| KROST | 382515.38N/1161154.98W | Y | FB | TF | 250.06 | 147.89 | | | |
| ARCHZ | 403352.03N/1121842.39W | Y | - | IF | - | - | AT/ABOVE 13000 | | ARCHZ1.MLF |
| TRILA | 401058.03N/1122802.59W | Y | FB | TF | 197.37 | 23.97 | AT/ABOVE FL190 | | |
| EDETH | 394048.65N/1124908.88W | Y | FB | TF | 208.43 | 34.23 | | | |
| SEVYR | 391302.81N/1125316.89W | Y | FB | TF | 186.61 | 27.92 | | | |
| MLF VORTAC | 382137.28N/1130047.64W | Y | FB | TF | 186.56 | 51.71 | | | |
| ARCHZ | 403352.03N/1121842.39W | Y | - | IF | - | - | AT/ABOVE 13000 | | ARCHZ1.WINEN |
| TRILA | 401058.03N/1122802.59W | Y | FB | TF | 197.37 | 23.97 | AT/ABOVE FL190 | | |
| EDETH | 394048.65N/1124908.88W | Y | FB | TF | 208.43 | 34.23 | | | |
| WINEN | 375600.00N/1133000.00W | Y | FB | TF | 197.17 | 109.47 | | | |

