

FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
GTLKE	ONE	GTLKE1.GTLKE	NONE		
TYPE:	OBSTACLE	COPTER	SID	SPECIAL	RNAV
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:  
CLEVELAND-HOPKINS INTL:

TAKEOFF RWY 06L: CLIMB ON HEADING 057.94 TO INTERCEPT COURSE 008.85 TO CROSS EDMNN AT OR ABOVE 2000 AND AT OR BELOW 240 KIAS, THEN ON TRACK 317.86 TO FTTZZ, THEN ON TRACK 262.90 TO CROSS GRALD AT OR ABOVE 8000, THEN ON TRACK 237.43 TO XMASS, THEN ON TRACK 249.13 TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 06R: CLIMB ON HEADING 057.94 TO INTERCEPT COURSE 004.85 TO CROSS EDMNN AT OR ABOVE 2000 AND AT OR BELOW 240 KIAS, THEN ON TRACK 317.86 TO FTTZZ, THEN ON TRACK 262.90 TO CROSS GRALD AT OR ABOVE 8000, THEN ON TRACK 237.43 TO XMASS, THEN ON TRACK 249.13 TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 10: CLIMB ON HEADING 101.31 TO 3000, THEN AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 24L: CLIMB ON HEADING 237.96 TO INTERCEPT COURSE 269.58 TO CROSS CNWAY AT OR BELOW 6000, THEN ON TRACK 259.89 TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 24R: CLIMB ON HEADING 237.95 TO INTERCEPT COURSE 268.92 TO CROSS CNWAY AT OR BELOW 6000, THEN ON TRACK 259.89 TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 28: CLIMB ON HEADING 281.32 TO 2200, THEN AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...

BURKE LAKEFRONT:

TAKEOFF RWY 06L: CLIMB ON HEADING 065.91 TO 1100, THEN ON HEADING 350.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 06R: CLIMB ON HEADING 065.92 TO 1100, THEN ON HEADING 350.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 24L: CLIMB ON HEADING 245.93 TO 1100, THEN RIGHT TURN HEADING 350.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 24R: CLIMB ON HEADING 245.92 TO 1100, THEN RIGHT TURN HEADING 350.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...

CUYAHOGA COUNTY:

TAKEOFF RWY 06: CLIMB ON HEADING 057.48 TO 2500, THEN ON HEADING 330.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 24: CLIMB ON HEADING 237.49 TO 2700, THEN RIGHT TURN HEADING 330.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...

LORAIN COUNTY RGNL:

TAKEOFF RWY 07: CLIMB ON HEADING 073.01 TO 2200, THEN ON HEADING 360.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 25: CLIMB ON HEADING 253.02 TO 2200, THEN RIGHT TURN HEADING 360.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...

WILLOUGHBY LOST NATION MUNI:

TAKEOFF RWY 05: CLIMB ON HEADING 052.59 TO 2500, THEN LEFT TURN HEADING 280.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 10: CLIMB ON HEADING 098.51 TO 2500, THEN LEFT TURN HEADING 280.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY 23: CLIMB ON HEADING 232.60 TO 2500, THEN ON HEADING 280.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 9000, THENCE...  
TAKEOFF RWY28: CLIMB ON HEADING 278.52 TO 2500, THEN ON HEADING 280.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO CROSS AYYLE AT OR ABOVE 10000, THENCE...

...ON TRACK 274.77 TO CROSS BRNIN AT OR BELOW 14000, THEN ON TRACK 284.15 TO GTLKE THEN ON (TRANSITION). MAINTAIN 14000, EXPECT FILED ALTITUDE TEN MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

TRANSITION NAME	TRANSITION COMPUTER CODE	FROM FIX/NAVAID	TO FIX/NAVAID	COURSE	DISTANCE	MEA	MOCA	CROSSING ALTITUDE/FIXES
ALPHE	GTLKE1.ALPHE	GTLKE	DORRT	TRACK 320.44	53.64	14000	2900	
		DORRT	ALPHE	TRACK 326.07	42.57	14000	3000	
BAGEL	GTLKE1.BAGEL	GTLKE	ELEOT	TRACK 286.25	14.42	14000	2100	
		ELEOT	MUNDR	TRACK 288.48	45.70	14000	2100	

QUALITY  
3  
CHECKED

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

DP NAME			NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
GTLKE			ONE	GTLKE1.GTLKE	NONE			
			MUNDR	BAGEL	TRACK 280.65	59.36	14000	2400
DAIFE	GTLKE1.DAIFE	GTLKE	ELEOT	TRACK 286.25	14.42	14000	2100	
			ELEOT	NOLNN	TRACK 272.26	60.73	14000	2400
			NOLNN	DAIFE	TRACK 280.55	55.19	14000	2300
YABRO	GTLKE1.YABRO	GTLKE	ELEOT	TRACK 286.25	14.42	14000	2100	
			ELEOT	NESSS	TRACK 279.63	59.48	14000	2100
			NESSS	YABRO	TRACK 280.49	49.24	14000	2500

**PROCEDURAL DATA NOTES:**

RADAR REQUIRED

RNAV 1

DME/DME/IRU OR GPS REQUIRED

BAGEL TRANSITION: FOR AIRCRAFT LANDING MDW ONLY, OR AS ASSIGNED BY ATC.

DAIFE TRANSITION: FOR AIRCRAFT LANDING ORD ONLY, OR AS ASSIGNED BY ATC.

**TAKEOFF MINIMUMS:**

**CLEVELAND-HOPKINS INTL:** RWY 6L, 6R, 24R, 24L, 28 STANDARD WITH A MINIMUM CLIMB OF 500 FT PER NM TO 1300. **RWY 10** STANDARD WITH A MINIMUM CLIMB OF 500 FT PER NM TO 1600.

**BURKE LAKEFRONT:** RWY 6R, 6L, 24R STANDARD WITH A MINIMUM CLIMB OF 500 FT PER NM TO 1100. **RWY 24L** 400-1 3/8 OR STANDARD WITH MINIMUM CLIMB OF 757 FT PER NM TO 1000.

**CUYAHOGA COUNTY:** RWY 6, 24 STANDARD WITH A MINIMUM CLIMB OF 500 FT PER NM TO 1400.

**LORAIN COUNTY RGNL:** RWY 7, 25 STANDARD WITH A MINIMUM CLIMB OF 500 FT PER NM TO 1300.

**WILLOUGHBY LOST NATION MUNI:** RWY 5, 10, 23, 28 STANDARD WITH A MINIMUM CLIMB OF 500 FT PER NM TO 1140.

**TAKEOFF OBSTACLES NOTES:**

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

**CONTROLLING OBSTACLES:**

**CLEVELAND-HOPKINS INTL:** RWY 10 2048 FT MSL TOWER 412254.00N/0814157.00W.

**BURKE LAKEFRONT:** RWY 24L: 740 FT MSL BUILDING 413031.10N/0814144.07W (CLIMB GRADIENT), 896 FT MSL BUILDING 413004.41N/0814214.10W (CEILING/CLIMB-TO ALTITUDE), 787 FT MSL BRIDGE 412953.73N/0814231.66W (VISIBILITY).

**LOST COMMUNICATIONS PROCEDURES:**

**ADDITIONAL FLIGHT DATA:**

REFERENCE MAG VAR: KCLE 8W EPOCH YEAR: 2020

CHART: TOP ALTITUDE: 14000

DME/DME/IRU ASSESSMENT: SAT (RNP 2.0)

CHART SPEED ICON MAXIMUM SPEED 240 KIAS AT EDMNN



**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
GTLKE	ONE	GTLKE1.GTLKE	NONE		

**AIRPORTS SERVED:**

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
CLEVELAND-HOPKINS INTL (KCLE)	CLEVELAND	OH
BURKE LAKEFRONT (KBKL)	CLEVELAND	OH
CUYAHOGA COUNTY (KCGF)	CLEVELAND	OH
LORAIN COUNRY RGNL (KLPR)	LORAIN/ELYRIA	OH
WILLOUGHBY LOST NATION MUNI (KLNN)	WILLOUGHBY	OH

**COMMUNICATIONS:**

**CLEVELAND-HOPKINS INTL:** ATIS, CLNC DEL, CPDLC, GND CON, CLE ATCT, CLE APP CON, CLE DEP CON.

**BURKE LAKEFRONT:** ATIS, AWOS/ASOS, BKL ATCT, CTAF DEPARTURE CONTROL.

**CUYAHOGA COUNTY:** ATIS, AWOS/ASOS, CGF ATCT, CTAF DEPARTURE CONTROL.

**LORAIN COUNTY RGNL:** ATIS, AWOS/ASOS, LPR ATCT, CTAF DEPARTURE CONTROL.

**WILLOUGHBY LOST NATION MUNI:** ATIS, AWOS/ASOS, LNN ATCT, CTAF DEPARTURE CONTROL.

**FIXES AND/OR NAVAIDS:**

**REMARKS:**

THE ENVIRONMENTAL REVIEW UNDER ORDER 1050.1F AND THE NOISE SCREENING HAVE BEEN ACCOMPLISHED.

CATEGORICAL EXCLUSION ISSUED.

MOCA(S) NOT CHARTED PER ATC REQUEST TO REDUCE CHART CLUTTER.

LETTER OF APPROVAL ON FILE FOR KBKL RWY 24L MINIMUM CLIMB OF 757 FT PER NM TO 1000.

02/23/18: THIS IS AN UPDATED COPY OF THE FORM DEVELOPED ON 11/28/17. JH

1. CHANGED 8260-15B, ENROUTE TRANSITION NAME FROM GTLKE TO DAIFE ON GTLKE1.DAIFE.
2. CHANGED 8260-15B, ENROUTE TRANSITION NAME FROM GTLKE TO YABRO ON GTLKE1.YABRO.
3. ADDED CHART NOTE: BAGEL TRANSITION: FOR AIRCRAFT LANDING MDW ONLY, OR AS ASSIGNED BY ATC.
4. ADDED CHART NOTE: DAIFE TRANSITION: FOR AIRCRAFT LANDING ORD ONLY, OR AS ASSIGNED BY ATC.



**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
GTLKE	ONE	GTLKE1.GTLKE	NONE		
<u>FLIGHT INSPECTED BY:</u>			<u>OFFICE SYMBOL:</u>	<u>DATE:</u>	
 <u>DEVELOPED BY:</u> <i>Digitally signed by</i>			<u>OFFICE SYMBOL:</u>	<u>DATE:</u>	
HEIDI SNIDER <b><i>HEIDI SNIDER</i></b>			AJV-5423	11/28/2017	
Jan 30, 2018					
<u>APPROVED BY:</u>			<u>OFFICE SYMBOL:</u>	<u>DATE:</u>	
JULIE MORGAN			AJV-5420		
<u>REQUIRED EFFECTIVE DATE:</u>					
ROUTINE					
<u>COORDINATED WITH:</u>					
<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<u>OTHER:</u>					
ZOB, CLE APP CON, CLE ATCT, CFPT, AMGR					
<u>CHANGES - REASONS:</u>					
ORIGINAL - ATC REQUEST					

QUALITY  
3  
CHECKED

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)**

DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
GTLKE							ONE	GTLKE1.GTLKE	NONE		
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED		REMARKS	
	CLEVELAND-HOPKINS INTL					(KCLE)					
RW06L (AER)	412359.53N/0815224.55W	N	-	-	-	-					
-	412536.89N/0814950.69W	-	-	VI	049.94	1.04				CG 500 FT/NM TO 1300; RECOMMENDED NAVAID: EWC VOR/DME	
EDMNN	412932.72N/0814946.03W	Y	FB	CF	000.85	3.93	AT/ABOVE 2000	AT/BELOW 240K			
FTTZZ	413220.00N/0815412.81W	Y	FB	TF	309.86	4.35					
GRALD	413054.16N/0820114.98W	Y	FB	TF	254.90	5.47	AT/ABOVE 8000				
XMASS	412240.23N/0821359.82W	Y	FB	TF	229.43	12.63					
AYYLE	411655.55N/0822746.51W	Y	FB	TF	241.13	11.86	AT/ABOVE 9000				
RW06R (AER)*	412404.10N/0815152.03W*	N	-	-	-	-				*DISPL THLD (1926.0 FEET)	
-	412534.86N/0814928.56W	-	-	VI	049.94	1.03				CG 500 FT/NM TO 1300; RECOMMENDED NAVAID: EWC VOR/DME	
EDMNN	412932.72N/0814946.03W	Y	FB	CF	356.84	3.97	AT/ABOVE 2000	AT/BELOW 240K			
FTTZZ	413220.00N/0815412.81W	Y	FB	TF	309.86	4.35					
GRALD	413054.16N/0820114.98W	Y	FB	TF	254.90	5.47	AT/ABOVE 8000				
XMASS	412240.23N/0821359.82W	Y	FB	TF	229.43	12.63					
AYYLE	411655.55N/0822746.51W	Y	FB	TF	241.13	11.86	AT/ABOVE 9000				
RW10 (AER)	412501.26N/0815115.28W	N	-	-	-	-					
1300 MSL	-	-	-	VA	093.31	-				CG 500 FT/NM TO 1600	
-	-	-	-	VM	093.31	-					
RW24L (AER)	412455.14N/0815031.37W	N	-	-	-	-					

QUALITY

3

QUALITY  
3  
CHECKED

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)**

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		EFFECTIVE DATE	
GTLKE		ONE		GTLKE1.GTLKE		NONE					
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS		
-	412311.33N/0815315.36W	-	-	VI	229.96	1.05			CG 500 FT/NM TO 1300; RECOMMENDED NAVAID: EWC VOR/DME		
CNWAY	412120.89N/0820956.85W	Y	FB	CF	261.58	12.70	AT/BELOW 6000				
AYYLE	411655.55N/0822746.51W	Y	FB	DF	251.89	14.14	AT/ABOVE 9000				
RW24R (AER)	412456.75N/0815054.15W	N	-	-	-	-					
-	412318.61N/0815329.17W	-	-	VI	229.95	1.06			CG 500 FT/NM TO 1300; RECOMMENDED NAVAID: EWC VOR/DME		
CNWAY	412120.89N/0820956.85W	Y	FB	CF	260.92	12.55	AT/BELOW 6000				
AYYLE	411655.55N/0822746.51W	Y	FB	TF	251.89	14.14	AT/ABOVE 9000				
RW28 (AER)	412457.82N/0814956.44W	N	-	-	-	-					
1300 MSL	-	-	-	VA	273.32	-			CG 500 FT/NM TO 1300		
-	-	-	-	VM	273.32	-					
BURKE LAKEFRONT					(KBKL)						
RW06L (AER)*	413051.82N/0814129.42W*	N	-	-	-	-			*DISPL THLD (178.0 FEET)		
1100 MSL	-	-	-	VA	057.91	-			CG 500 FT/NM TO 1100		
-	-	-	-	VM	342.00	-					
RW06R (AER)*	413047.12N/0814127.01W*	N	-	-	-	-			*DISPL THLD (275 FEET)		
1100 MSL	-	-	-	VA	057.92	-			CG 500 FT/NM TO 1100		
-	-	-	-	VM	342.00	-					

QUALITY

3

QUALITY  
3  
CHECKED

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)**

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		EFFECTIVE DATE	
GTLKE		ONE		GTLKE1.GTLKE		NONE					
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS		
RW24L (AER)	413112.95N/0814032.20W	N	-	-	-	-					
1100 MSL	-	-	-	VA	237.93	-			CG 500 FT/NM TO 1100		
-	-	-	-	VM	342.00	-			RIGHT TURN		
RW24R (AER)*	413122.39N/0814024.54W*	N	-	-	-	-			DISPL THLD (600.00 FEET)		
1100 MSL	-	-	-	VA	237.92	-			CG 500 FT/NM TO 1100		
-	-	-	-	VM	342.00	-			RIGHT TURN		
CUYAHOGA COUNTY						(KCGF)					
RW06 (AER)	413338.07N/0812936.39W	N	-	-	-	-					
2500 MSL	-	-	-	VA	049.48	-			CG 500 FT/NM TO 1400		
-	-	-	-	VM	322.00						
RW24 (AER)*	413410.82N/0812845.37W*	N	-	-	-	-			*DISPL THLD (501.48 FEET)		
2700 MSL	-	-	-	VA	229.49	-			CG 500 FT/NM TO 1400		
-	-	-	-	VM	322.00				RIGHT TURN		
LORAIN COUNTY RGNL						(KLPR)					
RW07 (AER)	412028.96N/0821109.17W	N	-	-	-	-					
2200 MSL	-	-	-	VA	065.01	-			CG 500 FT/NM TO 1300		
-	-	-	-	VM	352.00						

QUALITY

3

2025-01-01

QUALITY  
3  
CHECKED

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)**

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		EFFECTIVE DATE	
GTLKE		ONE		GTLKE1.GTLKE		NONE					
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS		
RW25 (AER)	412049.83N/0821009.74W	N	-	-	-	-					
2200 MSL	-	-	-	VA	245.02	-			CG 500 FT/NM TO 1300		
-	-	-	-	VM	352.00				RIGHT TURN		
WILLOUGHBY LOST NATION MUNI						(KLNN)					
RW05 (AER)*	414052.54N/0812346.82W*	N	-	-	-	-			*DISPL THLD (428.0 FEET)		
2500 MSL	-	-	-	VA	044.59	-			CG 500 FT/NM TO 1140		
-	-	-	-	VM	272.00				LEFT TURN		
RW10 (AER)	414057.07N/0812346.03W	N	-	-	-	-					
2500 MSL	-	-	-	VA	090.51	-			CG 500 FT/NM TO 1140		
-	-	-	-	VM	272.00	-			LEFT TURN		
RW23 (AER)	414124.90N/0812304.26W	N	-	-	-	-					
2500 MSL	-	-	-	VA	224.60	-			CG 500 FT/NM TO 1140		
-	-	-	-	VM	272.00						
RW28 (AER)*	414056.79N/0812304.54W*	N	-	-	-	-			*DISPL THLD (1124.0 FEET)		
2500 MSL	-	-	-	VA	270.52	-			CG 500 FT/NM TO 1140		
-	-	-	-	VM	272.00	-					
COMMON TRANSITION											

QUALITY

3

CHECKED

QUALITY  
3  
CHECKED



**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
GTLKE		ONE		GTLKE1.GTLKE		NONE			
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
AYYLE	411655.55N/0822746.51W	Y	-	IF	-	-	AT/ABOVE 9000		
BRNIN	411636.64N/0823814.05W	Y	FB	TF	267.77	7.89	AT/BELOW 14000		
GTLKE	411833.58N/0825909.65W	Y	FB	TF	277.15	15.89			
ENROUTE TRANSITION									
GTLKE	411833.58N/0825909.65W	Y	-	IF	-	-			GTLKE1.ALPHE
DORRT	415434.50N/0835210.74W	Y	FB	TF	312.44	53.64			
ALPHE	422609.24N/0843035.70W	Y	FB	TF	318.07	42.57			
GTLKE	411833.58N/0825909.65W	Y	-	IF	-	-			GTLKE1.BAGEL
ELEOT	412036.20N/0831806.19W	Y	FB	TF	278.25	14.42			
MUNDR	412839.70N/0841753.41W	Y	FB	TF	280.48	45.70			
BAGEL	413057.51N/0853649.28W	Y	FB	TF	272.65	59.36			
GTLKE	411833.58N/0825909.65W	Y	-	IF	-	-			GTLKE1.DAIFE
ELEOT	412036.20N/0831806.19W	Y	FB	TF	278.25	14.42			
NOLNN	411403.75N/0843812.01W	Y	FB	TF	264.26	60.73			
DAIFE	411608.00N/0855119.00W	Y	FB	TF	272.55	55.19			
GTLKE	411833.58N/0825909.65W	Y	-	IF	-	-			GTLKE1.YABRO
ELEOT	412036.20N/0831806.19W	Y	FB	TF	278.25	14.42			
NESSS	412150.66N/0843704.18W	Y	FB	TF	271.63	59.48			
YABRO	412340.69N/0854226.27W	Y	FB	TF	272.49	49.24			

QUALITY  
3  
CHECKED