

[Print](#)

Project Name: BMI - RVR 1800 backup altimeter notes

Project Reason: 1. Backup altimeter restriction added to RVR 1800 note IAW 8/24/17 Memo, "Guidance for 8400.13 CAT I RVR 1800 Approach Operations with RASS". 2. Add inoperative ALS note for primary and backup altimeter sources.

Last Updated By: Russell Roslewski

Last Updated At: 2018-03-02 18:50:22.446485

Digitally signed by

ROBERT G HAMILTON

May 30, 2018

Status: Verified

!FDC 8/6132 BMI IAP CENTRAL IL RGNL ARPT AT BLOOMINGTON-NORMAL, Bloomington/Normal, IL. ILS OR LOC RWY 29, AMDT 11A... DELETE NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA. CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA (NA WHEN USING GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING). CHART NOTE: LOC MINIMUMS: FOR INOPERATIVE ALS, INCREASE S-LOC 29 CATS C AND D VISIBILITY TO 1 3/8 SM; WURSU FIX MINIMUMS: FOR INOPERATIVE ALS, INCREASE S-LOC 29 VISIBILITY TO RVR 5500. CHART NOTE: FOR INOPERATIVE ALS WHEN USING GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING: INCREASE S-ILS 29 VISIBILITY TO RVR 4500; INCREASE S-LOC 29 CATS C AND D VISIBILITY TO 1 3/4 SM; INCREASE WURSU FIX MINIMUMS S-LOC 29 CATS C AND D VISIBILITY TO 1 3/8 SM. THIS IS ILS OR LOC RWY 29, AMDT 11B. 1803021850-PERM

