

[Print](#)

Project Name: HYA - RVR 1800 backup altimeter notes

Project Reason: ILS OR LOC RWY 15: Backup altimeter restriction added to RVR 1800 note IAW 8/24/17 Memo, "Guidance for 8400.13 CAT I RVR 1800 Approach Operations with RASS". RNAV (GPS) RWY 15: 1. Increase LNAV visibility Cat C to RVR 6000 due to current calculations. 2. Increase Circling visibility Cat C to 1 5/8 sm due to current calculations. 3. Add (NA when using...) to RVR 1800 note due to current policy. 4. adjust inoperative note and backup altimeter note due to current calculations. 5. replace DME/DME note with PBN requirements note due to current policy. 6. correct "procedure na for arrivals..." note to read northwest bound.

Last Updated By: Russell Roslewski

Last Updated At: 2018-02-28 15:10:50.978975

Status: Verified

8/8564

!FDC X/XXXX HYA IAP BARNSTABLE MUNI-BOARDMAN/POLANDO FIELD, Hyannis, MA. RNAV (GPS) RWY 15, ORIG-A... LNAV VIS CAT C RVR 6000. CIRCLING VIS CAT C 1 5/8. DELETE NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA. CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA (NA WHEN USING CHATHAM ALTIMETER SETTING). DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHATHAM ALTIMETER SETTING AND INCREASE ALL DA 33 FEET AND ALL MDA 40 FEET. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHATHAM ALTIMETER SETTING: INCREASE ALL DAS 33 FEET; INCREASE ALL MDAS 40 FEET AND VISIBILITY LNAV CATS C AND D AND CIRCLING CAT C 1/8 SM. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHANGE NOTE: PROCEDURE NA FOR ARRIVALS AT BOS VOR/DME ON V141 NORTHEAST BOUND TO READ NORTHWEST BOUND. THIS IS RNAV (GPS) RWY 15, ORIG-B. 1802281510-PERM

Digitally signed by
DION E LANCIA
Mar 27, 2018

