

[Print](#)

Project Name: BMI BLOOMINGTON NORMAL ILS OR LOC/DME RWY 2 FPT REQ

Project Reason: Allan, Can you please prepare NOTAM to raise the visibility for the ILS or LOC/DME RWY 2 from 1/2 SM to 3/4 SM. Please see request information below from the airport. Please provide NOTAM FDC # when done. Any questions, please let me know and thanks in advance. Ponce Barber Airspace Program Evaluation Specialist Ponce Barber further advises, from an e-mail response dated 4/30/2015, that this NOTAM should not be made permanent. reauth 10/27/15...ens From the ADO via the airport manager...so we'll need to enter a project to amend this permanently...NOTAM still required until we amend. In follow-up to conversations I had with both you and the airport sponsor, it appears as if the most realistic approach to the temporary raised minimums issue is to allow the temporary status to be allowed to become a permanent status. The situation locally at the airport with the building located within the Runway Protection Zone (the larger RPZ associated with the 1/2 -mile visibility minimums) does not appear to be changing in the near future. I did explain to the airport sponsor the timeframe and effort involved with lowering the minimums down in the future to 1/2 -mile visibility. From: Barber, Ponce (FAA) Sent: Thursday, October 19, 2017 9:14 AM To: Sadorra, Marcello G (FAA) Subject: RE: KBMI: NOTAM for ILS or LOC/DME RWY 2

Last Updated By: Leo Palmer

*Digitally signed by*

Last Updated At: 2018-11-21 17:37:02.586752

**DAVID DANNER**

Nov 27, 2018

Status: Verified

8/1335

!FDC X/XXXX BMI IAP CENTRAL IL RGNL ARPT AT BLOOMINGTON-NORMAL, Bloomington/Normal, IL. ILS OR LOC/DME RWY 2, ORIG-B... S-ILS 2 VIS RVR 4000 ALL CATS. S-LOC 2 VIS RVR 4000 CATS A/B. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 2 CAT A/B VISIBILITY TO RVR 5500 AND CAT C/D TO RVR 6000. DELETE NOTE: FOR INOPERATIVE MALSR WHEN USING GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING, INCREASE S-ILS 2 ALL CATS VISIBILITY TO RVR 5000. CHART NOTE: FOR INOPERATIVE ALS WHEN USING GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING, INCREASE S-ILS-2 ALL CATS VISIBILITY TO RVR 4500, S-LOC-2 CAT C/D VISIBILITY TO 1-3/8 SM. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-ILS 2. THIS IS ILS OR LOC/DME RWY 2, ORIG-C. 1811211737-PERM

QUALITY  
24  
CHECKED