

[Print](#)

Project Name: IA, SPW_ILS OR LOC RWY 12, AMDT 2B

Project Reason: NEW S-LOC 12 OBSTACLES, 7:1 OBSTACLE: 19-053698, WINDMILL 431343.54N/0952034.95W 1932 MSL (4D), FINAL OBSTACLE: 19-028232, TRANSMISSION_LINE 431219.21N/0951721.16W 1513 MSL (4D) - NEW DATA SINCE LAST AMENDMENT. OBSTACLE 1513 + ROC 250 + (AC) 50 + (XL) 14 = 1827 (1840). CHART FAS OBST CHANGED FROM 1579 AAO 431142N/0951646W TO 1513 TRANSMISSION_LINE 431219N/0951721W - NEW DATA SINCE LAST AMENDMENT. S-LOC 12 MDA/HAT RAISED FROM 1760/421 TO 1840/501 ALL CATS - NEW FAS OBSTACLE. S-LOC 12 CATS C AND D VISIBILITY CHANGED FROM 3/4 TO 1 - HIGHER MDA/HAT. ADDED CHART CIRCLING ICON - NEW CIRCLING RADII, FLIGHT CHECK WITH RNAV (GPS) RWY 30, AMDT 1, DATED 5/14/13. CIRCLING CAT A MDA/HAA CHANGED FROM 1780/441 TO 1840/501 - S-LOC 12 STRAIGHT-IN MINIMA. CIRCLING CAT B MDA/HAA CHANGED FROM 1800/461 TO 1840/501 - S-LOC 12 STRAIGHT-IN MINIMA. CIRCLING CAT C MDA/HAA CHANGED FROM 1800/461 TO 2100/761, VISIBILITY CHANGED FROM 1 1/2 TO 2 1/4 - NEW CIRCLING RADII, FLIGHT CHECK WITH RNAV (GPS) RWY 30, AMDT 1, DATED 5/14/13. CIRCLING CAT D MDA/HAA CHANGED FROM 2040/701 TO 2100/761, VISIBILITY CHANGED FROM 2 1/4 TO 2 1/2 - NEW CIRCLING RADII, FLIGHT CHECK WITH RNAV (GPS) RWY 30, AMDT 1, DATED 5/14/13. DELETED ALL BACKUP ALTIMETER NOTES TO INCLUDE INOPERATIVE MALSR NOTE - REPLACED WITH NEW NOTES. ADDED INOPERATIVE ALS MINIMUMS NOTE - SUPPORTS NEW INOPERATIVE TABLE.

Last Updated By: Deanna Fields

Last Updated At: 2018-11-20 15:37:39.264587

Status: Verified

Digitally signed by

DAVID DANNER

Mar 04, 2019

!FDC 9/0996 SPW IAP SPENCER MUNI, Spencer, IA. ILS OR LOC RWY 12, AMDT 2A... S-LOC 12 MDA 1840/HAT 501 ALL CATS, VISIBILITY CATS C/D 1. CIRCLING CATS A/B MDA 1840/HAA 501. CIRCLING CAT C MDA 2100/HAA 761, VISIBILITY 2 1/4. CIRCLING CAT D MDA 2100/HAA 761, VISIBILITY 2 1/2. CHART 1932 WINDMILL 431344N/0952035W. CHART FAS OBST: 1513 TRANSMISSION LINE 431219N/0951721W. CHART CIRCLING ICON. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 12 CATS C/D VISIBILITY TO 1-3/8 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ESTHERVILLE ALTIMETER SETTING: INCREASE DA AND ALL MDAS 60 FEET; INCREASE VISIBILITY S-LOC 12 CATS C AND D AND CIRCLING CATS C AND D 1/4 SM. CHART NOTE: FOR INOPERATIVE ALS, WHEN USING ESTHERVILLE ALTIMETER SETTING, INCREASE S-ILS 12 ALL CATS VISIBILITY TO 1 SM AND S-LOC 12 CATS C/D VISIBILITY TO 1-5/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ESTHERVILLE ALTIMETER SETTING AND INCREASE DA AND ALL MDA 60 FEET, INCREASE S-LOC 12 AND CIRCLING CAT D VISIBILITY 1/4 MILE. DELETE NOTE: FOR INOPERATIVE MALSR, WHEN USING ESTHERVILLE ALTIMETER SETTING, INCREASE S-ILS 12 ALL CATS VISIBILITY TO 1 MILE. THIS IS ILS OR LOC RWY 12, AMDT 2B. 1811201537-PERM

