

[Print](#)

Project Name: AUS - RNAV (GPS) Y RWY 17L

Project Reason: REPLACING T- NOTAM IFDC 8/0041 WHICH IS APPROACHING ITS EXPIRATION DATE WITH A P- NOTAM. UPDATED LNAV MDA FROM 880/HAT 388 ALL CATS TO MDA 900/HAT 408 ALL CATS AND CATS C/D/E VISIBILITY FROM RVR 3500 TO RVR 4000 - NEW LNAV FINAL CONTROLLING OBSTACLE: 647 MSL ANTENNA (48-135609) AT 301234.02N/0973900.51W, AC 1A. DELETE NOTE: CHART VDP AT 0.98 NM TO RW17L*. NOTE: CHART VDP AT 1.05 NM TO RW17L* - REFERENCE UPDATED CALCULATIONS. DELETED NOTE: DME/DME RNP-0.3 NA AND ADDED PBN REQUIREMENTS NOTE: RNP APCH - REFERENCE REVISED CRITERIA. EQUIPMENT REQUIREMENTS NOTE: RADAR REQUIRED FOR PROCEDURE ENTRY - MOVED EQUIPMENT REQUIREMENTS NOTE ENTRY FROM 8260-9 TO 8260-3. ADDED 20:1 IS CLEAR - REFERENCE NO VISUAL SURFACE PENETRATIONS. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -6C (22F) OR ABOVE 54C (130F). NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -6C OR ABOVE 54C - FAHRENHEIT NO LONGER REQUIRED. DELETE NOTE: FOR INOP ALS, INCREASE LPV CAT E VISIBILITY TO RVR 4000, INCREASE LNAV/VNAV CAT E VISIBILITY TO 1 3/8 SM AND INCREASE LNAV CAT E VISIBILITY TO RVR 6000. NOTE: FOR INOPERATIVE ALS, INCREASE LPV CAT E VISIBILITY TO RVR 4000, INCREASE LNAV/VNAV CAT E VISIBILITY TO 1 3/8 SM AND INCREASE LNAV CATS C/D/E VISIBILITY TO 1 1/8 SM - REFERENCE REVISED VISIBILITY MINIMUMS.

Last Updated By: Sylvan Drakes

Last Updated At: 2019-03-21 11:56:03.325712

Status: Verified

FDC 9/1725

Digitally signed by
WARDELL HENNING
Mar 26, 2019

IFDC X/XXXX AUS IAP AUSTIN-BERGSTROM INTL, Austin, TX. RNAV (GPS) Y RWY 17L, AMDT 2... DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. EQUIPMENT REQUIREMENTS NOTE: RADAR REQUIRED FOR PROCEDURE ENTRY. CHART VDP AT 1.05 NM TO RW17L*. LNAV MDA 900/HAT 408 ALL CATS, VISIBILITY CATS C/D/E RVR 4000. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -6C (22F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -6C OR ABOVE 54C. DELETE NOTE: FOR INOP ALS, INCREASE LPV CAT E VISIBILITY TO RVR 4000, INCREASE LNAV/VNAV CAT E VISIBILITY TO 1 3/8 SM AND INCREASE LNAV CAT E VISIBILITY TO RVR 6000. CHART NOTE: FOR INOPERATIVE ALS, INCREASE VISIBILITY LPV CAT E TO RVR 4000, LNAV/VNAV CAT E TO 1 3/8 SM AND LNAV CATS C/D/E TO 1 1/8 SM. THIS IS RNAV (GPS) Y RWY 17L, AMDT 2A. 1903211156-PERM

QUALITY
31
CHECKED