

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> COLORADO PLAINS RGNL	<u>AIRPORT ID</u> KAKO	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 11	<u>ORIGINAL/AMENDMENT</u> 2A	<u>CITY</u> AKRON	<u>STATE</u> CO	
<u>AIRPORT ELEVATION</u> 4716	<u>TDZE</u> 4716	<u>SUPERSEDED</u> RNAV (GPS) RWY 11	<u>ORIGINAL/AMENDMENT</u> 2	<u>DATED</u> 03/02/2017	<u>MAG VAR</u> 10E	<u>EPOCH YEAR</u> 2000
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u>	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TAA

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>ALTITUDE</u>
1. 019/30 CW 199/30	NOPT	019/15 CW 199/15		8700
2. 019/15 CW 199/15		KUKMY	IF/IAF	7500
3. 199/30 CW 289/30		FENGA	IAF	10000
4. 289/30 CW 019/30		CASMI	IAF	10000

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
FENGA	IAF	KUKMY	NOPT	TF	FB	1.00	199.23	10.00	7500
CASMI	IAF	KUKMY	NOPT	TF	FB	1.00	019.09	10.00	7500
KUKMY	IF/IAF	ADEWU		TF	FB	1.00	109.16	8.00	6300
ADEWU	FAF	RW11	MAP	TF	FO	0.30	109.26	4.80	
RW11	MAP	4966 MSL		CA			109.26		
4966 MSL		JUBOS		DF	FO	1.00			7500

MISSED APPROACH

MAP:

LPV: DA
LNAV/VNAV: DA
LNAV: RW11

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 7500 DIRECT JUBOS AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. HOLD W KUKMY, RT, 109.16 INBOUND, 7500 FT. IN LIEU OF PT (IAF), MAX 17500.

3. FAC: 109.26FAF: ADEWUDIST FAF TO MAP: 4.80DIST FAF TO THLD: 4.80

4. MIN ALT: KUKMY 7500, ADEWU 6300

5. DIST TO THLD FROM OM:MM:IM:150 HAT:250 HAT: 0.62GS ANT:

6. MIN GP INCPT: 6300GP ALT AT FAF : ADEWU 6300OM:MM:IM:

7. GP ANGLE: 3.0034:1: IS NOT CLEAR20:1: IS CLEARTCH: 54.1

8. MSA FROM:

PBN REQUIREMENTS NOTE:

RNP APCH

NOTES:

CHART NOTE: RWY 11 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -22°C OR ABOVE 54°C.
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON.
CHART VDP AT 0.81 NM TO RW11*
*LNAV ONLY
WAAS CHANNEL #82340
REFERENCE PATH ID: W11A
CHART FAS OBST: 4758 POLE 401037N/1031440W.
HOLD E, RT, 289.49 INBOUND
LTP HAE: 1417.2 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - CAT D 800-2 1/4

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LPV DA	4966	1	250	4966	1	250	4966	1	250	4966	1	250			
LNAV/VNAV DA	4966	1	250	4966	1	250	4966	1	250	4966	1	250			
LNAV MDA	5020	1	304	5020	1	304	5020	1	304	5020	1	304			
CIRCLING	5140	1	424	5260	1	544	5420	2	704	5420	2 1/4	704			



FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAKO
RUNWAY	RW11
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W11A
LTP/FTP LATITUDE	401049.2095N
LTP/FTP LONGITUDE	1031358.6055W
LTP/FTP ELLIPSOIDAL HEIGHT	+14172
FPAP LATITUDE	401005.5385N
FPAP LONGITUDE	1031217.2655W
THRESHOLD CROSSING HEIGHT (TCH)	00054.1
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0616
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
CRC REMAINDER	21ADE4C4

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+14374
FPAP ORTHOMETRIC HEIGHT	+14374



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD INSTRUMENT APPROACH PROCEDURE DATA RECORD

<u>AIRPORT</u> COLORADO PLAINS RGNL	<u>AIRPORT ID</u> KAKO	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 11	<u>AMDT NO.</u> 2A	<u>CITY</u> AKRON	<u>STATE</u> CO	<u>AIRPORT ELEVATION</u> 4716	<u>FACILITY</u> RNAV
--	---------------------------	--	-----------------------	----------------------	--------------------	----------------------------------	-------------------------

PART A: OBSTRUCTION DATA SEGMENTS

STRAIGHT-IN AREA

FROM
019/30 CW 199/30

TO
019/15 CW 199/15

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>	<u>HAT</u>			<u>HMAS</u>				
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
1.TOWER (08-000971)	395521.84N/1035820.21W	6950	50	20	2C	2000				MT-250	8700
2.TERRAIN	395333.00N/1035339.00W	5108 (5100)								AS1500	6600

<u>COMPUTATIONS</u>	<u>ALT</u>	<u>KIAS</u>	<u>KTAS</u>	<u>HAA</u>	<u>VKTW</u>	<u>TR</u>	<u>BA</u>	<u>DTA</u>	<u>COURSE CHANGE</u>	<u>DVEB</u>	<u>VEB OCS</u>	<u>RF CENTER FIX/DISTANCE</u>
---------------------	------------	-------------	-------------	------------	-------------	-----------	-----------	------------	----------------------	-------------	----------------	-------------------------------

SEGMENT REMARKS:

STRAIGHT-IN AREA

FROM
019/15 CW 199/15

TO
KUKMY

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>	<u>HAT</u>			<u>HMAS</u>				
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
3.TOWER (08-000376)	402513.90N/1034538.80W	5023	500	50	5C	2000				AT477	7500
4.TERRAIN	402503.00N/1034548.00W	4958 (5000)								AS1500	6500

<u>COMPUTATIONS</u>	<u>ALT</u>	<u>KIAS</u>	<u>KTAS</u>	<u>HAA</u>	<u>VKTW</u>	<u>TR</u>	<u>BA</u>	<u>DTA</u>	<u>COURSE CHANGE</u>	<u>DVEB</u>	<u>VEB OCS</u>	<u>RF CENTER FIX/DISTANCE</u>
---------------------	------------	-------------	-------------	------------	-------------	-----------	-----------	------------	----------------------	-------------	----------------	-------------------------------

SEGMENT REMARKS:



LEFT BASE AREA

FROM

199/30 CW 289/30

TO

FENGA

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>	<u>HAT</u>			<u>HMAS</u>					
<u>OBSTRUCTION</u>	<u>COORDINATES</u>		<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
5.TREE	400851.00N/1031700.00W		4871	500	125	5E	2000				AT3129	10000
6.TERRAIN	400851.00N/1031700.00W		4771 (4800)								AS1500	6300

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:

RIGHT BASE AREA

FROM

289/30 CW 019/30

TO

CASMI

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>	<u>HAT</u>			<u>HMAS</u>					
<u>OBSTRUCTION</u>	<u>COORDINATES</u>		<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
7.TREE	393636.00N/1032930.00W		5366	500	125	5E	2000				AT2634	10000
8.TERRAIN	393636.00N/1032930.00W		5266 (5300)								AS1500	6800

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:



INITIAL

FROM

FENGA

TO

KUKMY

RNP	DISTANCE	PAT	MAP	HAT	HMAS							
	10.00											
OBSTRUCTION	COORDINATES	ELEV MSL	HORZ	VERT	AC	ROC	OCS	CG	CGTA	ADJUSTMENTS	MIN ALT	
9.AAO	401857.00N/1032145.00W	4708	500	125	5E	1000				AT1792	7500	
10.TERRAIN	401857.00N/1032145.00W	4508 (4500)								AS1500	6000	

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:

INITIAL

FROM

CASMI

TO

KUKMY

RNP	DISTANCE	PAT	MAP	HAT	HMAS							
	10.00											
OBSTRUCTION	COORDINATES	ELEV MSL	HORZ	VERT	AC	ROC	OCS	CG	CGTA	ADJUSTMENTS	MIN ALT	
11.AAO	400948.00N/1033230.00W	4728	500	125	5E	1000				AT1772	7500	
12.TERRAIN	400948.00N/1033230.00W	4528 (4500)								AS1500	6000	

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:



RF CENTER FIX/DISTANCERF CENTER FIX/DISTANCE

QUALITY
10
CHECKED

FINAL: LNAV/VNAV

FROM

ADEWU

TO

DA

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>	<u>HAT</u>			<u>HMAS</u>					
	4.80		DA		250							
<u>OBSTRUCTION</u>	<u>COORDINATES</u>		<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
16.POLE (08-022019)	401037.11N/1031440.13W		4758	20	3	1A		23.19:1				4966

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:

FINAL: LNAV

FROM

ADEWU

TO

RW11

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>	<u>HAT</u>			<u>HMAS</u>					
	4.80		RW11			304						
<u>OBSTRUCTION</u>	<u>COORDINATES</u>		<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
16.POLE (08-022019)	401037.11N/1031440.13W		4758	20	3	1A	250					5020

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:



TO
P-9

PAT
P-9

HMAS

COMPUTATIONS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

MISSED APPROACH : LPV

TO
JUBOS

PAT

HMAS
4777

COMPUTATIONS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:



MISSED APPROACH : LNAV/VNAV

FROM

DA

TO

JUBOS

RNP	DISTANCE	PAT	MAP	HAT			HMAS				
							4805				
OBSTRUCTION	COORDINATES	ELEV MSL	HORZ	VERT	AC	ROC	OCS	CG	CGTA	ADJUSTMENTS	MIN ALT
							ASC				7500
19.ELEVATOR (08-074765)	400925.47N/1031212.66W	4822	20	3	1A	1000					5900
20.TERRAIN	400709.00N/1030936.00W	4594 (4600)								AS1500	6100

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:

MISSED APPROACH : LNAV

FROM

RW11

TO

JUBOS

RNP	DISTANCE	PAT	MAP	HAT			HMAS				
							4920				
OBSTRUCTION	COORDINATES	ELEV MSL	HORZ	VERT	AC	ROC	OCS	CG	CGTA	ADJUSTMENTS	MIN ALT
							ASC				7500
19.ELEVATOR (08-074765)	400925.47N/1031212.66W	4822	20	3	1A	1000					5900
20.TERRAIN	400709.00N/1030936.00W	4594 (4600)								AS1500	6100

COMPUTATIONS	ALT	KIAS	KTAS	HAA	VKTW	TR	BA	DTA	COURSE CHANGE	DVEB	VEB OCS	RF CENTER FIX/DISTANCE
--------------	-----	------	------	-----	------	----	----	-----	---------------	------	---------	------------------------

SEGMENT REMARKS:



AIRPORT

COLORADO PLAINS RGNL

AIRPORT ID

KAKO

PROCEDURE NAME

RNAV (GPS) RWY 11

AMDT NO.

2A

CITY

AKRON

STATE

CO

AIRPORT ELEVATION

4716

FACILITY

RNAV

CIRCLING

☐ ALL CATS

☒ CAT A

☒ CAT B

☒ CAT C

☒ CAT D

☐ CAT E

☐ NOT AUTHORIZED

OBSTRUCTION	COORDINATES	RADIUS	HAA	ELEV MSL	HORZ	VERT	AC	ROC	OCS	ADJUSTMENTS	MIN ALT
CATEGORY A											
19.ELEVATOR (08-074765)	400925.47N/1031212.66W	1.39	424	4822	20	3	1A	300			5140
CATEGORY B											
21.ANTENNA (08-074745)	400954.15N/1031551.84W	1.98	544	4952	20	10	1A	300			5260
CATEGORY C											
22.TOWER (08-000379)	400856.00N/1031707.00W	3.14	704	5062	500	50	5D	300		AC50	5420
CATEGORY D											
22.TOWER (08-000379)	400856.00N/1031707.00W	4.11	704	5062	500	50	5D	300		AC50	5420

CIRCLING REMARKS:

CENTERRADIUS

MSA REMARKS:

NOTES/EXPLANATIONS FROM PROCEDURE SEGMENTS:

USED 20 FT TREE HEIGHT WITHIN AAO EXEMPT AREA PER FPT, 100 FT VEGETATION OUTSIDE AAO EXEMPT AREA FOR MOUNTAINOUS ROC REDUCTION.

TAA DEVELOPED PER ATC REQUEST.

VISIBILITY LIMITED TO 1 MILE DUE TO LACK OF FULL LENGTH PARALLEL TAXIWAY.

TCH 54.1 USED TO MITIGATE OCS PENETRATIONS.

- RD (N) KAKOT0282
- RD (N) KAKOT0277
- RD (N) KAKOT0281
- RD (N) KAKOT0279
- RD (N) KAKOT0278
- RD (N) KAKOT0283
- RD (N) KAKOT0276
- ROAD (N) KAKO0006
- ROAD (N) KAKO0005



<u>AIRPORT</u>	<u>AIRPORT ID</u>	<u>PROCEDURE NAME</u>	<u>AMDT NO.</u>	<u>CITY</u>	<u>STATE</u>	<u>AIRPORT ELEVATION</u>	<u>FACILITY</u>
COLORADO PLAINS RGNL	KAKO	RNAV (GPS) RWY 11	2A	AKRON	CO	4716	RNAV



FACILITY
RNAV

"VISUAL PORTION OF FINAL" PENETRATIONS

Final Type	LPV, LNAV/VNAV, LNAV		
34:1			
4745 TRAVERSE_WAY (08-027162) 401052.51N/1031411.44W (4.53)		4741 TRAVERSE_WAY (08-025978) 401051.19N/1031411.51W (2.31)	
4745 TRAVERSE_WAY (08-027152) 401055.53N/1031411.36W (0.29)			

HELICOPTER 'VISUAL PORTION OF FINAL' PENETRATIONS

and/or
5280-FT "PROCEED VFR" SEGMENT LEVEL SURFACE AREA PENETRATIONS

PART C: GENERAL REMARKS:
PRECIPITOUS TERRAIN EVALUATION COMPLETED.

ORDER 8260.3, VOLUME 1, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED.



<u>AIRPORT</u> COLORADO PLAINS RGNL	<u>AIRPORT ID</u> KAKO	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 11	<u>AMDT NO.</u> 2A	<u>CITY</u> AKRON	<u>STATE</u> CO	<u>AIRPORT ELEVATION</u> 4716	<u>FACILITY</u> RNAV
--	---------------------------	--	-----------------------	----------------------	--------------------	----------------------------------	-------------------------

PART D: AIRSPACE

DOCKET #

ALL DISTANCES TO 1/100NM; ELEVATION TO NEAREST 100 FEET; COORDINATES TO 1/100 SECOND; DEG TO 1/100 DEGREE

DISTANCE FROM	THLD	TO 1000FT POINT	2.61
WIDTH OF	FINAL	SEGMENT AT 1000FT POINT	1.20
TRUE COURSE OF	FINAL	SEGMENT CONTAINING 1000FT POINT	119.26
HIGH TERRAIN IN	FINAL	SEGMENT CONTAINING 1000FT POINT	4594
DISTANCE FROM	THLD	TO 1500FT POINT	4.40
WIDTH OF	FINAL	SEGMENT AT 1500FT POINT	1.76
TRUE COURSE OF	FINAL	SEGMENT CONTAINING 1500FT POINT	119.26
HIGH TERRAIN IN	FINAL	SEGMENT CONTAINING 1500FT POINT	4594

THRESHOLD COORDINATES (IF STR-IN)

401049.21N/1031358.61W

ARP COORDINATES

401032.30N/1031319.30W

RUNWAY APCH END AND DIST FURTHEST FROM ARP

RUNWAY 29 DISTANCE 0.58 NM

FAF COORDINATES

401310.33N/1031926.67W

FIX NAME COORDINATES

IAF FENGA: 402548.90N/1032210.98W, IAF CASMI: 400820.26N/1033455.09W, IF/IAF KUKMY: 401704.76N/1032833.86W

REMARKS

TAA RADIUS: 30NM

QUALITY
10
CHECKED

FAA Form 8260-9 / (11/16) Supersedes Previous Edition

Electronic Version

Page 12 of 13

<u>AIRPORT</u> COLORADO PLAINS RGNL	<u>AIRPORT ID</u> KAKO	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 11	<u>AMDT NO.</u> 2A	<u>CITY</u> AKRON	<u>STATE</u> CO	<u>AIRPORT ELEVATION</u> 4716	<u>FACILITY</u> RNAV
PART E: PREPARED BY							
<u>NAME</u> DAVID DANNER (APRIL SARMENTO)	<u>OFFICE</u> AJV-A421			<u>DATE</u> 03/18/2019	<u>TITLE</u> AERONAUTICAL INFORMATION SPECIALIST		

QUALITY

10

CHECKED

FAA Form 8260-9 / (11/16) Supersedes Previous Edition

Electronic Version

Page 13 of 13