

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>						<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS						TWO	LIDDS2.LIDDS	ONE	07/19/2018	
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>					
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>					

DP ROUTE DESCRIPTION:

DETROIT METROPOLITAN WAYNE COUNTY (KDTW):

TAKEOFF RWY 3L: CLIMB ON HEADING 035.71 TO INTERCEPT COURSE 069.88 TO CROSS BESST AT OR ABOVE 2500 AND AT OR BELOW 230 KIAS, THEN ON TRACK 128.00 TO CROSS SWNDL AT OR BELOW 7000, THEN ON TRACK 126.36 TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 3R: CLIMB ON HEADING 035.71 TO INTERCEPT COURSE 064.45 TO CROSS BESST AT OR ABOVE 2500 AND AT OR BELOW 230 KIAS, THEN ON TRACK 128.00 TO CROSS SWNDL AT OR BELOW 7000, THEN ON TRACK 126.36 TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 4L: CLIMB ON HEADING 035.68 TO INTERCEPT COURSE 074.28 TO CROSS BESST AT OR ABOVE 2500 AND AT OR BELOW 230 KIAS, THEN ON TRACK 128.00 TO CROSS SWNDL AT OR BELOW 7000, THEN ON TRACK 126.36 TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 4R: CLIMB ON HEADING 035.70 TO INTERCEPT COURSE 074.29 TO CROSS BESST AT OR ABOVE 2500 AND AT OR BELOW 230 KIAS, THEN ON TRACK 128.00 TO CROSS SWNDL AT OR BELOW 7000, THEN ON TRACK 126.36 TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 21L: CLIMB ON HEADING 215.72 TO INTERCEPT COURSE 184.56 TO JOELU, THEN ON TRACK 107.88 TO CROSS YIMMY AT OR BELOW 7000, THEN ON TRACK 086.49 TO CROSS HWARD AT OR BELOW 9000, THEN ON TRACK 086.75 TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 21R: CLIMB ON HEADING 215.72 TO INTERCEPT COURSE 184.92 TO JOELU, THEN ON TRACK 107.88 TO CROSS YIMMY AT OR BELOW 7000, THEN ON TRACK 086.49 TO CROSS HWARD AT OR BELOW 9000, THEN ON TRACK 086.75 TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 22L: CLIMB ON HEADING 215.71 TO INTERCEPT COURSE 179.22 TO JOELU, THEN ON TRACK 107.88 TO CROSS YIMMY AT OR BELOW 7000, THEN ON TRACK 086.49 TO CROSS HWARD AT OR BELOW 9000, THEN ON TRACK 086.75 TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 22R: CLIMB ON HEADING 215.69 TO INTERCEPT COURSE 175.77 TO JOELU, THEN ON TRACK 107.88 TO CROSS YIMMY AT OR BELOW 7000, THEN ON TRACK 086.49 TO CROSS HWARD AT OR BELOW 9000, THEN ON TRACK 086.75 TO CROSS KZLOV BETWEEN 4000 AND 1500, THENCE...

TAKEOFF RWY 27L: CLIMB ON HEADING 275.73 TO 1146, THEN ON HEADING 275.71 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 27R: CLIMB ON HEADING 275.72 TO 1146, THEN ON HEADING 275.70 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN 17000 OR AS ASSIGNED BY ATC, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

WILLOW RUN (KYIP):

TAKEOFF RWY 5L: CLIMB ON HEADING 053.71 TO 1220, THEN LEFT TURN HEADING 300.00 FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 5R: CLIMB ON HEADING 053.70 TO 1220, THEN LEFT TURN HEADING 300.00 FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 9: CLIMB ON HEADING 095.55 TO 1220, THEN LEFT TURN HEADING 300.00 FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 23L: CLIMB ON HEADING 233.72 TO 1220, THEN ON HEADING 233.70 FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 23R: CLIMB ON HEADING 233.73 TO 1220, THEN ON HEADING 233.72 FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 27: CLIMB ON HEADING 275.57 TO 1220, THEN ON HEADING 275.56 FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

ANN ARBOR MUNI (KARB):

TAKEOFF RWY 6: CLIMB ON HEADING 059.53 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 24: CLIMB ON HEADING 239.53 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS	TWO	LIDDS2.LIDDS	ONE	07/19/2018	

COLEMAN A YOUNG MUNI (KDET):

TAKEOFF RWY 7: CLIMB ON HEADING 068.30 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 15: CLIMB ON HEADING 148.32 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 25: CLIMB ON HEADING 248.31 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 33: CLIMB ON HEADING 328.33 TO 1800 THEN AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

CUSTER (KTTF):

TAKEOFF RWY 3: CLIMB ON HEADING 027.49 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 21: CLIMB ON HEADING 207.50 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

GROSSE ILE MUNI (KONZ):

TAKEOFF RWY 4: CLIMB ON HEADING 037.34 TO 1200 THEN AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 17: CLIMB ON HEADING 173.78 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 22: CLIMB ON HEADING 217.34 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 35: CLIMB ON HEADING 005.78 TO 1800 THEN AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

LIVINGSTON COUNTY SPENCER J HARDY (KOZW):

TAKEOFF RWY 13: CLIMB ON HEADING 132.35 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 31: CLIMB ON HEADING 312.36 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

OAKLAND COUNTY INTL (KPTK):

TAKEOFF RWY 9L: CLIMB ON HEADING 094.66 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 9R: CLIMB ON HEADING 094.63 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 27L: CLIMB ON HEADING 274.65 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 27R: CLIMB ON HEADING 274.68 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

OAKLAND/TROY (KVLL):

TAKEOFF RWY 9: CLIMB ON HEADING 095.71 TO 1400 THEN AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...
TAKEOFF RWY 27: CLIMB ON HEADING 275.72 TO 1500 THEN AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS	TWO	LIDDS2.LIDDS	ONE	07/19/2018	

SELFRIDGE ANGB (KMTCT):

TAKEOFF RWY 1: CLIMB ON HEADING 007.47 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 19: CLIMB ON HEADING 187.47 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

WINDSOR (CYQG):

TAKEOFF RWY 7: CLIMB ON HEADING 069.55 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 12: CLIMB ON HEADING 122.61 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 25: CLIMB ON HEADING 249.56 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

TAKEOFF RWY 30: CLIMB ON HEADING 302.60 OR AS ASSIGNED FOR RADAR VECTORS TO CROSS KZLOV BETWEEN 4000 AND 15000, THENCE...

...ON TRACK 110.95 TO LIDDS, THEN ON (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
GRIVY	LIDDS2.GRIVY	LIDDS	NOONR	TRACK 110.72	19.56	10000		
		NOONR	ZEYOU	TRACK 148.78	19.08	10000		
		ZEYOU	GRIVY	TRACK 150.65	46.33	10000		

PROCEDURAL DATA NOTES:

NOTE: RNAV 1

NOTE: RADAR REQUIRED

NOTE: DME/DME/IRU OR GPS REQUIRED.

NOTE: TURBOJET DEPARTURES AT/ABOVE 10000, MAINTAIN 280K UNTIL ADVISED BY ATC.

NOTE: KDTW/KYIP DEPARTURES: IF UNABLE TO ACCEPT 500 FT PER NM CLIMB RATE, ADVISE CLEARANCE DELIVERY ON INITIAL CONTACT.

TAKEOFF MINIMUMS:

DETROIT METROPOLITAN WAYNE COUNTY (KDTW):

RWY 3L, 3R, 4L, 4R, 21L, 21R, 22L, 22R, 27L, 27R: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1146.

WILLOW RUN (KYIP):

RWY 5L, 5R, 9, 23L, 23R, 27: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1220.

ANN ARBOR MUNI (KARB):

RWY 6, 24: STANDARD.

RWY 12, 30: NA - ENVIRONMENTAL.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS	TWO	LIDDS2.LIDDS	ONE	07/19/2018	

COLEMAN A YOUNG MUNI (KDET):

RWY 7, 15, 33: STANDARD.

RWY 25: STANDARD WITH MINIMUM CLIMB OF 210 FEET PER NM TO 1000.

CUSTER (KTTF):

STANDARD.

GROSSE ILE MUNI (KONZ):

RWY 4, 17, 22: STANDARD.

RWY 35: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1100.

LIVINGSTON COUNTY SPENCER J HARDY (KOZW):

STANDARD.

OAKLAND COUNTY INTL (KPTK):

RWY 9L, 9R, 27L, 27R: STANDARD.

RWY 18, 36: NA - ENVIRONMENTAL.

OAKLAND/TROY (KVLL):

RWY 9: STANDARD.

RWY 27: STANDARD WITH MINIMUM CLIMB OF 476 FT PER NM TO 1500.

SELFRIDGE ANGB (KMTX):

RWY 1: STANDARD.

RWY 19: STANDARD WITH MINIMUM CLIMB OF 234 FT PER NM TO 1500.

WINDSOR (CYQG):

RWY 7, 12, 25: STANDARD.

RWY 30: STANDARD WITH MINIMUM CLIMB OF 210 FT PER NM TO 1300.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

WILLOW RUN (KYIP):

RWY 27: 903 FT MSL TOWER 421431.78N/0833411.47W

COLEMAN A YOUNG MUNI (KDET):

RWY 25: 871 FT MSL STACK 422307.00N/0830235.00W

RWY 33: 1749 FT MSL TOWER 422653.00N/0831023.00W

GROSSE ILE MUNI (KONZ):

RWY 35: 1146 FT MSL STACK, 420718.61N/0831050.62W

OAKLAND/TROY (KVLL):

RWY 27: 940 FT MSL BLDG 423234.20N/0831235.50W (CG), 1749 FT MSL TOWER 422858.00N/0831219.00W (CGTA)

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS	TWO	LIDDS2.LIDDS	ONE	07/19/2018	

SELFRIDGE ANGB (KMTC):
RWY 19: 1246 FT MSL TOWER 423315.00N/0825315.00W

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:
CHART: TOP ALTITUDE: KDTW 17000
CHART: TOP ALTITUDE: ALL OTHER AIRPORTS ASSIGNED BY ATC
REFERENCE MAG VAR: KDTW 7W/2020
DME/DME ASSESSMENT: SAT (RNP 2.0)
KDTW CHART: SEE ADDITIONAL REQUIREMENTS IN RNAV DEPARTURE AAUP.

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
DETROIT METROPOLITAN WAYNE COUNTY (KDTW)	DETROIT	MI
WILLOW RUN (KYIP)	DETROIT	MI
ANN ARBOR MUNI (KARB)	ANN ARBOR	MI
COLEMAN A YOUNG MUNI (KDET)	DETROIT	MI
CUSTER (KTTF)	MONROE	MI
GROSSE ILE MUNI (KONZ)	DETROIT/GROSSE ILE	MI
LIVINGSTON COUNTY SPENCER J HARDY (KOZW)	HOWELL	MI
OAKLAND COUNTY INTL (KPTK)	PONTIAC	MI
OAKLAND/TROY (KVLL)	TROY	MI
SELFRIDGE ANGB (KMTC)	MOUNT CLEMENS	MI
WINDSOR (CYQG)	WINDSOR, ONTARIO, CANADA	

COMMUNICATIONS:
ATIS, AWOS/ASOS, CLNC DEL, GND CON, TWR, CTAF, DEP CON, CPDLC



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS	TWO	LIDDS2.LIDDS	ONE	07/19/2018	

FIXES AND/OR NAVAIDS:

REMARKS:

MOCA(S) NOT CHARTED PER ATC REQUEST TO REDUCE CHART CLUTTER.

CHANGES TO THIS PROCEDURE MUST BE COORDINATED WITH NAVCANADA, AERONAUTICAL INFORMATION MANAGEMENT (AIM), AIMDATA@NAVCANADA.CA (CURRENT POC IS CHARLES SIMARD, 613-248-3819, SIMACHA@NAVCANADA.CA).

FLIGHT INSPECTED BY:

BRYAN VEIT

<i>Digitally signed by</i>	<u>OFFICE SYMBOL:</u>	<u>DATE:</u>
WARDELL HENNING	FICO	06/05/2019
Jun 27, 2019		

DEVELOPED BY:
CHRISTINE BAYSE

Digitally signed by
CHRISTINE BAYSE
Jun 27, 2019

<u>OFFICE SYMBOL:</u>	<u>DATE:</u>
AJV-A432	03/11/2019

APPROVED BY:
LONNIE EVERHART

Digitally signed by
WARDELL HENNING
Jun 27, 2019

<u>OFFICE SYMBOL:</u>	<u>DATE:</u>
AJV-A430	

REQUIRED EFFECTIVE DATE:
ROUTINE

COORDINATED WITH:

<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:

ZOB, DTW APP CON, AMGR

CHANGES - REASONS:

1. CHANGED TOP ALTITUDE FOR KDTW TO 17000.- INDUSTRY REQUEST TO REDUCE CONFUSION.
2. CHANGED DEPARTURE ROUTE DESCRIPTION FOR KDTW FROM "MAINTAIN ATC ASSIGNED ALTITUDE" TO "MAINTAIN 17000 OR AS ASSIGNED BY ATC".- INDUSTRY REQUEST TO REDUCE CONFUSION.
3. MOVE JOELU 1.38 NM NORTH. - DECONFLICT FROM OTHER PROCEDURES.
4. REMOVE ALTITUDE RESTRICTION AT JOELU. - DECONFLICT FROM OTHER PROCEDURES.
5. ADD YIMMY WITH AT OR BELOW 7000 RESTRICTION. - DECONFLICT FROM OTHER PROCEDURES.
6. ADD HWARD WITH AT OR BELOW 9000 RESTRICTION. -DECONFLICT FROM OTHER PROCEDURES.
7. ADD TF LEGS JOELU-YIMMY, YIMMY-HWARD, HWARD-KZLOV. - DECONFLICT FROM OTHER PROCEDURES.
8. REPLACE LAZYI WITH SWNDL AND MOVE 1 NM SOUTHEAST. - DECONFLICT FROM OTHER PROCEDURES.
9. MOVE NOONR 1.12 NM NORTHWEST AND MOTIFIED COURSE AND DISTANCE ON ENROUTE TRANSITIONS SEGMENTS LIDDS TO NOONR AND NOONR TO ZEYOU. - CORRECT CRITERIA FAILURE.
10. CHANGE ALL VI LEGS TO MINIMUM ALLOWABLE LENGTH. - REDUCE DRIFT ON INITIAL CLIMBOUT.
11. MOVE BESST 0.70 NM NE. - REDUCE DRIFT ON INITIAL CLIMBOUT.
12. ADD AT OR ABOVE 2500 AND AT OR BELOW 230 KIAS RESTRICTIONS AT BESST. - REDUCE DRIFT ON INITIAL CLIMBOUT.
13. ADD CHART NOTE: KDTW/KYIP DEPARTURES: IF UNABLE TO ACCEPT 500 FT PER NM CLIMB RATE, ADVISE CLEARANCE DELIVERY ON INITIAL CONTACT.- ENSURE PILOTS ARE AWARE OF REQUIREMENTS.
14. ADD KDTW CHART: SEE ADDITIONAL REQUIREMENTS IN RNAV DEPARTURE AAUP. - ENSURE PILOTS ARE AWARE OF REQUIREMENTS.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS	TWO	LIDDS2.LIDDS	ONE	07/19/2018	
15. UPDATED DP ROUTE DESCRIPTION KDTW RWY 3L INTERCEPT COURSE FROM "079.50 TO BESST" TO "069.88 TO CROSS BESST". - BESST MOVED AND VI-CF MINIMUM.					
16. UPDATED DP ROUTE DESCRIPTION KDTW RWY 3R INTERCEPT COURSE FROM "071.65 TO BESST" TO "064.45 TO CROSS BESST". - BESST MOVED AND VI-CF MINIMUM.					
17. UPDATED DP ROUTE DESCRIPTION KDTW RWY 4L INTERCEPT COURSE FROM "082.75 TO BESST" TO "074.28 TO CROSS BESST". - BESST MOVED AND VI-CF MINIMUM.					
18. UPDATED DP ROUTE DESCRIPTION KDTW RWY 4R INTERCEPT COURSE FROM "084.25 TO BESST" TO "074.29 TO CROSS BESST". - BESST MOVED AND VI-CF MINIMUM.					
19. UPDATED DP ROUTE DESCRIPTION KDTW RWY 3L, 3R, 4L AND 4R FROM "ON TRACK 123.33 TO CROSS LAZYI... ON TRACK 126.35 TO CROSS KZLOV..." TO "ON TRACK 128.00 TO CROSS SWNDL... ON TRACK 126.36 TO CROSS KZLOV".- LAZYI CHANGED TO SWNDL AND MOVED.					
20. UPDATED DP ROUTE DESCRIPTION KDTW RWY 21L INTERCEPT COURSE FROM "180.43 TO CROSS JOELU" TO "184.56 TO JOELU".- JOELU MOVED AND VI-CF MINIMUM.					
21. UPDATED DP ROUTE DESCRIPTION KDTW RWY 21R INTERCEPT COURSE FROM "181.07 TO CROSS JOELU" TO "184.92 TO JOELU". - JOELU MOVED AND VI-CF MINIMUM.					
22. UPDATED DP ROUTE DESCRIPTION KDTW RWY 22L INTERCEPT COURSE FROM "175.62 TO CROSS JOELU" TO "179.22 TO JOELU". - JOELU MOVED AND VI-CF MINIMUM.					
23. UPDATED DP ROUTE DESCRIPTION KDTW RWY 22R INTERCEPT COURSE FROM "172.38 TO CROSS JOELU" TO "175.77 TO JOELU".- JOELU MOVED AND VI-CF MINIMUM.					
24. UPDATED DP ROUTE DESCRIPTION KDTW RWY 27L AND 27R FROM "1160" TO "1146". - UPDATED CLIMB GRADIENT TERMINATION ALTITUDE.					
25. UPDATED TAKEOFF MINIMUMS KDTW FROM "RWY 3L, 3R, 4L, 4R, 21L, 21R, 22L, 22R: STANDARD" AND "RWY 27L, 27R: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1160" TO "RWY 3L, 3R, 4L, 4R, 21L, 21R, 22L, 22R, 27L, 27R: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1146". - ALL RUNWAYS ARE 500 FT PER NM TO 500 FT ABOVE FOR LNAV ENGAGEMENT.					
26. UPDATED RECOMMENDED NAVAID FROM AIR VOR/DME TO ECK TACAN ON 8260-15C. - NAVAID CLOSER TO AIRPORT.					

06/27/19: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 06/11/19.

1. CHANGED TRANSITION COMPUTER CODE FROM "LIDDS1.GRIVY" TO "LIDDS2.GRIVY".



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS		TWO		LIDDS2.LIDDS		ONE		07/19/2018	
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
DETROIT METROPOLITAN WAYNE COUNTY (KDTW)									
RW03L (AER)	421228.21N/0832104.39W	N	-	-	-	-			
-	421436.02N/0831930.16W	-	-	VI	028.71	2.43			CG 500 FT/NM TO 1146
BESST	421656.69N/0831321.04W	Y	FB	CF	062.88	5.13	AT/ABOVE 2500	AT/BELOW 230K	RECOMMENDED NAVAID: ECK TACAN
SWNDL	421255.80N/0830422.44W	Y	FB	TF	121.00	7.78	AT/BELOW 7000		
KZLOV	420424.81N/0824407.44W	Y	FB	TF	119.36	17.30	4000B15000		
RW03R (AER)	421144.21N/0832106.49W	N	-	-	-	-			
-	421404.99N/0831922.74W	-	-	VI	028.71	2.67			CG 500 FT/NM TO 1146
BESST	421656.69N/0831321.04W	Y	FB	CF	057.45	5.31	AT/ABOVE 2500	AT/BELOW 230K	RECOMMENDED NAVAID: ECK TACAN
SWNDL	421255.80N/0830422.44W	Y	FB	TF	121.00	7.78	AT/BELOW 7000		
KZLOV	420424.81N/0824407.44W	Y	FB	TF	119.36	17.30	4000B15000		
RW04L (AER)	421207.82N/0832302.40W	N	-	-	-	-			
-	421427.53N/0832119.54W	-	-	VI	028.68	2.65			CG 500 FT/NM TO 1146
BESST	421656.69N/0831321.04W	Y	FB	CF	067.28	6.42	AT/ABOVE 2500	AT/BELOW 230K	RECOMMENDED NAVAID: ECK TACAN
SWNDL	421255.80N/0830422.44W	Y	FB	TF	121.00	7.78	AT/BELOW 7000		
KZLOV	420424.81N/0824407.44W	Y	FB	TF	119.36	17.30	4000B15000		
RW04R (AER)*	421212.78N/0832213.32W*	N	-	-	-	-			*DISPL THLD (509 FT)
-	421446.08N/0832020.37W	-	-	VI	028.70	2.91			CG 500 FT/NM TO 1146
BESST	421656.69N/0831321.04W	Y	FB	CF	067.29	5.63	AT/ABOVE 2500	AT/BELOW 230K	RECOMMENDED NAVAID: ECK TACAN



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
LIDDS							TWO	LIDDS2.LIDDS	ONE	07/19/2018	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED		REMARKS	
SWNDL	421255.80N/0830422.44W	Y	FB	TF	121.00	7.78	AT/BELOW 7000				
KZLOV	420424.81N/0824407.44W	Y	FB	TF	119.36	17.30	4000B15000				
RW21L (AER)	421310.86N/0832002.65W	N	-	-	-	-					
-	421050.18N/0832146.27W	-	-	VI	208.72	2.67				CG 500 FT/NM TO 1146	
JOELU	420213.33N/0832116.60W	Y	FB	CF	177.56	8.62				RECOMMENDED NAVAID: ECK TACAN	
YIMMY	420046.57N/0831114.47W	Y	FB	TF	100.88	7.62	AT/BELOW 7000				
HWARD	420130.79N/0830553.79W	Y	FB	TF	079.49	4.05	AT/BELOW 9000				
KZLOV	420424.81N/0824407.44W	Y	FB	TF	079.75	16.48	4000B15000				
RW21R (AER)	421341.85N/0832010.12W	N	-	-	-	-					
-	421134.48N/0832143.96W	-	-	VI	208.72	2.42				CG 500 FT/NM TO 1146	
JOELU	420213.33N/0832116.60W	Y	FB	CF	177.92	9.35				RECOMMENDED NAVAID: ECK TACAN	
YIMMY	420046.57N/0831114.47W	Y	FB	TF	100.88	7.62	AT/BELOW 7000				
HWARD	420130.79N/0830553.79W	Y	FB	TF	079.49	4.05	AT/BELOW 9000				
KZLOV	420424.81N/0824407.44W	Y	FB	TF	079.75	16.48	4000B15000				
RW22L (AER)	421352.37N/0832059.97W	N	-	-	-	-					
-	421114.77N/0832256.02W	-	-	VI	208.71	2.99				CG 500 FT/NM TO 1146	
JOELU	420213.33N/0832116.60W	Y	FB	CF	172.22	9.10				RECOMMENDED NAVAID: ECK TACAN	
YIMMY	420046.57N/0831114.47W	Y	FB	TF	100.88	7.62	AT/BELOW 7000				
HWARD	420130.79N/0830553.79W	Y	FB	TF	079.49	4.05	AT/BELOW 9000				

QUALITY

18



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS		TWO		LIDDS2.LIDDS		ONE		07/19/2018	
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
KZLOV	420424.81N/0824407.44W	Y	FB	TF	079.75	16.48	4000B15000		
RW22R (AER)	421334.48N/0832158.61W	N	-	-	-	-			
-	421115.08N/0832341.20W	-	-	VI	208.69	2.65			CG 500 FT/NM TO 1146
JOELU	420213.33N/0832116.60W	Y	FB	CF	168.77	9.20			RECOMMENDED NAVAID: ECK TACAN
YIMMY	420046.57N/0831114.47W	Y	FB	TF	100.88	7.62	AT/BELOW 7000		
HWARD	420130.79N/0830553.79W	Y	FB	TF	079.49	4.05	AT/BELOW 9000		
KZLOV		Y	FB	TF	079.75	16.48	4000B15000		
RW27L (AER)	421158.34N/0831949.33W	N	-	-	-	-			
1146 MSL	-	-	-	VA	268.73	-			CG 500 FT/NM TO 1146
-	-	-	-	VM	268.71	-			
RW27R (AER)	421303.02N/0831951.72W	N	-	-	-	-			
1146 MSL	-	-	-	VA	268.72	-			CG 500 FT/NM TO 1146
-	-	-	-	VM	268.70	-			
WILLOW RUN (KYIP)									
RW05L (AER)	421355.86N/0833230.06W	N	-	-	-	-			
1220 MSL	-	-	-	VA	046.71	-			CG 500 FT/NM TO 1220
-	-	-	-	VM	293.00	-			LEFT TURN

QUALITY
18
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		EFFECTIVE DATE	
LIDDS		TWO		LIDDS2.LIDDS		ONE		07/19/2018			
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS		
RW05R (AER)	421350.25N/0833223.46W	N	-	-	-	-					
1220 MSL	-	-	-	VA	046.70	-			CG 500 FT/NM TO 1220		
-	-	-	-	VM	293.00	-			LEFT TURN		
RW09 (AER)*	421438.37N/0833228.33W*	N	-	-	-	-			*DISPL THLD (576 FT)		
1220 MSL	-	-	-	VA	088.55	-			CG 500 FT/NM TO 1220		
-	-	-	-	VM	293.00	-			LEFT TURN		
RW23L (AER)	421441.34N/0833110.47W	N	-	-	-	-					
1220 MSL	-	-	-	VA	226.72	-			CG 500 FT/NM TO 1220		
-	-	-	-	VM	226.70	-					
RW23R (AER)	421436.47N/0833132.03W	N	-	-	-	-					
1220 MSL	-	-	-	VA	226.73	-			CG 500 FT/NM TO 1220		
-	-	-	-	VM	226.72	-					
RW27 (AER)	421440.03N/0833059.06W	N	-	-	-	-					
1220 MSL	-	-	-	VA	268.57	-			CG 500 FT/NM TO 1220		
-	-	-	-	VM	268.56	-					

QUALITY
18
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
LIDDS		TWO		LIDDS2.LIDDS		ONE		07/19/2018	
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
KZLOV	420424.81N/0824407.44W	Y	-	IF	-	-	4000B15000		
LIDDS	420154.21N/0823038.74W	Y	FB	TF	103.95	10.35			
LIDDS	420154.21N/0823038.74W	Y	-	IF	-	-			LIDDS2.GRIVY
NOONR	415712.96N/0820511.04W	Y	FB	TF	103.72	19.56			
ZEYOU	414212.20N/0814925.71W	Y	FB	TF	141.78	19.08			
GRIVY	410446.28N/0811306.60W	Y	FB	TF	143.65	46.33			

